




**CITY OF WAUWATOSA  
CONTRACT 24-02  
116TH STREET PARK  
CITY PROJECT #8045  
SIGMA PROJECT #21231**

SHEET NO.	DESCRIPTION
C 001	SITE SURVEY
C 002	EROSION CONTROL AND SITE PREPARATION PLAN
C 100	OVERALL SITE PLAN
C 200	GRADING PLAN
C 201	DETAILED GRADING PLAN
C 202	DETAILED GRADING PLAN
C 300	UTILITY PLAN
C 400	EROSION CONTROL DETAILS
C 401	PAVING DETAILS
C 402	UTILITY DETAILS
C 403	SITE DETAILS
C 404	GI CROSS SECTION DETAIL
C 500-502	SPECIFICATIONS



**PROJECT COORDINATION:**  
ALEX KRUTSCH  
PARKS & FORESTRY SUPERINTENDENT  
(414) 471-8422  
AKRUTSCH@WAUWATOSA.NET

**THE SIGMA GROUP:**  
CHRISTOPHER CARR, PE  
VICE PRESIDENT  
(414) 643-4163  
CCARR@THESIGMAGROUP.COM

**SITE DESIGN LANDSCAPE ARCHITECTURE:**  
BRENDA KIESGEN  
PROJECT MANAGER  
(708) 691-0601  
BKIESGEN@SITE-DESIGN.COM

**IBC ENGINEERING SERVICES:**  
COLLEEN HOFFMANN, PE  
ELECTRICAL ENGINEER  
(262) 522-4423  
COLLEENH@IBCENGINEERING.COM

site

SHEET NO.	DESCRIPTION
L002	OVERALL SITE PLAN (FOR REFERENCE ONLY)
L003	GENERAL NOTES
L008	TREE PRESERVATION AND DEMOLITION PLAN
L101	LANDSCAPE SITE PLAN
L101A.1	LANDSCAPE SITE PLAN ENLARGEMENT
L101A.2	LANDSCAPE PLAN ENLARGEMENT
L102A.2	PLAYGROUND GRADING PLAN ENLARGEMENT
L103A.1	HARDSCAPE PLAN ENLARGEMENT
L103A.2	HARDSCAPE PLAN ENLARGEMENT
L104A.1	SITE FURNISHINGS PLAN ENLARGEMENT
L104A.2	PLAYGROUND EQUIPMENT ENLARGEMENT PLAN (FOR REFERENCE ONLY)
L105	SOILS PLAN
L106	PLANTING PLAN
L106A	PLANTING PLAN ENLARGMENT
L106B	PLANTING PLAN ENLARGMENT
L106C	PLANTING PLAN ENLARGMENT
L106A.1	PLANTING PLAN ENLARGMENT
L106A.2	PLANTING PLAN ENLARGMENT
L501	PRESERVATION AND DEMOLITION DETAILS
L503	HARDSCAPE DETAILS
L503A	HARDSCAPE DETAILS
L503B	HARDSCAPE DETAILS
L503C	HARDSCAPE DETAILS
L503D	HARDSCAPE DETAILS
L503E	HARDSCAPE DETAILS
L504	SITE FURNISHING DETAILS
L504A	SITE STRUCTURES
L504B	PLAYGROUND DETAILS
L504C	PLAYGROUND FURNISHING RENDERINGS (FOR REFERENCE ONLY)
L506	PLANTING DETAILS
L506A	PLANTING DETAILS
L603	HARDSCAPE SCHEDULE
L604	SITE FURNISHING SCHEDULE
L606	PLANTING SCHEDULE
L1000	IRRIGATION PLAN



SHEET NO.	DESCRIPTION
E 000	LEGEND AND NOTES
E 100	ELECTRICAL SITE PLANS
E 500	ELECTRICAL SCHEDULES

APPROVED BY THE BOARD OF PUBLIC WORKS OF THE CITY OF WAUWATOSA, WISCONSIN BY RESOLUTION ADOPTED:

DATE \_\_\_\_\_ CITY CLERK \_\_\_\_\_  
SUBMITTED FOR APPROVAL:  
**JANUARY 5, 2024**  
DATE \_\_\_\_\_ CITY ENGINEER  
REG. PROF. ENGR. \_\_\_\_\_



**CITY OF WAUWATOSA  
ENGINEERING SERVICES DIVISION**

**116TH STREET PARK**

**1900 N. 116TH STREET**

SCALE: AS NOTED

SHEETS:



- LEGEND:**
- SECTION 1/4 SECTION LINE
  - PROPERTY LINE
  - X- EASEMENT
  - X- CHAIN LINK FENCE
  - X- TREE LINE
  - OH --- OVERHEAD UTILITY LINE
  - E --- ELECTRIC
  - TEL --- TELEPHONE
  - FO --- FIBER OPTIC
  - CTV --- CABLE TV
  - SAN --- SANITARY SEWER
  - FM --- FORCE MAIN
  - ST --- STORM SEWER
  - W --- WATER MAIN
  - G --- GAS
  - 670 --- EXISTING CONTOUR
  - WET --- WETLAND
  - FP --- FLOODPLAIN
- 
- MANHOLE
  - ⊕ CATCH BASIN
  - CATCH BASIN (ROUND)
  - ⊙ ROOF DRAIN
  - ⊕ HYDRANT
  - ⊕ WATER VALVE
  - ⊕ GAS VALVE
  - ⊕ UTILITY POLE
  - ⊕ GUY WIRE
  - ⊕ GAS METER
  - ⊕ ELECTRIC METER
  - ⊕ UTILITY PEDESTAL
  - ⊕ TRAFFIC SIGNAL
  - ⊕ LIGHT POLE
  - ⊕ SOIL BORING
  - ⊕ MONITORING WELL
  - IRON PIPE FOUND/SET
  - REBAR FOUND/SET
  - ⊗ CHISELED CROSS FOUND/SET
  - ⊕ PK NAIL FOUND/SET
  - SPIKE/NAIL
  - ⊕ MONUMENT
  - ⊕ BENCHMARK
  - ⊕ SIGN
  - DECIDUOUS TREE
  - ⊕ CONIFEROUS TREE
  - BUSH
  - ⊕ POST

DRAWING IS BASED ON FIELD LOCATIONS AND/OR RECORDS FURNISHED BY MUNICIPALITIES AND UTILITY COMPANIES. THE LOCATION AND ACCURACY OF WHICH CANNOT BE GUARANTEED. THERE MAY BE ADDITIONAL UNDERGROUND UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.

2. VERIFY ACTUAL LOCATIONS AND INVERTS IN THE FIELD. ANY POTENTIAL ERRORS, OMISSIONS, OR DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
3. DRAWING IS BASED ON FIELD SURVEY COMPLETED BY THE CITY OF WAUWATOSA ON OCTOBER 2022.
4. DATUM FOR THE PROJECT SURVEY IS WAUWATOSA DATUM.
5. CONTRACTOR TO VERIFY EXISTING CONDITIONS, CONTACT ENGINEER WITH DISCREPANCIES.
6. PRIVATE CONSTRUCTION THAT DISTURBS UNDERGROUND UTILITIES IS REQUIRED TO INSTALL AND MAINTAIN ENCLOSED RAT TRAPS OR BAIT STATIONS.

THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS MAP IS BASED ON FIELD MARKINGS AND INFORMATION FURNISHED BY UTILITY COMPANIES AND THE LOCAL MUNICIPALITY. WHILE THIS INFORMATION IS BELIEVED TO BE RELIABLE, ITS ACCURACY AND COMPLETENESS CANNOT BE GUARANTEED.




CALL DIGGERS' HOTLINE  
1-800-242-8511  
TOLL FREE  
MS STATUTE 182.07(2)(974)  
REQUIRES 48 HOURS NOTICE BEFORE YOU EXCAVATE  
MILW. AREA 259-1181


DATE	DESCRIPTION

 <b>CITY OF WAUWATOSA</b> ENGINEERING SERVICES DIVISION	
 <b>SIGMA GROUP</b> Single Source. Sound Solutions.	
 <b>site</b>	
<b>SITE SURVEY</b> 1900 N 116TH STREET WAUWATOSA, WI 53226	
CONTRACT NO.: 21231 FILE NO.: JRG DRAWN BY: CTC CHECKED BY: AS SHOWN SCALE:	<b>C001</b>



- LEGEND:**
- PROPOSED SILT FENCE
  - PROPOSED INLET PROTECTION
  - PROPOSED TRACKING PAD
  - PROPOSED EROSION MATTING WISDOT APPROVED CLASS 1 TYPE B
  - PROPOSED TREE PROTECTION FENCE (SEE SHEET L501)
  - PAVEMENT REMOVAL
  - EXISTING CONTOUR
  - PROPOSED CONTOUR
  - CURB REMOVAL
  - STRUCTURE REMOVAL



- GENERAL NOTES:**
- THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS DRAWING IS BASED ON FIELD LOCATIONS AND/OR RECORDS FURNISHED BY MUNICIPALITIES AND UTILITY COMPANIES. THE LOCATION AND ACCURACY OF WHICH CANNOT BE GUARANTEED. THERE MAY BE ADDITIONAL UNDERGROUND UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.
  - VERIFY ACTUAL LOCATIONS AND INVERTS IN THE FIELD. ANY POTENTIAL ERRORS, OMISSIONS, OR DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
  - WORK TO BE COMPLETED IS INDICATED IN BOLD TYPE LINES AND EXISTING CONDITIONS ARE INDICATED BY LIGHT TYPE LINES.
  - ELECTRONIC CIVIL FILES ARE AVAILABLE UPON WRITTEN REQUEST. DO NOT USE ELECTRONIC CIVIL FILES TO LAYOUT FOUNDATIONS, COLUMN LINES, LIGHT POLES, OR OTHER NON CIVIL SITE WORK. REFER TO ARCHITECTURAL DRAWINGS FOR DIMENSIONS OF BUILDING AND ARCHITECTURAL FEATURES.
  - SEE SHEET C400 FOR A COMPLETE LIST OF EROSION CONTROL NOTES AND DETAILS. EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO START OF LAND DISTURBING ACTIVITIES.
  - DO NOT BEGIN LAND DISTURBING ACTIVITIES UNTIL AN EROSION CONTROL PERMIT IS OBTAINED FROM LOCAL JURISDICTION.
  - PRIVATE CONSTRUCTION THAT DISTURBS UNDERGROUND UTILITIES IS REQUIRED TO INSTALL AND MAINTAIN ENCLOSED RAT TRAPS OR BAIT STATIONS.


THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS MAP IS BASED ON FIELD MARKINGS AND INFORMATION FURNISHED BY UTILITY COMPANIES AND THE LOCAL MUNICIPALITY. WHILE THIS INFORMATION IS BELIEVED TO BE RELIABLE, ITS ACCURACY AND COMPLETENESS CANNOT BE GUARANTEED.



CALL DIGGERS HOTLINE  
1-800-242-8511  
TOLL FREE


WI STATUTE 182.012(1)(174)  
REQUIRES MIN. 3 WORK DAYS  
NOTICE BEFORE YOU DIG/PAVE  
MILW. AREA 259-1181

CONTRACT:	21231	DESCRIPTION:	
FILE NO.:	JRG	DATE:	
DRAWN BY:	CTC		
CHECKED BY:	AS SHOWN		
SCALE:			
<b>EROSION CONTROL PLAN</b>		<b>CITY OF WAUWATOSA</b>	
1900 N 116TH STREET		ENGINEERING DIVISION	
WAUWATOSA, WI 53226			
<b>C002</b>			



**LEGEND:**


- 5' THICK CONCRETE WALK (A C401)
- POROUS ASPHALT PATH (INTERIOR) (G C401)
- POROUS ASPHALT PATH (EXTERIOR) (H C401)
- 
- EXISTING WETLAND TO REMAIN PRESERVE AND PROTECT
- CHAIN LINK FENCE
- LIGHT POLE (SEE LIGHTING PLANS)
- 



SITE INFORMATION			
SITE AREA	521611	11.975 AC	
SITE DISTURBED AREA	372576	8.553 AC	
EXISTING IMPERVIOUS AREA	1590	0.037 AC	0.3 %
EXISTING PERVIOUS AREA	370986	8.517 AC	99.6 %
PROPOSED IMPERVIOUS AREA	90710	2.082 AC	24.3 %
PROPOSED PERVIOUS AREA	280276	6.434 AC	75.2 %
ADA PARKING SPACES	4		
BIKE PARKING SPACES	9		

NOTE: ALL PAVEMENT MARKINGS ARE TO BE 3 INCH WIDE STRIPES OF WHITE OR YELLOW PAINT.

- GENERAL NOTES:**
- THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS DRAWING IS BASED ON FIELD LOCATIONS AND/OR RECORDS FURNISHED BY MUNICIPALITIES AND UTILITY COMPANIES. THE LOCATION AND ACCURACY OF WHICH CANNOT BE GUARANTEED. THERE MAY BE ADDITIONAL UNDERGROUND UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.
  - VERIFY ACTUAL LOCATIONS AND INVERTS IN THE FIELD. ANY POTENTIAL ERRORS, OMISSIONS, OR DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
  - WORK TO BE COMPLETED IS INDICATED IN BOLD TYPE LINES AND EXISTING CONDITIONS ARE INDICATED BY LIGHT TYPE LINES.
  - ELECTRONIC CIVIL FILES ARE AVAILABLE UPON WRITTEN REQUEST. DO NOT USE ELECTRONIC CIVIL FILES TO LAYOUT FOUNDATIONS, COLUMN LINES, LIGHT POLES, OR OTHER NON CIVIL SITE WORK. REFER TO ARCHITECTURAL DRAWINGS FOR DIMENSIONS OF BUILDING AND ARCHITECTURAL FEATURES.
  - DIMENSIONS ARE FROM FACE OF CURB OR EDGE OF PAVEMENT.
  - WORK WITHIN THE PUBLIC RIGHT OF WAY, INCLUDING BUT NOT LIMITED TO DRIVEWAY OPENINGS, SIDEWALK AND RAMPS, PAVING, AND CURB AND GUTTER SHALL BE COMPLETED PER MUNICIPAL AND/OR COUNTY REQUIREMENTS AND STANDARDS.
  - EARTHWORK SHALL BE IN ACCORDANCE WITH GEOTECHNICAL ENGINEER'S RECOMMENDATIONS.



CALL DIGGERS HOTLINE  
1-800-242-8511  
TOLL FREE

WE STATUTE 182.07(2)(17A)  
REQUIRES MIN. 3 WORK DAYS  
NOTICE BEFORE YOU EXCAVATE

MILW. AREA 259-1181

THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS MAP IS BASED ON FIELD MARKINGS AND INFORMATION FURNISHED BY UTILITY COMPANIES AND THE LOCAL MUNICIPALITY. WHILE THIS INFORMATION IS BELIEVED TO BE RELIABLE, ITS ACCURACY AND COMPLETENESS CANNOT BE GUARANTEED.

DATE	DESCRIPTION

CITY OF WAUWATOSA  
ENGINEERING SERVICES DIVISION

THE SIGMA GROUP  
Single Source. Sound Solutions.


OVERALL SITE PLAN  
1900 N 116TH STREET  
WAUWATOSA, WI 53226

CONTRACT NO.	21231
FILE NO.	JRG
DRAWN BY:	CTC
CHECKED BY:	AS SHOWN
SCALE:	AS SHOWN

**C100**







**LEGEND:**

- 5' THICK CONCRETE WALK
- POROUS ASPHALT PATH (INTERIOR)
- POROUS ASPHALT PATH (EXTERIOR)
- 8" THICK, 3/4" DENSE GRADED BASE COURSE MAINTENANCE DRIVE
- EXISTING WETLAND TO REMAIN PRESERVE AND PROTECT
- CHAIN LINK FENCE
- LIGHT POLE (SEE LIGHTING PLANS)
- 8" STAND UP CURB
- EXISTING CONTOUR
- PROPOSED CONTOUR
- PROPOSED SWALE
- PROPOSED CURB & GUTTER SPOT GRADE  
T/C: TOP OF CURB GRADE  
FL: FLOW LINE CURB GRADE
- PROPOSED SURFACE SPOT GRADE
- PROPOSED TOP OF WALL AT FINISHED GRADE  
PROPOSED BOTTOM OF WALL AT FINISHED GRADE
- EXISTING SURFACE SPOT GRADE (MATCH)

- GENERAL NOTES:**
- THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS DRAWING IS BASED ON FIELD LOCATIONS AND/OR RECORDS FURNISHED BY MUNICIPALITIES AND UTILITY COMPANIES. THE LOCATION AND ACCURACY OF WHICH CANNOT BE GUARANTEED. THERE MAY BE ADDITIONAL UNDERGROUND UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.
  - VERIFY ACTUAL LOCATIONS AND INVERTS IN THE FIELD. ANY POTENTIAL ERRORS, OMISSIONS, OR DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
  - WORK TO BE COMPLETED IS INDICATED IN BOLD TYPE LINES AND EXISTING CONDITIONS ARE INDICATED BY LIGHT TYPE LINES.
  - ELECTRONIC CIVIL FILES ARE AVAILABLE UPON WRITTEN REQUEST. DO NOT USE ELECTRONIC CIVIL FILES TO LAYOUT FOUNDATIONS, COLUMN LINES, LIGHT POLES, OR OTHER NON CIVIL SITE WORK. REFER TO ARCHITECTURAL DRAWINGS FOR DIMENSIONS OF BUILDING AND ARCHITECTURAL FEATURES.
  - DIMENSIONS ARE FROM FACE OF CURB OR EDGE OF PAVEMENT.
  - WORK WITHIN THE PUBLIC RIGHT OF WAY, INCLUDING BUT NOT LIMITED TO DRIVEWAY OPENINGS, SIDEWALK AND RAMP, PAVING, AND CURB AND GUTTER SHALL BE COMPLETED PER MUNICIPAL AND/OR COUNTY REQUIREMENTS AND STANDARDS.
  - EARTHWORK SHALL BE IN ACCORDANCE WITH GEOTECHNICAL ENGINEER'S RECOMMENDATIONS.

DATE	DESCRIPTION

**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION

**SIGMA GROUP**  
Single Source. Sound Solutions.

**Site**

<b>DETAILED GRADING PLAN</b>	<b>C202</b>
<b>1900 N 116TH STREET</b>	
<b>WAUWATOSA, WI 53226</b>	

CONTRACT NO.:	21231
FILE NO.:	JRG
DRAWN BY:	CTC
CHECKED BY:	AS SHOWN
SCALE:	AS SHOWN



THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS MAP IS BASED ON FIELD MARKINGS AND INFORMATION FURNISHED BY UTILITY COMPANIES AND THE LOCAL MUNICIPALITY. WHILE THIS INFORMATION IS BELIEVED TO BE RELIABLE, ITS ACCURACY AND COMPLETENESS CANNOT BE GUARANTEED.

TO OBTAIN LOCATIONS OF PARTICIPANTS UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN


CALL DIGGERS HOTLINE  
1-800-242-8511  
TOLL FREE

WIS. STATUTE 183.02(187A)  
REQUIRES MIN. 3 WORK DAYS  
NOTICE BEFORE YOU DIG ANYTHING


MILW. AREA 259-1181



- GENERAL NOTES:**
- THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS DRAWING IS BASED ON FIELD LOCATIONS AND/OR RECORDS FURNISHED BY MUNICIPALITIES AND UTILITY COMPANIES. THE LOCATION AND ACCURACY OF WHICH CANNOT BE GUARANTEED. THERE MAY BE ADDITIONAL UNDERGROUND UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.
  - VERIFY ACTUAL LOCATIONS AND INVERTS IN THE FIELD. ANY POTENTIAL ERRORS, OMISSIONS, OR DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
  - WORK TO BE COMPLETED IS INDICATED IN BOLD TYPE LINES AND EXISTING CONDITIONS ARE INDICATED BY LIGHT TYPE LINES.
  - ELECTRONIC CIVIL FILES ARE AVAILABLE UPON WRITTEN REQUEST. DO NOT USE ELECTRONIC CIVIL FILES TO LAYOUT FOUNDATIONS, COLUMN LINES, LIGHT POLES, OR OTHER NON CIVIL SITE WORK. REFER TO ARCHITECTURAL DRAWINGS FOR DIMENSIONS OF BUILDING AND ARCHITECTURAL FEATURES.
  - ALL UTILITIES WITHIN 5 FEET OF PAVED AREAS SHALL REQUIRE GRANULAR BACKFILL. SLURRY BACKFILL IS REQUIRED FOR ALL WORK IN PUBLIC RIGHT OF WAY.
  - PRIVATE STORM INLETS IN PAVEMENT SHALL REQUIRE DRAIN TILE STUBS OF 10 FEET IN TWO DIRECTIONS FOR SUBDRAINAGE. RIM GRADE FOR STORM INLETS IN CURB AND GUTTER ARE FLOW LINE GRADES.
  - WORK IN PUBLIC RIGHT OF WAY SHALL FOLLOW MATERIAL AND INSTALLATION REQUIREMENTS PER MUNICIPAL AND/OR COUNTY.
  - PRIVATE STORM SEWER 12-INCH DIAMETER OR LARGER SHALL BE HDPE. BELOW 12-INCH DIAMETER SHALL BE PVC SDR-35 ASTM D3034. PRIVATE WATER MAIN SHALL BE CLASS 235 DR 18 PVC CONFORMING TO AWWA C-900. PRIVATE SANITARY SEWER SHALL BE PVC SDR-35 ASTM D3034.
  - COORDINATE FINAL LOCATION AND DESIGN OF PRIVATE UTILITY SERVICES (ELECTRIC, GAS, PHONE, CABLE) WITH UTILITY COMPANIES.
  - IF PROJECT IS DESIGN BUILD MEP, THE GENERAL CONTRACTOR IS REQUIRED TO PROVIDE FINAL SEWER AND WATER DESIGN SHOWING LOCATION, INVERTS AND SIZES TO THE ENGINEER FOR FINAL REVIEW AND VERIFICATION PRIOR TO STARTING UNDERGROUND UTILITY CONSTRUCTION.
  - WATER MAIN CONNECTION: TAP WATER MAIN WITH SIZE AND LOCATION INDICATED ON PLAN IN ACCORDANCE WITH LOCAL WATER UTILITY REQUIREMENTS. COORDINATE CONNECTION WITH LOCAL WATER UTILITY. ALL JOINTS SHALL BE RESTRAINED FROM CONNECTION OF WATER MAIN TO BUILDING WALL. SUBMIT JOINT RESTRAINT DETAILS FOR ALL JOINT TYPES INCLUDING PUSH-ON AND MECHANICAL CONNECTIONS. INSTALL MEGA-LUG OR APPROVED EQUAL TIGHT TO WALL FOR RESTRAINT FOR ALL BUILDING WALL PENETRATIONS AS APPROVED BY LOCAL PLUMBING INSPECTOR AND WATER UTILITY. INSTALL THRUST BLOCKING AND MEGA-LUG AT BEND BELOW FLOOR FOR ALL FLOOR PENETRATIONS.
  - INSTALL JOINT RESTRAINT AND CONCRETE THRUST BLOCKS AT ALL OFFSET FITTINGS (TEES, BENDS, DEAD ENDS, VALVES, REDUCERS) USING MEGA-LUG OR APPROVED EQUAL. CONCRETE THRUST BLOCKS SHALL BE INSTALLED PER FILE NO'S 44,45,46 FROM THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN. SEE DETAIL FOR MINIMUM LENGTH OF RESTRAINED JOINT REQUIRED. SUBMIT JOINT RESTRAINT DETAILS FOR ALL JOINT TYPES INCLUDING PUSH-ON AND MECHANICAL CONNECTIONS.



DATE	DESCRIPTION



<b>UTILITY PLAN</b>	
<b>1900 N 116TH STREET WAUWATOSA, WI 53226</b>	
CONTRACT NO.:	21231
FILE NO.:	JRG
DRAWN BY:	CTC
CHECKED BY:	AS SHOWN
SCALE:	<b>C300</b>




CALL DIGGERS HOTLINE  
1-800-242-8511  
TOLL FREE

MS STATUTE 183.012(187A)  
REQUIRES MIN. 3 WORK DAYS  
NOTICE BEFORE YOU DIG/PAVE  
MIL.W. AREA 259-1181


THE UNDERGROUND UTILITY INFORMATION SHOWN ON THIS MAP IS BASED ON FIELD MARKINGS AND INFORMATION FURNISHED BY UTILITY COMPANIES AND THE LOCAL MUNICIPALITY. WHILE THIS INFORMATION IS BELIEVED TO BE RELIABLE, ITS ACCURACY AND COMPLETENESS CANNOT BE GUARANTEED.






**A CONCRETE SIDEWALK SECTION**  
SCALE: NTS


**B CONCRETE JOINT - DOWEL**  
SCALE: NTS




**C CURB HEAD**  
SCALE: 1" = 1'




**H EXTERIOR POROUS PAVEMENT**  
SCALE: NTS



**G INTERIOR POROUS PAVEMENT**  
SCALE: NTS



**E 24 INCH CONCRETE GUTTER**  
SCALE: NTS



ENGINEERED WETLAND CONSTRUCTION INFORMATION					
ENGINEERED WETLAND	TOP OF BERM MIN. (FT)	HWL (100-YR) (FT)	2-YR PEAK ELEV. (FT)	NORMAL WATER ELEV.	BOTTOM ELEVATION (FT)
WETLAND	150.00	149.88	148.06	147.50	143.50


**LOW PERMEABILITY CLAY POND LINER:**  
MATERIAL FOR LOW PERMEABILITY CLAY POND LINER SHALL BE A NATURAL CLAY SOIL (CL MATERIAL) AS DEFINED BY THE UNIFIED SOIL CLASSIFICATION SYSTEM, FREE FROM ORGANIC OR OTHER DELETERIOUS MATERIAL. CLAY LINER SHALL BE A TYPE "B" LINER PER WDNR TECHNICAL STANDARD 1001 WHICH INCLUDES THE FOLLOWING CRITERIA: 50 PERCENT FINES (200 SIEVE) OR MORE, AN IN-PLACE HYDRAULIC CONDUCTIVITY OF  $1 \times 10^{-6}$  CM/SEC OR LESS. AN AVERAGE LIQUID LIMIT VALUE OF 16 OR GREATER, WITH NO VALUE LESS THAN 14, AN AVERAGE PI OF 7 OR MORE WITH NO VALUES LESS THAN 5. IN-SITU CLAY (IF PRESENT) AT THE BASIN MAY BE USED TO SATISFY THE LINER REQUIREMENT PROVIDED IT MEETS THE WDNR TYPE B LINER REQUIREMENTS AND IS PRESENT IN-SITU AT A THICKNESS OF 3 OR MORE FEET. SUBMIT TEST DATA DEMONSTRATING ANY MATERIALS INTENDED FOR USE AS THE BASIN LINER MEET THE REQUIRED CRITERIA FOR A TYPE B LINER.

CLAY SOURCE SHALL BE APPROVED PRIOR TO INITIATING PLACEMENT OF THE CLAY MATERIAL. SUBMIT REPRESENTATIVE MOISTURE-DENSITY DATA FOR PROPOSED CLAY MATERIAL PRIOR TO START OF WORK. IF REQUESTED, FURNISH ENGINEER WITH REPRESENTATIVE CLAY MATERIAL SAMPLES FOR TESTING.


FIELD THICKNESS AND FIELD COMPACTION OF CLAY TO BE TESTED BY OWNER'S INDEPENDENT TESTING AGENCY.

LOW PERMEABILITY CLAY/POND LINER SHALL BE PLACED USING STANDARD COMPACTION TECHNIQUES, AS PER THE STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, SECTION 207.3.6. PERCENT COMPACTION SHALL BE GREATER THAN 95% OF STANDARD PROCTOR. MATERIAL SHALL BE COMPACTED WITH MOISTURE CONTENT WET OF OPTIMUM DENSITY MOISTURE. MATERIAL SHOULD BE PLACED IN LAYERS GENERALLY NOT EXCEEDING 8 INCHES IN THICKNESS BEFORE COMPACTION.

**CLEARING AND SUBGRADE PREPARATION:**  
ALL EXISTING TOPSOIL, ROOTMATS, AND ANY OTHER SOFT OR UNSUITABLE MATERIALS SHALL BE REMOVED FROM THE CLEARING AND STRIPPING LIMITS. PRIOR TO INITIATION OF FILL PLACEMENT, THE STRIPPED AREA SHALL BE OBSERVED BY AN EXPERIENCED GEOTECHNICAL ENGINEER OR HIS AUTHORIZED REPRESENTATIVE TO AID IN LOCATING UNSUITABLE AND/OR HIGHLY PLASTIC MATERIALS WHICH REQUIRE COMPLETE AND/OR PARTIAL REMOVAL. THE PREPARATION OF FILL SUBGRADES OF EMBANKMENTS SHALL BE OBSERVED ON A FULL-TIME BASIS BY AN EXPERIENCED GEOTECHNICAL ENGINEER OR HIS AUTHORIZED REPRESENTATIVE TO ENSURE THAT ALL UNSUITABLE MATERIALS HAVE BEEN COMPLETELY REMOVED.



**TYPICAL BIO-FILTRATION DETAILS (BIO-FILTRATION BASIN 1)**



**BIOFILTRATION AREA - GRATE DETAIL**

**NOTE:**  
1. BIO-FILTRATION BASINS THAT HAVE MULTIPLE VERTICAL ORIFICES SHALL BE INSTALLED AT THE SAME ELEVATION AS IDENTIFIED IN THE TABLE.  
2. MULTIPLE VERTICAL ORIFICES SHALL HAVE A MINIMUM OF 12 INCHES HORIZONTAL SEPARATION.

BIO-FILTRATION SUMMARY TABLE														
BIO-FILTRATION AREA	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)	(K)	(L)	(M)	
BIO 1	152.50	151.85	150.50	149.00	148.00	12	148.00	148.00	3	148.00	1	-	150.10	151.98

**D BIOFILTRATION BASIN**  
SCALE: NTS

**F ENGINEERED CONSTRUCTED WETLAND**  
SCALE: NTS

**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION



**SIGMA GROUP**  
Single Source. Sound Solutions.

**THE SITE**


**PAVING DETAILS**  
1900 N 116TH STREET  
WAUWATOSA, WI 53226

CONTRACT: 21231  
FILE NO: JRG  
DRAWN BY: CTC  
CHECKED BY: AS SHOWN  
SCALE: C401

**CATCH BASIN WITHIN LOW POINT OF PAVEMENT AREA**




- NOTES:**
- ADJUST FRAME TO GRADE WITH CONCRETE RINGS OF VARIABLE THICKNESS. MAXIMUM RING HEIGHT = 6". MINIMUM RING HEIGHT = 2". CONCRETE RINGS SHALL BE REINFORCED WITH ONE LINE OF STEEL CENTERED WITHIN THE RING.
  - CONCRETE AND REINFORCEMENT STEEL SHALL CONFORM TO THE REQUIREMENTS OF ASTM DESIGNATION C-478.
  - 3" MIN. BEDDING OF STONE UNDER BASE REQUIRED. ADDITIONAL BEDDING STONE MAY BE REQUIRED ON WET SUB-GRADE.
  - UNLESS NOTED ON THE PLANS CONTRACTOR IS RESPONSIBLE FOR ALL CATCH BASIN SIZING AND SHALL PROVIDE A SHOP DRAWING TO THE SIGMA GROUP, INC. BEFORE THEY ARE RELEASED FOR PRODUCTION.



**CATCH BASIN / INLET CASTING TABLE**


	IF 18" CURB & GUTTER		IF 24" CURB & GUTTER		IF 30" CURB AND GUTTER	
	CASTING	GRATE	CASTING	GRATE	CASTING	GRATE
CURB INLET	NEENAH R-3067	A	NEENAH R-3067	A	NEENAH R-3228H	C
AREA INLET	NEENAH R-1661-B	R-2467-D				

**A INLET AND CATCH BASIN SCALE:NTS**



- NOTES:**
- CONTRACTOR TO VERIFY ADA RAMP DETAIL WITH CITY AND ADJUST AS NEEDED.
  - PROVIDE DETECTABLE WARNING CONSISTING OF RAISED TRUNCATED DOMES OF SIZE, SPACING AND CONTRAST REQUIRED BY ADA GUIDELINES.
  - DETECTABLE WARNINGS SHALL BE PER CITY STANDARDS.


**E ADA RAMP - TYPE 2 SCALE:NTS**



**B PRECAST STORM MANHOLE SCALE:NTS**


- NOTES:**
- CONSTRUCT MANHOLE IN ACCORDANCE WITH FILE NO. 12 OF THE STATE STANDARD SPECIFICATIONS FOR SEWER AND WATER.
  - ADJUST FRAME TO GRADE WITH CONCRETE RINGS OF VARIABLE THICKNESS. MAXIMUM RING HEIGHT = 6". MINIMUM RING HEIGHT = 2". CONCRETE RINGS SHALL BE REINFORCED WITH ONE LINE OF STEEL CENTERED WITHIN THE RING. WHERE NECESSARY RINGS SHALL BE GROOVED TO RECEIVE STEP.
  - CONCRETE AND REINFORCEMENT STEEL SHALL CONFORM TO THE REQUIREMENTS OF ASTM DESIGNATION C-478.
  - JOINTS SHALL BE WATERTIGHT AND SHALL BE MADE USING MORTAR, OR FLEXIBLE RUBBER TYPE GASKETS FOR STORM MANHOLES.
  - AREA OF CIRCUMFERENTIAL STEEL = 0.12 SQ. INCH PER LINEAL FOOT MIN.
  - 3" OF BEDDING STONE UNDER BASE.
  - UNLESS NOTED ON THE PLANS CONTRACTOR IS RESPONSIBLE FOR ALL MANHOLE SIZING AND SHALL PROVIDE A SHOP DRAWING TO THE SIGMA GROUP, INC. BEFORE THEY ARE RELEASED FOR PRODUCTION.

**D ADA RAMP - TYPE 1 SCALE:NTS**




- NOTES:**
- CONTRACTOR TO VERIFY ADA RAMP DETAIL WITH CITY AND ADJUST AS NEEDED.
  - PROVIDE DETECTABLE WARNING CONSISTING OF RAISED TRUNCATED DOMES OF SIZE, SPACING AND CONTRAST REQUIRED BY ADA GUIDELINES.
  - DETECTABLE WARNINGS SHALL BE PER CITY STANDARDS.

**C RIP-RAP DISCHARGE APRON SCALE:NTS**



- NOTES:**
- INSTALL RIP-RAP WHERE SHOWN ON PLANS.
  - FOR PERMANENT POOL (WET) DETENTION BASINS: EXTEND RIP-RAP FROM OUTFALL TO AT LEAST 10 FEET BEYOND THE NORMAL WATER LEVEL.
  - RIP-RAP SHALL BE MEDIUM RIP-RAP PER WISDOT STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION.
  - GEOTEXTILE FABRIC SHALL BE TYPE R PER WISDOT STANDARD SPECIFICATIONS PER HIGHWAY AND STRUCTURE CONSTRUCTION.

**D ADA RAMP - TYPE 1 SCALE:NTS**



**F ADA SIGN AND POST SCALE:NTS**

- NOTE:**
- PROVIDE ADDITIONAL SIGN "VAN ACCESSIBLE" BELOW THE SYMBOL OF ACCESSIBILITY, WHEN PROVIDING A MIN. 8' WIDE ACCESS AISLE. SIGN SHOULD BE LOCATED SO IT CANNOT BE OBTURED BY A VEHICLE PARKED IN THE SPACE.


CONTRACT:	DATE	DESCRIPTION
21231		
JRG		
CTC		
AS SHOWN		

**CITY OF WAUWATOSA ENGINEERING SERVICES DIVISION**


**UTILITY DETAILS**

**1900 N 116TH STREET WAUWATOSA, WI 53226**

**C402**




**(A) OUTLET CONTROL - WETLAND**  
SCALE: NTS




**(D) MODULAR BLOCK MSE WALL (WITH FENCE)**  
SCALE: NTS

- NOTES:**
- RETAINING WALL SYSTEM SHALL BE KEYSTONE, ROCKWOOD, OR APPROVED EQUAL.
  - TYPICAL SECTION IS FOR CONCEPTUAL DESIGN ONLY. THE CONTRACTOR SHALL PROVIDE COMPLETE DESIGN, PLANS, DETAILS, SPECIFICATIONS, AND STAMPED AND SEALED SHOP DRAWINGS AND STABILITY CALCULATIONS FOR THE RETAINING WALLS TO THE ENGINEER. THE RETAINING WALL MANUFACTURER SHALL PROVIDE TECHNICAL ASSISTANCE TO THE CONTRACTOR DURING CONSTRUCTION. THE COST OF THESE ITEMS SHALL BE INCLUDED.
  - STAMPED AND SEALED RETAINING WALL DESIGN, PLANS, DETAILS AND CALCULATIONS SHALL BE PROVIDED TO THE CITY.
  - GEOGRID REINFORCEMENT SPACING AND LENGTH PER MANUFACTURER'S ENGINEER RECOMMENDATIONS.
  - GEO TECHNICAL ENGINEER MAY REQUIRE THAT ADDITIONAL DRAIN PIPING IS NEEDED DEPENDENT UPON SOILS ENCOUNTERED DURING WALL CONSTRUCTION.
  - WALL STRUCTURE TO BE VERIFIED WITH GEOTECHNICAL ENGINEER.
  - ANY SPECIAL TREATMENT SOILS BELOW LEVELING PAD WHICH ARE SUBJECT TO FROST HEAVE SHALL BE DESIGNED BY STRUCTURAL ENGINEER OF RECORD.
  - PLANS, ELEVATIONS, AND DETAILS SHOWN ON THESE DRAWINGS ARE INTENDED TO INDICATE WALL LOCATIONS, LENGTHS, HEIGHTS, AND DETAILS COMMON TO THE WALL SYSTEM SELECTED. THE CONTRACTOR SHALL VERIFY THAT THE WALL SYSTEM SELECTED WILL CONFORM TO THE REQUIRED ALIGNMENTS AND DETAILS.
  - THE RETAINING WALL IS TO BE DESIGNED USING THE ELEVATIONS GIVEN ON THIS SHEET AND GRADING PLAN SHEETS.
  - STYLE AND COLOR OF THE MODULAR BLOCK SHALL BE SELECTED BY THE OWNER AND ARCHITECT
  - PROTECTIVE RAILINGS/GUARD RAILS REQUIRED FOR ALL RETAINING WALLS ADJACENT TO PEDESTRIAN PATHS TO BE VERIFIED BY WALL DESIGNER, ARCHITECT, AND LOCAL JURISDICTION.

**(B) OUTLET CONTROL - BIOFILTRATION**  
SCALE: NTS




**(C) UTILITY TRENCH BEDDING & BACKFILL**  
SCALE: NTS



- NOTES:**
- INSTALL ALL PIPE IN ACCORDANCE WITH PROJECT SPECIFICATIONS AND STANDARD SPECIFICATIONS FOR SEWER AND WATER IN WISCONSIN, LATEST EDITION.
  - FOUNDATION:** TRENCH BOTTOMS WITH UNSTABLE OR UNYIELDING MATERIAL SHALL BE EXCAVATED TO A DEPTH DIRECTED BY THE GEOTECHNICAL ENGINEER AND REPLACED WITH SUITABLE MATERIAL FOR UNSTABLE MATERIALS. GEOTEXTILE MAY BE USED TO STABILIZE THE TRENCH BOTTOM, IF DIRECTED BY THE GEOTECHNICAL ENGINEER.
  - BEDDING:** APPROPRIATE BEDDING IS REQUIRED TO PROVIDE UNIFORM SUPPORT FOR THE PIPE AND TO SUSTAIN GRADE.
  - HAUNCHING:** ADEQUATE HAUNCH SUPPORT IS CRITICAL TO THE INSTALLED PERFORMANCE OF BURIED PIPE. THE HAUNCH AREA ENCOMPASSES THE BEDDING ZONE UP TO THE SPRINGLINE OF THE PIPE. IF COMPACTION IS NECESSARY, AVOID DISTURBING PIPE ALIGNMENT DURING COMPACTION OPERATIONS. ALWAYS WORK ENOUGH MATERIAL UNDER THE HAUNCH TO PROVIDE ADEQUATE COMPACTION.
  - BACKFILLING:** IN ACCORDANCE WITH PROJECT SPECIFICATIONS AND STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.

**(E) 3-RAIL WESTERN CEDAR FENCE**  
SCALE: NTS



- NOTES:**
- 3-RAIL WESTERN CEDAR FENCING SHALL BE HOOPER FENCE OR APPROVED EQUAL.


CONTRACT:	FILE NO:	DRAWN BY:	CHECKED BY:	SCALE:
	21231	JRG	CTC	AS SHOWN

DATE	DESCRIPTION

<p><b>CITY OF WAUWATOSA</b> ENGINEERING SERVICES DIVISION</p>
<p><b>SITE DETAILS</b></p> <p>1900 N 116TH STREET WAUWATOSA, WI 53226</p>
<p><b>C403</b></p>




DATE	DESCRIPTION

CITY OF WAUWATOSA  
ENGINEERING SERVICES DIVISION


THE SIGMA GROUP  
Single Source. Sound Solutions.

site



GI CROSS SECTION  
1900 N 116TH STREET  
WAUWATOSA, WI 53226

CONTRACT:	21231
FILE NO.:	JRG
DRAWN BY:	CTC
CHECKED BY:	AS SHOWN
SCALE:	C404

GENERAL:	SITE WATER SERVICE CONT.:	STORM DRAINAGE:	DESCRIPTION
SITE CLEARING:	SANITARY SEWERAGE:	EARTH MOVING:	DATE
<p>1. EXISTING UTILITIES ARE SHOWN FOR INFORMATIONAL PURPOSES ONLY, AND NO RESPONSIBILITY IS ASSUMED BY THE OWNER OR ENGINEER FOR THEIR ACCURACY OR COMPLETENESS.</p> <p>2. CONTRACTOR IS RESPONSIBLE FOR MAKING THEIR OWN DETERMINATION AS TO THE TYPE AND LOCATION OF UNDERGROUND UTILITIES AS MAY BE NECESSARY TO AVOID DAMAGE THERETO. CONTRACTOR SHALL HAVE SITE MARKED BY DIGGER'S HOTLINE AND SHALL HAVE PRIVATE UTILITIES MARKED BY A PRIVATE UTILITY LOCATOR PRIOR TO CONSTRUCTION. CONTRACTOR SHALL VERIFY ALL ELEVATIONS, LOCATIONS, AND SIZES OF EXISTING UTILITIES AND SHALL CHECK ALL UTILITY CROSSINGS AND PROPOSED CONNECTIONS FOR CONFLICTS/DISCREPANCIES PRIOR TO INITIATING CONSTRUCTION. REPORT ANY CONFLICTS OR DISCREPANCIES TO THE ENGINEER SO REDESIGN MAY OCCUR IF NEEDED.</p> <p>3. LENGTHS OF ALL UTILITIES ARE TO CENTER OF STRUCTURES OR FITTINGS AND MAY VARY SLIGHTLY FROM PLANS. LENGTHS SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR.</p>	<p>14. ALL DUCTILE IRON PIPE SHALL BE ENCASED IN POLYETHYLENE PER AWWA C105, LATEST EDITION AND IN ACCORDANCE WITH CHAPTER 4.4.4 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN. ALL JOINTS AND FITTINGS SHALL HAVE POLYETHYLENE ENCASEMENT INSTALLED PER MANUFACTURER'S REQUIREMENTS AND PROCEDURES.</p> <p>15. INSTALL PVC AWWA PIPE ACCORDING TO ASTM F645 AND AWWA M23 AND CHAPTER 4.6.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN.</p> <p>16. INSTALL JOINT RESTRAINT AND CONCRETE THRUST BLOCKS AT ALL OFFSET FITTINGS (TEES, BENDS, DEAD ENDS, VALVES, REDUCERS) USING MEGA-LUG OR APPROVED EQUAL. CONCRETE THRUST BLOCKS SHALL BE INSTALLED PER FILE NO'S:44,45,46 FROM THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN. SEE DETAIL FOR MINIMUM LENGTH OF RESTRAINED JOINT REQUIRED. SUBMIT JOINT RESTRAINT DETAILS FOR ALL JOINT TYPES INCLUDING PUSH-ON AND MECHANICAL CONNECTIONS. INSTALL WATER SERVICE PIPING SUCH THAT THERE IS A MINIMUM OF 6" OF COVER OVER THE TOP OF THE WATER SERVICE PIPING.</p> <p>17. BEDDING AND COVER FOR WATER SERVICE PIPING SHALL BE IN ACCORDANCE WITH SECTION 4.3.3 AND FILE NO. 36 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION. TRENCH BACKFILL SHALL BE GRANULAR BACKFILL IN ACCORDANCE WITH SECTION 8.43.4 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION ON-SITE.</p> <p>18. INSTALL TRACER WIRE FOR NON-METALLIC WATER SERVICES IN ACCORDANCE WITH SPS SECTION 382.40(8)(K). TRACER WIRE INSULATION COLOR SHALL BE BLUE FOR POTABLE WATER SERVICE PIPING.</p> <p>19. DUCTILE-IRON PIPING, RUBBER GASKETED JOINTS IN ACCORDANCE WITH SECTION 4.4.2 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN.</p> <p>20. PVC PIPING GASKETED JOINTS: USING JOINING MATERIALS ACCORDING TO AWWA C900. CONSTRUCT JOINTS WITH ELASTOMERIC SEALS AND LUBRICANTS ACCORDING TO ASTM D2774 OR ASTM D3139 AND PIPE MANUFACTURER'S WRITTEN INSTRUCTIONS.</p> <p>21. CONDUCT HYDROSTATIC TESTS IN ACCORDANCE WITH CHAPTER 4.15.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN.</p> <p>22. CLEAN AND DISINFECT WATER SERVICE PIPING IN ACCORDANCE WITH SPS CHAPTER 82.40(8)(I) AND AWWA C651.</p>	<p>12. CLASS B COMPACTED TRENCH SECTION (FILE NO. NO. 4 OF STANDARD SPECIFICATIONS) SHALL BE UTILIZED. BEDDING AND COVER MATERIAL SHALL BE IN ACCORDANCE WITH SECTION 8.43.0 OF THE STANDARD SPECIFICATIONS.</p> <p>13. TRENCH BACKFILL MATERIAL SHALL BE GRANULAR BACKFILL IN ACCORDANCE WITH SECTION 8.43.4 OF THE STANDARD SPECIFICATIONS BENEATH AND WITHIN FIVE FEET OF PAVEMENT AREAS; COMPACTED SPOIL BACKFILL IN ACCORDANCE WITH SECTION 8.43.5 OF THE STANDARD SPECIFICATIONS MAY BE USED BENEATH LANDSCAPE AREAS.</p> <p>14. MANHOLE INSTALLATION SHALL BE IN ACCORDANCE WITH SECTION 3.5.0 OF THE STANDARD SPECIFICATIONS. SET MANHOLE RIMS TO ELEVATIONS INDICATED ON PLANS.</p> <p>15. CATCH BASIN INSTALLATION SHALL BE IN ACCORDANCE WITH SECTION 3.6 OF THE STANDARD SPECIFICATIONS. CATCH BASIN EXCAVATION AND PREPARATION SHALL BE IN ACCORDANCE WITH SECTION 3.5.4(A) AND (B) OF THE STANDARD SPECIFICATIONS. FRAMES AND GRATES SHALL BE SET TO THE ELEVATIONS SHOWN ON THE PLANS.</p> <p>16. AFTER INSTALLATION OF SEWER PIPE CLEAN ALL DEBRIS FROM SEWER AND INSPECT INTERIOR OF PIPING TO DETERMINE WHETHER LINE DISPLACEMENT OR OTHER DAMAGE HAS OCCURRED. CONDUCT DEFLECTION TESTING OF INSTALLED PIPE IN ACCORDANCE WITH SECTION 3.2.6(I)(4) OF THE STANDARD SPECIFICATIONS; REPLACE ANY PIPE SECTION NOT PASSING THE DEFLECTION TESTING USING NEW PIPE MATERIALS.</p>	
<p>1. EXCEPT FOR STRIPPED TOPSOIL OR OTHER MATERIALS INDICATED TO REMAIN ON OWNER'S PROPERTY, CLEARED MATERIALS SHALL BECOME CONTRACTOR'S PROPERTY AND SHALL BE REMOVED FROM PROJECT SITE.</p> <p>2. MINIMIZE INTERFERENCE WITH ADJOINING ROADS, STREETS, WALKS, AND OTHER ADJACENT OCCUPIED OR USED FACILITIES DURING SITE-CLEARING OPERATIONS.</p> <p>3. SALVAGE IMPROVEMENTS: CAREFULLY REMOVE ITEMS INDICATED TO BE SALVAGED AND STORE ON OWNER'S PREMISES WHERE INDICATED.</p> <p>4. UTILITY LOCATOR SERVICE: NOTIFY UTILITY LOCATOR SERVICE FOR AREA WHERE PROJECT IS LOCATED BEFORE SITE CLEARING.</p> <p>5. DO NOT COMMENCE SITE CLEARING OPERATIONS UNTIL TEMPORARY EROSION AND SEDIMENTATION CONTROL MEASURES ARE IN PLACE.</p> <p>6. PROTECT AND MAINTAIN BENCHMARKS AND SURVEY CONTROL POINTS FROM DISTURBANCE DURING CONSTRUCTION.</p> <p>7. LOCATE AND CLEARLY FLAG TREES AND VEGETATION TO REMAIN OR TO BE RELOCATED.</p> <p>8. PROTECT EXISTING SITE IMPROVEMENTS TO REMAIN FROM DAMAGE DURING CONSTRUCTION; RESTORE DAMAGED IMPROVEMENTS TO THEIR ORIGINAL CONDITION, AS ACCEPTABLE TO OWNER.</p> <p>9. LOCATE, IDENTIFY, DISCONNECT, AND SEAL OR CAP OFF UTILITIES INDICATED TO BE REMOVED; ARRANGE WITH UTILITY COMPANIES TO SHUT OFF INDICATED UTILITIES.</p> <p>10. EXISTING UTILITIES: DO NOT INTERRUPT UTILITIES SERVING FACILITIES OCCUPIED BY OWNER OR OTHERS UNLESS PERMITTED BY THE OWNER AND THEN ONLY AFTER ARRANGING TO PROVIDE TEMPORARY UTILITY SERVICES.</p> <p>11. FILL DEPRESSIONS CAUSED BY CLEARING AND GRUBBING OPERATIONS WITH SATISFACTORY SOIL MATERIAL UNLESS FURTHER EXCAVATION OR EARTHWORK IS INDICATED; PLACE FILL MATERIAL IN HORIZONTAL LAYERS NOT EXCEEDING A LOOSE DEPTH OF 8 INCHES, AND COMPACT EACH LAYER TO A DENSITY EQUAL TO ADJACENT ORIGINAL GROUND.</p> <p>12. REMOVE SOD AND GRASS BEFORE STRIPPING TOPSOIL.</p> <p>13. STRIP TOPSOIL TO WHATEVER DEPTHS ARE ENCOUNTERED IN A MANNER TO PREVENT INTERMINGLING WITH UNDERLYING SUBSOIL OR OTHER WASTE MATERIALS.</p> <p>14. STOCKPILE TOPSOIL MATERIALS AWAY FROM EDGE OF EXCAVATIONS WITHOUT INTERMIXING WITH SUBSOIL. GRADE AND SHAPE STOCKPILES TO DRAIN SURFACE WATER. COVER TO PREVENT WINDBLOWN DUST.</p> <p>15. REMOVE EXISTING ABOVE- AND BELOW-GRADE IMPROVEMENTS AS INDICATED AND AS NECESSARY TO FACILITATE NEW CONSTRUCTION.</p> <p>16. SAWCUT ALL PAVEMENTS FULL DEPTH PRIOR TO REMOVAL; SAWCUTS SHALL BE IN STRAIGHT LINES PERPENDICULAR AND/OR PARALLEL TO EXISTING PAVEMENT JOINTS AND PAVEMENT EDGES.</p> <p>17. REMOVE SURPLUS SOIL MATERIAL, UNSUITABLE TOPSOIL, OBSTRUCTIONS, DEMOLISHED MATERIALS, AND WASTE MATERIALS INCLUDING TRASH AND DEBRIS, AND LEGALLY DISPOSE OF THEM OFF OWNER'S PROPERTY.</p> <p>18. SEPARATE RECYCLABLE MATERIALS PRODUCED DURING SITE CLEARING FROM OTHER NONRECYCLABLE MATERIALS. STORE OR STOCKPILE WITHOUT INTERMIXING WITH OTHER MATERIALS AND TRANSPORT THEM TO RECYCLING FACILITIES.</p>	<p>1. ALL PRIVATE SANITARY SEWER WORK SHALL BE IN ACCORDANCE WITH THE DEPARTMENT OF SAFETY AND PROFESSIONAL SERVICES (DSPS) PLUMBING CODE - CHAPTERS SPS 382 AND SPS 384 AND LOCAL MUNICIPAL REQUIREMENTS.</p> <p>2. ALL PUBLIC SANITARY SEWER WORK SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS AND LOCAL MUNICIPAL REQUIREMENTS.</p> <p>3. PVC SEWER PIPE AND FITTINGS: ASTM D 3034, SDR 35, WITH BELL-AND-SPIGOT ENDS WITH RUBBER GASKETED JOINTS IN ACCORDANCE WITH CHAPTER 8.10.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION. JOINTS SHALL CONFORM TO ASTM D-3212.</p> <p>4. MANHOLES: STANDARD PRECAST REINFORCED CONCRETE MANHOLES CONFORMING TO ASTM C478, SECTION 8.39.0 OF THE STANDARD SPECIFICATIONS AND CONFORMING TO FILE NOS. 12, 13 AND 15 OF THE STANDARD SPECIFICATIONS. DIAMETER AND DEPTH AS INDICATED ON PLANS. MANHOLE SIZES TO BE VERIFIED BY CONTRACTOR AND SHOP DRAWINGS SHALL BE PROVIDED TO THE ENGINEER FOR REVIEW PRIOR TO ORDERING STRUCTURES.</p> <p>5. MANHOLES DEEPER THAN FOUR FEET SHALL BE PROVIDED WITH MANHOLE STEPS CONFORMING TO SECTION 8.40.0 OF THE STANDARD SPECIFICATIONS.</p> <p>6. SEWERS SHALL BE INSTALLED IN CONFORMANCE WITH SECTION 3.2.0 OF THE STANDARD SPECIFICATIONS. INSTALL PROPER SIZE INCREASERS, REDUCERS AND COUPLINGS WHERE DIFFERENT SIZES OR MATERIALS OF PIPES AND FITTINGS ARE CONNECTED. INSTALL TRACER PIPE OVER NON-METALLIC PIPING IN ACCORDANCE WITH SPS SECTION 382.30(11)(H) AND 382.36(7)(D).</p> <p>7. PIPE JOINT CONSTRUCTION: FOLLOW PIPING MANUFACTURER'S RECOMMENDATIONS; JOIN PVC SEWER PIPE ACCORDING TO ASTM D2321 AND ASTM D 3212 FOR ELASTOMERIC GASKET JOINTS. JOIN DISSIMILAR PIPE MATERIALS WITH NONPRESSURE-TYPE, FLEXIBLE COUPLINGS</p> <p>7. PROVIDE AND INSTALL CLEANOUTS IN ACCORDANCE WITH SPS CHAPTER 382.35. INSTALL CLEANOUTS AND RISER EXTENSIONS FORM SEWER PIPES TO PROPOSED GRADE. INSTALL PIPING SO CLEANOUTS OPEN IN DIRECTION OF FLOW IN SEWER PIPE. USE LIGHT DUTY, TOP LOADING CLASSIFICATION CLEANOUTS IN EARTH OR UNPAVED FOOT TRAFFIC AREAS; USE MEDIUM DUTY, TOP-LOADING CLASSIFICATION CLEANOUTS IN PAVED FOOT TRAFFIC AREAS; USE HEAVY DUTY, TOP-LOADING CLASSIFICATION CLEANOUTS IN VEHICULAR TRAFFIC AREAS. SET CLEANOUT FRAMES AND COVERS IN PAVEMENT AREAS FLUSH WITH PAVEMENT SURFACE.</p> <p>8. CLASS B COMPACTED TRENCH SECTION (FILE NO. NO. 4 OF STANDARD SPECIFICATIONS) SHALL BE UTILIZED. BEDDING AND COVER MATERIAL SHALL BE IN ACCORDANCE WITH SECTION 8.43.0 OF THE STANDARD SPECIFICATIONS.</p> <p>9. TRENCH BACKFILL MATERIAL SHALL BE GRANULAR BACKFILL IN ACCORDANCE WITH SECTION 8.43.4 OF THE STANDARD SPECIFICATIONS BENEATH AND WITHIN FIVE FEET OF PAVEMENT AREAS; COMPACTED SPOIL BACKFILL IN ACCORDANCE WITH SECTION 8.43.5 OF THE STANDARD SPECIFICATIONS MAY BE USED BENEATH LANDSCAPE AREAS.</p> <p>10. MANHOLE INSTALLATION SHALL BE IN ACCORDANCE WITH SECTION 3.5.0 OF THE STANDARD SPECIFICATIONS. SET MANHOLE RIMS TO ELEVATIONS INDICATED ON PLANS.</p> <p>11. AFTER INSTALLATION OF SEWER PIPE CLEAN ALL DEBRIS FROM SEWER AND INSPECT INTERIOR OF PIPING TO DETERMINE WHETHER LINE DISPLACEMENT OR OTHER DAMAGE HAS OCCURRED. CONDUCT DEFLECTION TESTING OF INSTALLED PIPE IN ACCORDANCE WITH SECTION 3.2.6(I)(4) OF THE STANDARD SPECIFICATIONS; REPLACE ANY PIPE SECTION NOT PASSING THE DEFLECTION TESTING USING NEW PIPE MATERIALS. TEST NEW BUILDING SEWER IN ACCORDANCE WITH SECTION 5.4.0 OF THE STANDARD SPECIFICATIONS. REPLACE LEAKING PIPE USING NEW PIPE MATERIALS AAND REPEAT TESTING UNTIL LEAKAGE IS WITHIN ALLOWANCES SPECIFIED.</p>	<p>1. ALL EARTH WORK SHALL BE DONE IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER PRESENTED IN THE SITE GEOTECHNICAL REPORT. GEOTECHNICAL ENGINEER RECOMMENDATIONS MADE IN THE FIELD AND THESE SPECIFICATIONS. IN CASE OF CONFLICT BETWEEN THESE SPECIFICATIONS AND THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER, THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER SHALL GOVERN.</p> <p>2. CONTRACTOR SHALL PROVIDE MATERIAL TEST REPORTS FROM A QUALIFIED TESTING AGENCY INDICATING TEST RESULTS FOR CLASSIFICATION ACCORDING TO ASTM D2487 AND LABORATORY COMPACTION CURVES ACCORDING TO ASTM D 1557 FOR EACH ON-SITE AND OFF-SITE SOIL MATERIAL PROPOSED FOR FILL AND BACKFILL.</p> <p>3. CONTRACTOR SHALL PROVIDE PREEXCAVATION PHOTOS OR VIDEOS SHOWING EXISTING CONDITIONS OF ADJOINING STRUCTURES AND SITE IMPROVEMENTS THAT MIGHT BE MISCONSTRUED AS DAMAGE CAUSED BY EARTHWORK OPERATIONS.</p> <p>4. OLD BUILDING FOUNDATIONS, BUILDING REMNANTS OR UNSUITABLE BACKFILL MATERIAL SHALL BE COMPLETELY REMOVED FROM WITHIN AND A MINIMUM OF 10 FEET BEYOND THE NEW BUILDING PAD AREAS. THE RESULTING EXCAVATION SHALL BE BACKFILLED WITH COMPACTED ENGINEERED FILL.</p> <p>5. FOUNDATIONS, FOUNDATION WALLS OR CONCRETE FLOOR SLABS SHALL BE REMOVED TO A MINIMUM OF TWO FEET BELOW PROPOSED SUBGRADE WITHIN PROPOSED PARKING AND GREENSPACE AREAS. BASEMENT SLABS LOCATED BELOW 2 FEET FROM PLANNED SUBGRADE ELEVATION MAY BE LEFT IN PLACE BUT SHALL BE BROKEN INTO MAXIMUM 6 INCH PIECES TO FACILITATE DRAINAGE.</p> <p>6. SATISFACTORY SOILS FOR FILL: ASTM D 2487 SOIL CLASSIFICATION GROUPS GW, GP, GM, SW, SP, AND SM OR A COMBINATION OF THESE GROUPS; FREE OF ROCK OR GRAVEL LARGER THAN 3 INCHES IN ANY DIMENSION, DEBRIS, WASTE, FROZEN MATERIALS, VEGETATION, AND OTHER DELETERIOUS MATTER OR ANY SOIL GROUP OR COMBINATION OF GROUPS APPROVED OF BY THE PROJECT GEOTECHNICAL ENGINEER.</p> <p>7. UNSATISFACTORY SOILS FOR FILL: SOIL CLASSIFICATION GROUPS GC, SC, CL, ML, OL, CH, MH, OH, AND PT ACCORDING TO ASTM D 2487 OR A COMBINATION OF THESE GROUPS UNLESS DEEMED SATISFACTORY BY THE PROJECT GEOTECHNICAL ENGINEER. UNSATISFACTORY SOILS ALSO INCLUDE SOILS NOT MAINTAINED WITHIN 3 PERCENT OF OPTIMUM SOIL MOISTURE CONTENT AT THE TIME OF COMPACTION.</p> <p>8. AGGREGATE BASE COURSE BENEATH PAVEMENTS: SHALL BE 1-1/4" DENSE GRADED BASE COURSE CONFORMING TO SECTION 305 OF THE STATE OF WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, LATEST EDITION.</p> <p>9. ENGINEERED FILL: NATURALLY OR ARTIFICIALLY GRADED MIXTURE OF NATURAL OR CRUSHED GRAVEL, CRUSHED STONE, AND NATURAL OR CRUSHED SAND; ASTM D 2940; WITH AT LEAST 90 PERCENT PASSING A 1-1/2-INCH (37.5-MM) SIEVE AND NOT MORE THAN 12 PERCENT PASSING A NO. 200 SIEVE OR ANY SOIL DEEMED ACCEPTABLE FOR ENGINEERED FILL BY THE PROJECT GEOTECHNICAL ENGINEER. ENGINEERED FILL SHALL BE FREE OF ORGANIC, FROZEN, OR OTHER DELETERIOUS MATERIAL AND HAVE A MAXIMUM PARTICLE SIZE LESS THAN 3 INCHES. CLAY FILLS SHALL HAVE A LIQUID LIMIT OF LESS THAN 49 AND PLASTICITY INDEX BETWEEN 11 AND 25.</p> <p>10. BEDDING COURSE FOR SEWERS AND WATER SERVICE: NATURALLY OR ARTIFICIALLY GRADED MIXTURE OF NATURAL OR CRUSHED GRAVEL, CRUSHED STONE, AND NATURAL OR CRUSHED SAND CONFORMING TO THE REQUIREMENTS OF SECTION 8.43.2 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.</p> <p>11. DRAINAGE COURSE BENEATH BUILDING SLABS: NARROWLY GRADED MIXTURE OF WASHED, CRUSHED STONE, OR CRUSHED OR UNCRUSHED GRAVEL; ASTM D 448; COARSE-AGGREGATE GRADING SIZE 57; WITH 100 PERCENT PASSING A 1-1/2-INCH (37.5-MM) SIEVE AND 0 TO 5 PERCENT PASSING A NO. 8 SIEVE.</p> <p>12. TRENCH BACKFILL MATERIAL SHALL BE GRANULAR BACKFILL IN ACCORDANCE WITH SECTION 8.43.4 OF THE STANDARD SPECIFICATIONS BENEATH AND WITHIN FIVE FEET OF PAVEMENT AREAS; COMPACTED SPOIL BACKFILL IN ACCORDANCE WITH SECTION 8.43.5 OF THE STANDARD SPECIFICATIONS MAY BE USED BENEATH LANDSCAPE AREAS.</p> <p>13. PIPE COVER MATERIAL: CONFORM TO SECTION 8.43.3 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.</p> <p>14. PREVENT SURFACE WATER AND GROUND WATER FROM ENTERING EXCAVATIONS, FROM PONDING ON PREPARED SUBGRADES, AND FROM FLOODING PROJECT SITE AND SURROUNDING AREA.</p> <p>15. SHORING, SHEETING AND BRACING: SHORE, BRACE OR SLOPE BANKS OF EXCAVATION TO PROTECT WORKMEN, BANKS, ADJACENT PAVING, STRUCTURES, AND UTILITIES TO MEET OSHA REQUIREMENTS. DESIGN OF TEMPORARY SUPPORT OF EXCAVATION IS THE RESPONSIBILITY OF THE CONTRACTOR.</p> <p>16. EXCAVATE TO SUBGRADE ELEVATIONS REGARDLESS OF THE CHARACTER OF SURFACE AND SUBSURFACE CONDITIONS ENCOUNTERED. UNCLASSIFIED EXCAVATED MATERIALS MAY INCLUDE ROCK, SOIL MATERIALS, AND OBSTRUCTIONS. NO CHANGES IN THE CONTRACT SUM OR THE CONTRACT TIME WILL BE AUTHORIZED FOR ROCK EXCAVATION OR REMOVAL OF OBSTRUCTIONS.</p> <p>17. PROOF-ROLL SUBGRADE BELOW THE BUILDING SLABS AND PAVEMENTS WITH FULLY LOADED TANDEM AXLE DUMP TRUCK OR RUBBER Tired VEHICLE OF SIMILAR SIZE AND WEIGHT, TYPICALLY 9 TONS/AXLE, WHERE COHESIVE SOILS ARE ENCOUNTERED OR WITH A SMOOTH DRUMMED VIBRATORY ROLLER WHERE ARE PRESENT. DO NOT PROOF-ROLL WET OR SATURATED SUBGRADES AND PROOFROLL IN DRY WEATHER. PROOF ROLL IN PRESENCE OF PROJECT GEOTECHNICAL ENGINEER OR TECHNICIAN. SOILS THAT ARE OBSERVED TO RUT OR DEFLECT EXCESSIVELY UNDER THE MOVING LOAD (TYPICALLY &gt;1") SHALL BE UNDERCUT AND REPLACED WITH PROPERLY COMPACTED ENGINEERED FILL. IN PAVEMENT AREAS WHERE UNDERCUTS ARE PERFORMED, THE EDGES OF THE OVEREXCAVATIONS SHALL BE FEATHERED INOT THE SURROUNDING SUITABLE SOIL SO THAT EDGE FAILURE OF THE OVEREXCAVATED AREA DOES NOT OCCUR.</p> <p>DUE TO CLAYEY SOILS, IF UNDERCUTS OCCUR WITHIN PAVEMENT AREAS AND THEY ARE BACKFILLED WITH GRANULAR SOILS, THE BOTTOM OF THE OVEREXCAVATION SHALL BE SLOPED TO A DRAINTILE THAT IS IN KIND SLOPED TOWARD THE NEAREST STORM SEWER. MINIMUM SLOPES OF SUCH DRAINTILES SHALL BE 0.5%.</p> <p>19. CONVENTIONAL DISKING AND AERATION TECHNIQUES SHALL BE USED TO DRY SOILS BEFORE PROOF ROLLING. ALLOT FOR PROPER DRYING TIME IN PROJECT SCHEDULE.</p> <p>20. ENGINEERED FILL SHALL BE PLACED IN MAXIMUM LIFTS OF EIGHT INCHES OF LOOSE MATERIAL AND COMPACTED WITHIN 3% OF OPTIMUM SOIL MOISTURE CONTENT VALUE AND A MINIMUM OF 95% OF THE MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR TEST ASTM D1557. EACH LIFT OF COMPACTED ENGINEERED FILL SHALL BE OBSERVED AND TESTED BY A QUALIFIED GEOTECHNICAL ENGINEER OR TECHNICIAN.</p> <p>21. EXISTING OLD FILL MATERIAL SHALL BE REMOVED BELOW FOOTINGS OR FOUNDATION SUPPORTING FILL. ENGINEERED FILL BELOW FOOTINGS SHOULD HAVE AN IN-PLACE DENSITY OF 95% OF THE MAXIMUM DRY DENSITY AND A MOISTURE CONTENT WITHIN 3% OF OPTIMUM AS DETERMINED BY ASTM D1557. ENGINEERED FILL BELOW FOOTINGS SHALL BE EVALUATED BY IN-FIELD DENSITY TESTS DURING CONSTRUCTION.</p> <p>WHERE UNSUITABLE BEARING SOILS ARE ENCOUNTERED IN A FOOTING EXCAVATION, THE EXCAVATION SHALL BE DEEPEENED TO COMPETENT BEARING SOIL AND THE FOOTING LOWERED OR AN OVEREXCAVATION AND BACKFILL PROCEDURE PERFORMED. OVEREXCAVATION AND BACKFILL TREATMENT REQUIRES WIDENING THE DEEPEENED EXCAVATION IN ALL DIRECTIONS AT LEAST 6 INCHES BEYOND THE EDGE OF THE FOOTING FOR EACH 12 INCHES OF OVEREXCAVATION DEPTH. THE OVEREXCAVATION SHALL BE BACKFILLED UP TO FOOTING BASE ELEVATION IN MAXIMUM 8 INCH LOOSE LIFTS WITH SUITABLE GRANULAR FILL MATERIAL AND COMPACTED TO 95% OF THE MAXIMUM DRY DENSITY AND A MOISTURE CONTENT WITHIN 3% OF OPTIMUM AS DETERMINED BY ASTM D1557. SOILS AT FOUNDATION BEARING ELEVATION IN THE FOOTING EXCAVATIONS SHALL BE OBSERVED AND TESTED BY A QUALIFIED GEOTECHNICAL ENGINEER OR TECHNICIAN.</p> <p>23. A MINIMUM OF FOUR INCHES OF DRAINAGE COURSE MAT SHALL BE PLACED BELOW BUILDING FLOOR SLABS. DRAINAGE COURSE SHALL BE COMPACTED TO A MINIMUM OF 95% COMPACTION WITH RESPECT TO THE MODIFIED PROCTOR (ASTM D1557)</p> <p>24. UTILITY TRENCHES FOR SEWER AND WATER SHALL CONFORM TO CLASS B COMPACTED TRENCH SECTION IN ACCORDANCE WITH FILE NO. 4 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.</p>	
<p>1. COMPLY WITH STANDARDS OF STATE PLUMBING CODE (SPS CH. 382, 384), LOCAL WATER UTILITY REQUIREMENTS AND STANDARDS OF AUTHORITIES HAVING JURISDICTION FOR FIRE-SUPPRESSION AND WATER SERVICE PIPING INCLUDING MATERIALS, FITTINGS, APPURTENANCES, INSTALLATION, TESTING, SERVICE TAPS, ETC. IN CASE OF CONFLICT BETWEEN THESE SPECIFICATIONS AND STATE PLUMBING CODE OR LOCAL JURISDICTIONAL AUTHORITY, STATE PLUMBING CODE AND LOCAL JURISDICTIONAL AUTHORITY REQUIREMENTS GOVERN.</p> <p>2. DO NOT INTERRUPT SERVICE TO FACILITIES OCCUPIED BY OWNER OR OTHERS UNLESS PERMITTED BY OWNERS OF SUCH FACILITIES AND THEN ONLY AFTER ARRANGING TO PROVIDE TEMPORARY WATER-DISTRIBUTION SERVICE.</p> <p>3. WATER SERVICE PIPING MAY BE EITHER DUCTILE IRON WATER PIPE OR PVC WATER PIPE AS ALLOWED BY THE LOCAL WATER UTILITY.</p> <p>4. DUCTILE IRON WATER PIPE CONFORMING TO THE REQUIREMENTS OF THE AMERICAN NATIONAL STANDARD FOR DUCTILE IRON PIPE, CENTRIFUGALLY CAST, AWWA C151/A21.51 - LATEST REVISION AND REQUIREMENTS OF CHAPTER 8.18.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.</p> <p>a. CLASS 52</p> <p>b. CEMENT MORTAR LINING AND INTERNAL AND EXTERNAL BITUMINOUS COATS IN ACCORDANCE WITH SECTION 51.8 OF AWWA C151.</p> <p>c. PUSH-ON GASKET PIPE</p> <p>d. PLAIN RUBBER GASKETS</p> <p>e. BONDING STRAPS TO PROVIDE ELECTRICAL CONDUCTIVITY WITHOUT FIELD TESTING</p> <p>5. JOINTS FOR DUCTILE IRON PIPE: JOINTS SHALL BE RUBBER GASKET JOINTS; CONFORM TO THE REQUIREMENTS OF AMERICAN NATIONAL STANDARD FOR RUBBER GASKET JOINTS FOR DUCTILE IRON PRESSURE PIPE AND FITTINGS (ANSI/AWWA C111/A21.11, LATEST EDITION)</p> <p>6. FITTINGS FOR DUCTILE IRON PIPE: CONFORM TO THE REQUIREMENTS OF AMERICAN NATIONAL STANDARD FOR DUCTILE IRON AND GRAY IRON FITTINGS, 3" THROUGH 48" FOR WATER ANSI/AWWA C110/A21.10, LATEST EDITION); CLASS 250 MECHANICAL JOINT PIPE FITTINGS; CEMENT LINED; ALL BELLS; ENTIRE FITTING TARRRED; CONDUCTIVE MECHANICAL JOINT (NO LEAD) RUBBER GASKETS, FLANGES, AND BOLTS.</p> <p>7. PVC AWWA PIPE: AWWA C900, CLASS 235 WITH BELL END WITH GASKET AND WITH SPIGOT END AND MEETING REQUIREMENTS OF CHAPTER 8.20.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, FITTINGS SHALL BE IN ACCORDANCE WITH CHAPTER 8.22.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN. MECHANICAL JOINT, DUCTILE IRON FITTINGS: AWWA C153, DUCTILE-IRON COMPACT PATTERN. GLANDS, GASKETS AND BOLTS: AWWA C111, DUCTILE IRON GLANDS, RUBBER GASKETS AND STEEL BOLTS.</p> <p>8. GATE VALVES: CONFORM TO AWWA C-500 AND STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN SUITABLE FOR DIRECT BURY.</p> <p>9. VALVE BOXES: CAST IRON CONFORMING TO ASTM DESIGNATION A-48, CLASS 20 AND STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN.</p> <p>10. FIRE HYDRANTS: TO MEET LOCAL STANDARDS.</p> <p>11. WATER MAIN CONNECTION: TAP WATER MAIN WITH SIZE AND LOCATION INDICATED ON PLAN IN ACCORDANCE WITH LOCAL WATER UTILITY REQUIREMENTS. COORDINATE CONNECTION WITH LOCAL WATER UTILITY. ALL JOINTS HALL BE RESTRAINED FROM CONNECTION OF WATER MAIN TO BUILDING WALL. SUBMIT JOINT RESTRAINT DETAILS FOR ALL JOINT TYPES INCLUDING PUSH-ON AND MECHANICAL CONNECTIONS. INSTALL MEGA-LUG OR APPROVED EQUAL TIGHT TO WALL FOR RESTRAINT FOR ALL BUILDING WALL PENETRATIONS AS APPROVED BY LOCAL PLUMBING INSPECTOR AND WATER UTILITY. INSTALL THRUST BLOCKING AND MEGA-LUG AT BEND BELOW FLOOR FOR ALL FLOOR PENETRATIONS</p> <p>12. GENERAL WATER PIPE INSTALLATION: IN ACCORDANCE WITH CHAPTER 4.3.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN.</p> <p>13. INSTALL DUCTILE-IRON, WATER-SERVICE PIPING ACCORDING TO AWWA C600 AND CHAPTER 4.4.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN.</p>	<p><b>STORM DRAINAGE:</b></p> <p>1. ALL PRIVATE STORM SEWER WORK SHALL BE IN ACCORDANCE WITH THE DEPARTMENT OF SAFETY AND PROFESSIONAL SERVICES (DSPS) PLUMBING CODE - CHAPTERS SPS 382 AND SPS 384 AND LOCAL MUNICIPAL REQUIREMENTS.</p> <p>2. ALL PUBLIC STORM SEWER WORK SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION (STANDARD SPECIFICATIONS) AND LOCAL MUNICIPAL REQUIREMENTS.</p> <p>3. PVC SEWER PIPE AND FITTINGS: ASTM D 3034, SDR 35, WITH BELL-AND-SPIGOT ENDS WITH RUBBER GASKETED JOINTS IN ACCORDANCE WITH CHAPTER 8.10.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION. JOINTS SHALL CONFORM TO ASTM D-3212.</p> <p>4. REINFORCED CONCRETE PIPE: ASTM C76 WITH BELL AND SPIGOT ENDS AND GASKETED JOINTS WITH ASTM C443 RUBBER GASKETS IN ACCORDANCE WITH CHAPTER 8.6.0 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.</p> <p>5. HDPE PIPE: ADS N12 PIPE AS APPROVED ON THE DEPARTMENT OF SAFETY AND PROFESSIONAL SERVICES PLUMBING PRODUCT REGISTER.</p> <p>6. CATCH BASINS: STANDARD PRECAST CONCRETE CATCH BASINS CONFORMING TO CHAPTER 3.6.0 OF THE STANDARD SPECIFICATIONS AND IN GENERAL CONFORMANCE WITH FILE NO. 26 OF THE STANDARD SPECIFICATIONS. DEPTH AND DIAMETER AS INDICATED ON PLANS. CATCH BASIN SIZES TO BE VERIFIED BY CONTRACTOR AND SHOP DRAWINGS SHALL BE PROVIDED TO THE ENGINEER FOR REVIEW PRIOR TO ORDERING STRUCTURES.</p> <p>7. FRAMES AND GRATES: AS INDICATED ON PLANS. CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING SPECIFIED FRAME/GRATE IS COMPATIBLE WITH STRUCTURE; IF NOT, NOTIFY ENGINEER.</p> <p>8. MANHOLES: STANDARD PRECAST REINFORCED CONCRETE MANHOLES CONFORMING TO ASTM C478, SECTION 8.39.0 OF THE STANDARD SPECIFICATIONS AND CONFORMING TO FILE NOS. 12, 13 AND 15 OF THE STANDARD SPECIFICATIONS. DIAMETER AND DEPTH AS INDICATED ON PLANS. MANHOLE SIZES TO BE VERIFIED BY CONTRACTOR AND SHOP DRAWINGS SHALL BE PROVIDED TO THE ENGINEER FOR REVIEW PRIOR TO ORDERING STRUCTURES.</p> <p>9. MANHOLES AND CATCH BASINS DEEPER THAN FOUR FEET SHALL BE PROVIDED WITH MANHOLE STEPS CONFORMING TO SECTION 8.40.0 OF THE STANDARD SPECIFICATIONS.</p> <p>10. SEWERS SHALL BE INSTALLED IN CONFORMANCE WITH SECTION 3.2.0 OF THE STANDARD SPECIFICATIONS. INSTALL PROPER SIZE INCREASERS, REDUCERS AND COUPLINGS WHERE DIFFERENT SIZES OR MATERIALS OF PIPES AND FITTINGS ARE CONNECTED. INSTALL TRACER PIPE OVER NON-METALLIC PIPING IN ACCORDANCE WITH SPS SECTION 382.30(11)(H) AND 382.36(7)(D).</p> <p>11. PROVIDE AND INSTALL CLEANOUTS IN ACCORDANCE WITH SPS CHAPTER 382.35. INSTALL CLEANOUTS AND RISER EXTENSIONS FORM SEWER PIPES TO PROPOSED GRADE. INSTALL PIPING SO CLEANOUTS OPEN IN DIRECTION OF FLOW IN SEWER PIPE. USE LIGHT DUTY, TOP LOADING CLASSIFICATION CLEANOUTS IN EARTH OR UNPAVED FOOT TRAFFIC AREAS; USE MEDIUM DUTY, TOP-LOADING CLASSIFICATION CLEANOUTS IN PAVED FOOT TRAFFIC AREAS; USE HEAVY DUTY, TOP-LOADING CLASSIFICATION CLEANOUTS IN VEHICULAR TRAFFIC AREAS. SET CLEANOUT FRAMES AND COVERS IN PAVEMENT AREAS FLUSH WITH PAVEMENT SURFACE.</p>	<p>12. CLASS B COMPACTED TRENCH SECTION (FILE NO. NO. 4 OF STANDARD SPECIFICATIONS) SHALL BE UTILIZED. BEDDING AND COVER MATERIAL SHALL BE IN ACCORDANCE WITH SECTION 8.43.0 OF THE STANDARD SPECIFICATIONS.</p> <p>13. TRENCH BACKFILL MATERIAL SHALL BE GRANULAR BACKFILL IN ACCORDANCE WITH SECTION 8.43.4 OF THE STANDARD SPECIFICATIONS BENEATH AND WITHIN FIVE FEET OF PAVEMENT AREAS; COMPACTED SPOIL BACKFILL IN ACCORDANCE WITH SECTION 8.43.5 OF THE STANDARD SPECIFICATIONS MAY BE USED BENEATH LANDSCAPE AREAS.</p> <p>14. MANHOLE INSTALLATION SHALL BE IN ACCORDANCE WITH SECTION 3.5.0 OF THE STANDARD SPECIFICATIONS. SET MANHOLE RIMS TO ELEVATIONS INDICATED ON PLANS.</p> <p>15. CATCH BASIN INSTALLATION SHALL BE IN ACCORDANCE WITH SECTION 3.6 OF THE STANDARD SPECIFICATIONS. CATCH BASIN EXCAVATION AND PREPARATION SHALL BE IN ACCORDANCE WITH SECTION 3.5.4(A) AND (B) OF THE STANDARD SPECIFICATIONS. FRAMES AND GRATES SHALL BE SET TO THE ELEVATIONS SHOWN ON THE PLANS.</p> <p>16. AFTER INSTALLATION OF SEWER PIPE CLEAN ALL DEBRIS FROM SEWER AND INSPECT INTERIOR OF PIPING TO DETERMINE WHETHER LINE DISPLACEMENT OR OTHER DAMAGE HAS OCCURRED. CONDUCT DEFLECTION TESTING OF INSTALLED PIPE IN ACCORDANCE WITH SECTION 3.2.6(I)(4) OF THE STANDARD SPECIFICATIONS; REPLACE ANY PIPE SECTION NOT PASSING THE DEFLECTION TESTING USING NEW PIPE MATERIALS.</p> <p>1. ALL EARTH WORK SHALL BE DONE IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER PRESENTED IN THE SITE GEOTECHNICAL REPORT. GEOTECHNICAL ENGINEER RECOMMENDATIONS MADE IN THE FIELD AND THESE SPECIFICATIONS. IN CASE OF CONFLICT BETWEEN THESE SPECIFICATIONS AND THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER, THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER SHALL GOVERN.</p> <p>2. CONTRACTOR SHALL PROVIDE MATERIAL TEST REPORTS FROM A QUALIFIED TESTING AGENCY INDICATING TEST RESULTS FOR CLASSIFICATION ACCORDING TO ASTM D2487 AND LABORATORY COMPACTION CURVES ACCORDING TO ASTM D 1557 FOR EACH ON-SITE AND OFF-SITE SOIL MATERIAL PROPOSED FOR FILL AND BACKFILL.</p> <p>3. CONTRACTOR SHALL PROVIDE PREEXCAVATION PHOTOS OR VIDEOS SHOWING EXISTING CONDITIONS OF ADJOINING STRUCTURES AND SITE IMPROVEMENTS THAT MIGHT BE MISCONSTRUED AS DAMAGE CAUSED BY EARTHWORK OPERATIONS.</p> <p>4. OLD BUILDING FOUNDATIONS, BUILDING REMNANTS OR UNSUITABLE BACKFILL MATERIAL SHALL BE COMPLETELY REMOVED FROM WITHIN AND A MINIMUM OF 10 FEET BEYOND THE NEW BUILDING PAD AREAS. THE RESULTING EXCAVATION SHALL BE BACKFILLED WITH COMPACTED ENGINEERED FILL.</p> <p>5. FOUNDATIONS, FOUNDATION WALLS OR CONCRETE FLOOR SLABS SHALL BE REMOVED TO A MINIMUM OF TWO FEET BELOW PROPOSED SUBGRADE WITHIN PROPOSED PARKING AND GREENSPACE AREAS. BASEMENT SLABS LOCATED BELOW 2 FEET FROM PLANNED SUBGRADE ELEVATION MAY BE LEFT IN PLACE BUT SHALL BE BROKEN INTO MAXIMUM 6 INCH PIECES TO FACILITATE DRAINAGE.</p> <p>6. SATISFACTORY SOILS FOR FILL: ASTM D 2487 SOIL CLASSIFICATION GROUPS GW, GP, GM, SW, SP, AND SM OR A COMBINATION OF THESE GROUPS; FREE OF ROCK OR GRAVEL LARGER THAN 3 INCHES IN ANY DIMENSION, DEBRIS, WASTE, FROZEN MATERIALS, VEGETATION, AND OTHER DELETERIOUS MATTER OR ANY SOIL GROUP OR COMBINATION OF GROUPS APPROVED OF BY THE PROJECT GEOTECHNICAL ENGINEER.</p> <p>7. UNSATISFACTORY SOILS FOR FILL: SOIL CLASSIFICATION GROUPS GC, SC, CL, ML, OL, CH, MH, OH, AND PT ACCORDING TO ASTM D 2487 OR A COMBINATION OF THESE GROUPS UNLESS DEEMED SATISFACTORY BY THE PROJECT GEOTECHNICAL ENGINEER. UNSATISFACTORY SOILS ALSO INCLUDE SOILS NOT MAINTAINED WITHIN 3 PERCENT OF OPTIMUM SOIL MOISTURE CONTENT AT THE TIME OF COMPACTION.</p> <p>8. AGGREGATE BASE COURSE BENEATH PAVEMENTS: SHALL BE 1-1/4" DENSE GRADED BASE COURSE CONFORMING TO SECTION 305 OF THE STATE OF WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, LATEST EDITION.</p> <p>9. ENGINEERED FILL: NATURALLY OR ARTIFICIALLY GRADED MIXTURE OF NATURAL OR CRUSHED GRAVEL, CRUSHED STONE, AND NATURAL OR CRUSHED SAND; ASTM D 2940; WITH AT LEAST 90 PERCENT PASSING A 1-1/2-INCH (37.5-MM) SIEVE AND NOT MORE THAN 12 PERCENT PASSING A NO. 200 SIEVE OR ANY SOIL DEEMED ACCEPTABLE FOR ENGINEERED FILL BY THE PROJECT GEOTECHNICAL ENGINEER. ENGINEERED FILL SHALL BE FREE OF ORGANIC, FROZEN, OR OTHER DELETERIOUS MATERIAL AND HAVE A MAXIMUM PARTICLE SIZE LESS THAN 3 INCHES. CLAY FILLS SHALL HAVE A LIQUID LIMIT OF LESS THAN 49 AND PLASTICITY INDEX BETWEEN 11 AND 25.</p> <p>10. BEDDING COURSE FOR SEWERS AND WATER SERVICE: NATURALLY OR ARTIFICIALLY GRADED MIXTURE OF NATURAL OR CRUSHED GRAVEL, CRUSHED STONE, AND NATURAL OR CRUSHED SAND CONFORMING TO THE REQUIREMENTS OF SECTION 8.43.2 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.</p> <p>11. DRAINAGE COURSE BENEATH BUILDING SLABS: NARROWLY GRADED MIXTURE OF WASHED, CRUSHED STONE, OR CRUSHED OR UNCRUSHED GRAVEL; ASTM D 448; COARSE-AGGREGATE GRADING SIZE 57; WITH 100 PERCENT PASSING A 1-1/2-INCH (37.5-MM) SIEVE AND 0 TO 5 PERCENT PASSING A NO. 8 SIEVE.</p> <p>12. TRENCH BACKFILL MATERIAL SHALL BE GRANULAR BACKFILL IN ACCORDANCE WITH SECTION 8.43.4 OF THE STANDARD SPECIFICATIONS BENEATH AND WITHIN FIVE FEET OF PAVEMENT AREAS; COMPACTED SPOIL BACKFILL IN ACCORDANCE WITH SECTION 8.43.5 OF THE STANDARD SPECIFICATIONS MAY BE USED BENEATH LANDSCAPE AREAS.</p> <p>13. PIPE COVER MATERIAL: CONFORM TO SECTION 8.43.3 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.</p> <p>14. PREVENT SURFACE WATER AND GROUND WATER FROM ENTERING EXCAVATIONS, FROM PONDING ON PREPARED SUBGRADES, AND FROM FLOODING PROJECT SITE AND SURROUNDING AREA.</p> <p>15. SHORING, SHEETING AND BRACING: SHORE, BRACE OR SLOPE BANKS OF EXCAVATION TO PROTECT WORKMEN, BANKS, ADJACENT PAVING, STRUCTURES, AND UTILITIES TO MEET OSHA REQUIREMENTS. DESIGN OF TEMPORARY SUPPORT OF EXCAVATION IS THE RESPONSIBILITY OF THE CONTRACTOR.</p> <p>16. EXCAVATE TO SUBGRADE ELEVATIONS REGARDLESS OF THE CHARACTER OF SURFACE AND SUBSURFACE CONDITIONS ENCOUNTERED. UNCLASSIFIED EXCAVATED MATERIALS MAY INCLUDE ROCK, SOIL MATERIALS, AND OBSTRUCTIONS. NO CHANGES IN THE CONTRACT SUM OR THE CONTRACT TIME WILL BE AUTHORIZED FOR ROCK EXCAVATION OR REMOVAL OF OBSTRUCTIONS.</p> <p>17. PROOF-ROLL SUBGRADE BELOW THE BUILDING SLABS AND PAVEMENTS WITH FULLY LOADED TANDEM AXLE DUMP TRUCK OR RUBBER Tired VEHICLE OF SIMILAR SIZE AND WEIGHT, TYPICALLY 9 TONS/AXLE, WHERE COHESIVE SOILS ARE ENCOUNTERED OR WITH A SMOOTH DRUMMED VIBRATORY ROLLER WHERE ARE PRESENT. DO NOT PROOF-ROLL WET OR SATURATED SUBGRADES AND PROOFROLL IN DRY WEATHER. PROOF ROLL IN PRESENCE OF PROJECT GEOTECHNICAL ENGINEER OR TECHNICIAN. SOILS THAT ARE OBSERVED TO RUT OR DEFLECT EXCESSIVELY UNDER THE MOVING LOAD (TYPICALLY &gt;1") SHALL BE UNDERCUT AND REPLACED WITH PROPERLY COMPACTED ENGINEERED FILL. IN PAVEMENT AREAS WHERE UNDERCUTS ARE PERFORMED, THE EDGES OF THE OVEREXCAVATIONS SHALL BE FEATHERED INOT THE SURROUNDING SUITABLE SOIL SO THAT EDGE FAILURE OF THE OVEREXCAVATED AREA DOES NOT OCCUR.</p> <p>DUE TO CLAYEY SOILS, IF UNDERCUTS OCCUR WITHIN PAVEMENT AREAS AND THEY ARE BACKFILLED WITH GRANULAR SOILS, THE BOTTOM OF THE OVEREXCAVATION SHALL BE SLOPED TO A DRAINTILE THAT IS IN KIND SLOPED TOWARD THE NEAREST STORM SEWER. MINIMUM SLOPES OF SUCH DRAINTILES SHALL BE 0.5%.</p> <p>19. CONVENTIONAL DISKING AND AERATION TECHNIQUES SHALL BE USED TO DRY SOILS BEFORE PROOF ROLLING. ALLOT FOR PROPER DRYING TIME IN PROJECT SCHEDULE.</p> <p>20. ENGINEERED FILL SHALL BE PLACED IN MAXIMUM LIFTS OF EIGHT INCHES OF LOOSE MATERIAL AND COMPACTED WITHIN 3% OF OPTIMUM SOIL MOISTURE CONTENT VALUE AND A MINIMUM OF 95% OF THE MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR TEST ASTM D1557. EACH LIFT OF COMPACTED ENGINEERED FILL SHALL BE OBSERVED AND TESTED BY A QUALIFIED GEOTECHNICAL ENGINEER OR TECHNICIAN.</p> <p>21. EXISTING OLD FILL MATERIAL SHALL BE REMOVED BELOW FOOTINGS OR FOUNDATION SUPPORTING FILL. ENGINEERED FILL BELOW FOOTINGS SHOULD HAVE AN IN-PLACE DENSITY OF 95% OF THE MAXIMUM DRY DENSITY AND A MOISTURE CONTENT WITHIN 3% OF OPTIMUM AS DETERMINED BY ASTM D1557. ENGINEERED FILL BELOW FOOTINGS SHALL BE EVALUATED BY IN-FIELD DENSITY TESTS DURING CONSTRUCTION.</p> <p>WHERE UNSUITABLE BEARING SOILS ARE ENCOUNTERED IN A FOOTING EXCAVATION, THE EXCAVATION SHALL BE DEEPEENED TO COMPETENT BEARING SOIL AND THE FOOTING LOWERED OR AN OVEREXCAVATION AND BACKFILL PROCEDURE PERFORMED. OVEREXCAVATION AND BACKFILL TREATMENT REQUIRES WIDENING THE DEEPEENED EXCAVATION IN ALL DIRECTIONS AT LEAST 6 INCHES BEYOND THE EDGE OF THE FOOTING FOR EACH 12 INCHES OF OVEREXCAVATION DEPTH. THE OVEREXCAVATION SHALL BE BACKFILLED UP TO FOOTING BASE ELEVATION IN MAXIMUM 8 INCH LOOSE LIFTS WITH SUITABLE GRANULAR FILL MATERIAL AND COMPACTED TO 95% OF THE MAXIMUM DRY DENSITY AND A MOISTURE CONTENT WITHIN 3% OF OPTIMUM AS DETERMINED BY ASTM D1557. SOILS AT FOUNDATION BEARING ELEVATION IN THE FOOTING EXCAVATIONS SHALL BE OBSERVED AND TESTED BY A QUALIFIED GEOTECHNICAL ENGINEER OR TECHNICIAN.</p> <p>23. A MINIMUM OF FOUR INCHES OF DRAINAGE COURSE MAT SHALL BE PLACED BELOW BUILDING FLOOR SLABS. DRAINAGE COURSE SHALL BE COMPACTED TO A MINIMUM OF 95% COMPACTION WITH RESPECT TO THE MODIFIED PROCTOR (ASTM D1557)</p> <p>24. UTILITY TRENCHES FOR SEWER AND WATER SHALL CONFORM TO CLASS B COMPACTED TRENCH SECTION IN ACCORDANCE WITH FILE NO. 4 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION.</p>	
FILE NAME: C500 SPECIFICATIONS.DWG	PLOT DATE: 2024-01-05	PLOTTED BY: HELEN JOHN	CITY OF WAUWATOSA
			ENGINEERING DIVISION
			
			
			SPECIFICATIONS
			1

**EARTH MOVING:**

- 25. BACKFILL UTILITY TRENCHES IN 4 TO 6 INCH LOOSE LIFTS COMPACTED TO 95% OF THE MAXIMUM DRY DENSITY AS DETERMINED BY ASTM D1557. BACKFILL SHALL BE MOISTURE CONDITIONED TO BE WITH 3% OF OPTIMUM MOISTURE CONTENT AS DETERMINED BY ASTM D1557.
- 26. UTILITY BEDDING PLACEMENT: CONFORM TO SECTION 3.2.6 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION. BEDDING MATERIAL SHALL BE COMPACTED TO A MINIMUM OF 90% COMPACTION WITH RESPECT TO THE MODIFIED PROCTOR (ASTM D1557).
- 27. COMPACTION TESTING OF UTILITY TRENCHES SHALL BE PERFORMED ONE FOR EVERY 200 CUBIC YARDS OF BACKFILL PLACED OR ONE FOR TEST PER 200 LINEAR FEET OF TRENCH FOR EACH LIFT, WHICHEVER IS LESS.
- 28. AGGREGATE BASE COURSE BENEATH PAVEMENTS SHALL BE PLACED AND COMPACTED TO 95% OF THE MAXIMUM DRY DENSITY WITH A MOISTURE CONTENT WITHIN 3% OF OPTIMUM AS DETERMINED BY ASTM D1557. AGGREGATE BASE SHALL BE OBSERVED AND TESTED BY A QUALIFIED GEOTECHNICAL ENGINEER OR TECHNICIAN.
- 29. GRADING GENERAL: UNIFORMLY GRADE AREAS TO A SMOOTH SURFACE, FREE OF IRREGULAR SURFACE CHANGES. COMPLY WITH COMPACTION REQUIREMENTS AND GRADE TO CROSS SECTIONS, LINES, AND ELEVATIONS INDICATED. SLOPE GRADES TO DIRECT WATER AWAY FROM BUILDINGS AND TO PREVENT PONDING.
- 30. TESTING AGENCY: CONTRACTOR SHALL ENGAGE A QUALIFIED INDEPENDENT GEOTECHNICAL ENGINEERING TESTING AGENCY TO PERFORM FIELD QUALITY-CONTROL TESTING.
- 31. FOOTING SUBGRADE TESTING: EACH ISOLATED FOOTING SHALL INCLUDE AT LEAST ONE TEST PROBE. TEST PROBES SHALL BE PERFORMED EVERY 20 LINEAR FEET IN CONTINUOUS FOOTINGS.
- 32. BUILDING SLAB AREA TESTING: AT SUBGRADE AND AT EACH COMPACTED FILL AND BACKFILL LAYER, AT LEAST 1 TEST PER LIFT FOR EVERY 2500 SQ. FT. OR LESS OF BUILDING SLAB, BUT IN NO CASE FEWER THAN 3 TESTS.
- 33. PAVEMENT AREA TESTING: AT SUBGRADE AND AT EACH COMPACTED FILL AND BACKFILL LAYER, AT LEAST ONE TEST FOR EVERY LIFT FOR EVERY 2,500 SQUARE FEET OF PAVEMENT AREA, BUT IN NO CASES FEWER THAN 3 TESTS.
- 34. FOUNDATION WALL BACKFILL: AT EACH COMPACTED BACKFILL LAYER, AT LEAST 1 TEST PER LIFT FOR EACH 50 FEET OR LESS OF WALL LENGTH, BUT NO FEWER THAN 2 TESTS.
- 35. WHEN TESTING AGENCY REPORTS THAT SUBGRADES, FILLS, OR BACKFILLS HAVE NOT ACHIEVED DEGREE OF COMPACTION SPECIFIED, SCARIFY AND MOISTEN OR AERATE, OR REMOVE AND REPLACE SOIL TO DEPTH REQUIRED; RECOMPACT AND RETEST UNTIL SPECIFIED COMPACTION IS OBTAINED.
- 36. DISPOSAL: REMOVE SURPLUS SOIL AND WASTE MATERIAL, INCLUDING UNSATISFACTORY SOIL, TRASH, AND DEBRIS, AND LEGALLY DISPOSE OF IT OFF OWNER'S PROPERTY.

**CONCRETE PAVING:**

- 1. THE COMPOSITION, PLACING AND CONSTRUCTION OF CONCRETE PAVEMENTS SHALL BE IN ACCORDANCE WITH THE APPLICABLE REQUIREMENTS OF SECTIONS 415, 416, 501, 601, AND 602 OF THE STATE OF WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, LATEST EDITION (WISDOT STANDARD SPECIFICATIONS) AND LOCAL MUNICIPAL REQUIREMENTS AND SPECIFICATIONS.
- 2. CONTRACTOR SHALL PROVIDE PRODUCT DATA FOR EACH TYPE OF PRODUCT INDICATED - INCLUDE TECHNICAL DATA AND TESTED PHYSICAL AND PERFORMANCE PROPERTIES; JOB-MIX DESIGNS: CERTIFICATION THAT MIX MEETS OR EXCEEDS WISDOT STANDARD SPECIFICATIONS; AND MATERIAL CERTIFICATES CERTIFYING COMPLIANCE WITH WISDOT STANDARD SPECIFICATIONS.
- 3. MANUFACTURER QUALIFICATIONS: MANUFACTURER OF READY-MIXED CONCRETE PRODUCTS WHO COMPLIES WITH ASTM C 94/C 94M REQUIREMENTS FOR PRODUCTION FACILITIES AND EQUIPMENT AND APPROVED BY THE WISCONSIN DEPARTMENT OF TRANSPORTATION.
- 4. CONCRETE GRADE: GRADE A, GRADE A-2, OR A-FA CONFORMING TO SECTION 501.3.1.3 OF THE WISDOT STANDARD SPECIFICATIONS
- 5. AGGREGATES: CONFORM TO SECTION 501 OF THE WISDOT STANDARD SPECIFICATIONS. PROVIDE AGGREGATES FROM A SINGLE SOURCE.
- 6. WATER: ASTM C 94/C 94M AND SECTION 501 OF THE WISDOT STANDARD SPECIFICATIONS.
- 7. AIR-ENTRAINING ADMIXTURE: ASTM C 260 AND SECTION 501 OF THE WISDOT STANDARD SPECIFICATIONS.
- 8. CHEMICAL ADMIXTURES: PER SECTION 501 OF THE WISDOT STANDARD SPECIFICATIONS.
- 9. CURING MATERIALS IN ACCORDANCE WITH SECTION 415.3.12 OF THE WISDOT STANDARD SPECIFICATIONS.
- 10. EXPANSION JOINT MATERIAL: CONFORM TO SECTION 415.2.3 OF THE WISDOT STANDARD SPECIFICATIONS.
- 11. MEASURE, BATCH, AND MIX CONCRETE MATERIALS AND CONCRETE IN ACCORDANCE WITH SECTION 501 OF THE WISDOT STANDARD SPECIFICATIONS.
- 12. GENERAL EXECUTION: CONFORM TO SECTION 415 OF THE WISDOT STANDARD SPECIFICATIONS.
- 13. PROOFROLL SUBGRADE AND AGGREGATE BASE AS OUTLINED IN EARTH MOVING SPECIFICATION PRIOR TO PLACEMENT OF PAVEMENTS.
- 14. SET, BRACE, AND SECURE EDGE FORMS, BULKHEADS, AND INTERMEDIATE SCREED GUIDES FOR PAVEMENT TO REQUIRED LINES, GRADES, AND ELEVATIONS. INSTALL FORMS TO ALLOW CONTINUOUS PROGRESS OF WORK AND SO FORMS CAN REMAIN IN PLACE AT LEAST 24 HOURS AFTER CONCRETE PLACEMENT.
- 15. CLEAN FORMS AFTER EACH USE AND COAT WITH FORM-RELEASE AGENT TO ENSURE SEPARATION FROM CONCRETE WITHOUT DAMAGE.
- 16. JOINTS GENERAL: FORM CONSTRUCTION, ISOLATION, AND CONTRACTION JOINTS AND TOOL EDGINGS TRUE TO LINE WITH FACES PERPENDICULAR TO SURFACE PLANE OF CONCRETE. CONSTRUCT TRANSVERSE JOINTS AT RIGHT ANGLES TO CENTERLINE, UNLESS OTHERWISE INDICATED. CONFORM TO SECTION 415 OF THE WISDOT STANDARD SPECIFICATIONS
- 17. CONSTRUCTION JOINTS: SET CONSTRUCTION JOINTS AT SIDE AND END TERMINATIONS OF PAVEMENT AND AT LOCATIONS WHERE PAVEMENT OPERATIONS ARE STOPPED FOR MORE THAN ONE-HALF HOUR UNLESS PAVEMENT TERMINATES AT ISOLATION JOINTS.
- 18. ISOLATION JOINTS: FORM ISOLATION JOINTS OF PREFORMED JOINT-FILLER STRIPS ABUTTING CONCRETE CURBS, CATCH BASINS, MANHOLES, INLETS, STRUCTURES, WALKS, OTHER FIXED OBJECTS, AND WHERE INDICATED.
- 19. CONTRACTION JOINTS: FORM WEAKENED-PLANE CONTRACTION JOINTS, SECTIONING CONCRETE INTO AREAS AS INDICATED. CONSTRUCT CONTRACTION JOINTS FOR A DEPTH EQUAL TO AT LEAST ONE-FOURTH OF THE CONCRETE THICKNESS TO MATCH JOINTING OF EXISTING ADJACENT CONCRETE PAVEMENT.
- 20. EDGING: TOOL EDGES OF PAVEMENT, GUTTERS, CURBS, AND JOINTS IN CONCRETE AFTER INITIAL FLOATING WITH AN EDGING TOOL TO A 1/4-INCH RADIUS. REPEAT TOOLING OF EDGES AFTER APPLYING SURFACE FINISHES. ELIMINATE TOOL MARKS ON CONCRETE SURFACES.
- 21. CURBING: COMPLY WITH SECTION 601 OF THE WISDOT STANDARD SPECIFICATIONS.
- 22. SIDEWALKS: COMPLY WITH SECTION 602 OF THE WISDOT STANDARD SPECIFICATIONS.
- 23. MOISTEN AGGREGATE TO PROVIDE A UNIFORM DAMPENED CONDITION AT TIME CONCRETE IS PLACED.
- 24. FINISH CURBING IN ACCORDANCE WITH SECTION 601.3.5 OF THE WISDOT STANDARD SPECIFICATIONS.
- 25. FINISH SIDEWALK AND PATIO IN ACCORDANCE WITH SECTION 602.3.2.3 OF THE WISDOT STANDARD SPECIFICATIONS (LIGHT BROOM FINISH).
- 26. FINISH CONCRETE VEHICULAR PAVEMENTS AND PADS IN ACCORDANCE WITH SECTION 415.3.8 OF THE WISDOT STANDARD SPECIFICATIONS (ARTIFICIAL TURF DRAG FINISH).
- 27. PROTECT AND CURE SIDEWALK IN ACCORDANCE WITH SECTION 602.3.2.6 OF THE WISDOT STANDARD SPECIFICATIONS.
- 28. PROTECT AND CURE CURBING IN ACCORDANCE WITH SECTION 601.3.7 OF THE WISDOT STANDARD SPECIFICATIONS.
- 29. PROTECT AND CURE VEHICULAR CONCRETE PAVING IN ACCORDANCE WITH SECTION 415.3.12 OF THE WISDOT STANDARD SPECIFICATIONS.
- 30. REMOVE AND REPLACE CONCRETE PAVEMENT THAT IS BROKEN, DAMAGED, OR DEFECTIVE OR THAT DOES NOT COMPLY WITH REQUIREMENTS IN THIS SECTION.
- 31. PROTECT CONCRETE FROM DAMAGE. EXCLUDE TRAFFIC FROM PAVEMENT FOR AT LEAST 7 DAYS AFTER PLACEMENT.
- 32. MAINTAIN CONCRETE PAVEMENT FREE OF STAINS, DISCOLORATION, DIRT, AND OTHER FOREIGN MATERIAL. SWEEP CONCRETE PAVEMENT NOT MORE THAN TWO DAYS BEFORE DATE SCHEDULED FOR SUBSTANTIAL COMPLETION INSPECTIONS.

**ASPHALTIC PAVING:**

- 1. THE COMPOSITION, PLACING AND CONSTRUCTION OF ASPHALTIC PAVEMENTS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTIONS 450, 455, 460, 465, AND 475 OF THE STATE OF WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, LATEST EDITION (WISDOT STANDARD SPECIFICATIONS).
- 2. CONTRACTOR SHALL PROVIDE PRODUCT DATA FOR EACH TYPE OF PRODUCT INDICATED - INCLUDE TECHNICAL DATA AND TESTED PHYSICAL AND PERFORMANCE PROPERTIES; JOB-MIX DESIGNS: CERTIFICATION THAT MIX MEETS OR EXCEEDS WISDOT STANDARD SPECIFICATIONS; AND MATERIAL CERTIFICATES CERTIFYING COMPLIANCE WITH WISDOT STANDARD SPECIFICATIONS.
- 3. MANUFACTURER QUALIFICATIONS: MANUFACTURER SHALL BE REGISTERED WITH AND APPROVED BY THE DOT OF THE STATE IN WHICH PROJECT IS LOCATED.
- 4. ENVIRONMENTAL LIMITATIONS: DO NOT APPLY ASPHALT MATERIALS IF BASE COURSE IS WET OR EXCESSIVELY DAMP OR IF THE FOLLOWING CONDITIONS ARE NOT MET: APPLY TACK COAT WHEN AMBIENT TEMPERATURE IS ABOVE 50 DEGREES FAHRENHEIT AND WHEN TEMPERATURE HAS NOT BEEN BELOW 35 DEGREES FAHRENHEIT FOR 12 HOURS IMMEDIATELY PRIOR TO APPLICATION; PLACE ASPHALTIC CONCRETE SURFACE COURSE WHEN TEMPERATURE IS ABOVE 40 DEGREES FAHRENHEIT; BASE COURSE MAY BE PLACED WHEN AIR TEMPERATURE IS ABOVE 30 DEGREES FAHRENHEIT AND RISING. PROCEED WITH PAVEMENT MARKING ONLY ON CLEAN, DRY SURFACES. DO NOT APPLY BELOW THE MINIMUM PAVEMENT TEMPERATURE AS RECOMMENDED BY THE MANUFACTURER.
- 5. AGGREGATES SHALL BE IN ACCORDANCE WITH SECTION 460.2.2 OF THE WISDOT STANDARD SPECIFICATIONS.
- 6. ASPHALT MATERIALS SHALL BE IN ACCORDANCE WITH CHAPTER 455 OF THE WISDOT STANDARD SPECIFICATIONS.
- 7. PAVEMENT MARKING PAINT: PROVIDE PAINT FROM THE WISCONSIN DEPARTMENT OF TRANSPORTATION'S APPROVED PRODUCTS LIST. COLOR SHALL BE WHITE UNLESS INDICATED OTHERWISE ON PLANS.
- 8. HOT-MIX ASPHALT: ASPHALTIC BINDER COURSE AND SURFACE COURSE SHALL BE MIXTURE LT FOR REGULAR DUTY PAVEMENT AND LT FOR HEAVY DUTY PAVEMENT COMPLYING WITH THE WISDOT STANDARD SPECIFICATIONS. ASPHALTIC BINDER SHALL BE 58-28 S UNLESS NOTED.
- 9. AGGREGATE BASE COURSE BENEATH PAVEMENTS: SHALL BE 1-1/4" DENSE GRADED BASE COURSE CONFORMING TO SECTION 305 OF THE WISDOT STANDARD SPECIFICATIONS.
- 10. PAVEMENT PLACEMENT GENERAL: ASPHALT CONCRETE PAVING EQUIPMENT, WEATHER LIMITATIONS, JOB-MIX FORMULA, MIXING, CONSTRUCTION METHODS, COMPACTION, FINISHING, TOLERANCE AND PROTECTION SHALL CONFORM TO THE REQUIREMENTS OF THE APPROPRIATE SECTIONS OF THE WISDOT STANDARD SPECIFICATIONS.
- 11. PREPARE AND PROOFROLL SUBGRADES AND AGGREGATE BASE COURSE AS OUTLINED IN EARTH MOVING SPECIFICATIONS PRIOR TO PLACEMENT OF ASPHALT PAVEMENTS.
- 12. SWEEP LOOSE GRANULAR PARTICLES FROM SURFACE OF AGGREGATE BASE COURSE PRIOR TO PAVEMENT PLACEMENT. DO NOT DISLODGE OR DISTURB AGGREGATE EMBEDDED IN COMPACTED SURFACE OF BASE COURSE.
- 13. SPREAD AND FINISH ASPHALTIC MIXTURE IN ACCORDANCE WITH SECTION 450.3.2.5 OF THE WISDOT STANDARD SPECIFICATIONS. PAVEMENT THICKNESSES SHALL BE AS INDICATED ON THE PLANS.
- 14. PROMPTLY CORRECT SURFACE IRREGULARITIES IN PAVING COURSE BEHIND PAVER. USE SUITABLE HAND TOOLS TO REMOVE EXCESS MATERIAL FORMING HIGH SPOTS. FILL DEPRESSIONS WITH HOT-MIX ASPHALT TO PREVENT SEGREGATION OF MIX; USE SUITABLE HAND TOOLS TO SMOOTH SURFACE.
- 15. COMPACT ASPHALTIC PAVEMENT IN ACCORDANCE WITH SECTION 450.3.2.6 OF THE WISDOT STANDARD SPECIFICATIONS.
- 16. PROTECTION: AFTER FINAL ROLLING, DO NOT PERMIT VEHICULAR TRAFFIC ON PAVEMENT UNTIL IT HAS COOLED AND HARDENED. ERECT BARRICADES TO PROTECT PAVING FROM TRAFFIC UNTIL MIXTURE HAS COOLED ENOUGH NOT TO BECOME MARKED.
- 17. THICKNESS TOLERANCE: COMPACT EACH COURSE TO PRODUCE THE THICKNESS INDICATED WITHIN PLUS/MINUS 1/4 INCH FOR BINDER COURSE AND PLUS 1/4 INCH FOR SURFACE COURSE, NO MINUS.
- 18. SURFACE SMOOTHNESS TOLERANCE: COMPACT EACH COURSE TO PRODUCE A SURFACE SMOOTHNESS WITHIN THE FOLLOWING TOLERANCES AS DETERMINED BY USING A 10-FOOT STRAIGHTEDGE APPLIED TRANSVERSELY OR LONGITUDINALLY TO PAVED AREAS: BINDER COURSE: 1/4 INCH; SURFACE COURSE: 1/8 INCH. REMOVE AND REPLACE ALL HUMPS OR DEPRESSIONS EXCEEDING THE SPECIFIED TOLERANCES.
- 19. DO NOT APPLY PAVEMENT-MARKING PAINT UNTIL LAYOUT, COLORS, AND PLACEMENT HAVE BEEN VERIFIED WITH ENGINEER.
- 20. APPLY MARKINGS TO A DRY SURFACE FREE FROM FROST. REMOVE DUST, DIRT, OIL, GREASE, GRAVEL, DEBRIS OR OTHER MATERIAL THAT MAY PREVENT BONDING TO THE PAVEMENT.
- 21. APPLY PAINT AS THE MANUFACTURER SPECIFIES WITH MECHANICAL EQUIPMENT TO PRODUCE PAVEMENT MARKINGS, OF DIMENSIONS INDICATED, WITH UNIFORM, STRAIGHT EDGES. APPLY AT MANUFACTURER'S RECOMMENDED RATES AT A MINIMUM RATE OF 17.6 GALLONS/MILE FOR A CONTINUOUS 4" LINE.
- 22. TESTING AGENCY: CONTRACTOR SHALL ENGAGE A QUALIFIED INDEPENDENT TESTING AND INSPECTING AGENCY TO PERFORM FIELD TESTS AND INSPECTIONS AND TO PREPARE TEST REPORTS.

**SEGMENTAL RETAINING WALL:**

- 1. WORK SHALL CONSIST OF FURNISHING DETAILED DESIGN, MATERIALS, LABOR, EQUIPMENT AND SUPERVISION TO INSTALL A SEGMENTAL RETAINING WALL SYSTEM IN ACCORDANCE WITH PLANS AND SPECIFICATIONS AND IN REASONABLY CLOSE CONFORMITY WITH THE LINES, GRADES, DESIGN AND DIMENSIONS SHOWN ON PLANS.
- 2. MATERIALS SUBMITTALS: THE CONTRACTOR SHALL SUBMIT MANUFACTURERS' CERTIFICATIONS TWO WEEKS PRIOR TO START OF WORK STATING THAT THE SRW UNITS AND GEOSYNTHETIC REINFORCEMENT MEET THE REQUIREMENTS OF THE DESIGN.
- 3. DESIGN SUBMITTAL: THE CONTRACTOR SHALL SUBMIT TWO SETS OF DETAILED DESIGN CALCULATIONS AND FINAL RETAINING WALL PLANS FOR APPROVAL AT LEAST TWO WEEKS PRIOR TO THE BEGINNING OF WALL CONSTRUCTION. ALL CALCULATIONS AND DRAWINGS SHALL BE PREPARED AND SEALED BY A PROFESSIONAL CIVIL ENGINEER (P.E.) - (WALL DESIGN ENGINEER) EXPERIENCED IN SRW DESIGN AND LICENSED IN THE STATE WHERE THE WALL IS TO BE BUILT.
- 4. SEGMENTAL RETAINING WALL (SRW) UNITS SHALL BE MACHINE FORMED, PORTLAND CEMENT CONCRETE BLOCKS SPECIFICALLY DESIGNED FOR RETAINING WALL APPLICATIONS. SRW UNITS SHALL BE VERSA-LOK STANDARD RETAINING WALL UNITS, KEYSTONE RETAINING WALL UNITS, ROCKWOOD RETAINING WALL UNITS OR APPROVED EQUIVA.
- 5. COLOR AND STYLE OF SRW UNITS SHALL BE AS SELECTED BY ARCHITECT AND OWNER FROM MANUFACTURER'S FULL RANGE.
- 6. SRW UNITS SHALL BE CAPABLE OF BEING ERECTED WITH THE HORIZONTAL GAP BETWEEN ADJACENT UNITS NOT EXCEEDING 1/8 INCH.
- 7. SRW UNITS SHALL BE SOUND AND FREE OF CRACKS OR OTHER DEFECTS THAT WOULD INTERFERE WITH THE PROPER PLACING OF THE UNIT OR SIGNIFICANTLY IMPAIR THE STRENGTH OR PERMANENCE OF THE STRUCTURE. ANY CRACKS OR CHIPS OBSERVED DURING CONSTRUCTION SHALL FALL WITHIN THE GUIDELINES OUTLINED IN ASTM C 1372.
- 8. CONCRETE SRW UNITS SHALL CONFORM TO THE REQUIREMENTS OF ASTM 1372 AND HAVE A MINIMUM NET AVERAGE 28 DAYS COMPRESSIVE STRENGTH OF 3000 PSI. COMPRESSIVE STRENGTH TEST SPECIMENS SHALL CONFORM TO THE SAW-CUT COUPON PROVISIONS OF ASTM C140.
- 9. SRW UNITS' MOLDED DIMENSIONS SHALL NOT DIFFER MORE THAN ± 1/8 INCH FROM THAT SPECIFIED, AS MEASURED IN ACCORDANCE WITH ASTM C 140. THIS TOLERANCE DOES NOT APPLY TO ARCHITECTURAL SURFACES, SUCH AS SPLIT FACES.
- 10. SRW UNITS SHALL BE INTERLOCKED WITH CONNECTION PINS. THE PINS SHALL CONSIST OF GLASS-REINFORCED NYLON MADE FOR THE EXPRESSED USE WITH THE SRW UNITS SUPPLIED.
- 11. GEOSYNTHETIC REINFORCEMENT SHALL CONSIST OF HIGH-TENACITY PET GEOGRIDS, HDPE GEOGRIDS, OR GEOTEXTILES MANUFACTURED FOR SOIL REINFORCEMENT APPLICATIONS. THE TYPE, STRENGTH AND PLACEMENT OF THE GEOSYNTHETIC REINFORCEMENT SHALL BE DETERMINED BY PROCEDURES OUTLINED IN THIS SPECIFICATION AND THE NCMA DESIGN MANUAL FOR SEGMENTAL RETAINING WALLS (3RD EDITION 2009) AND MATERIALS SHALL BE SPECIFIED BY WALL DESIGN ENGINEER IN THEIR FINAL WALL PLANS AND SPECIFICATIONS. THE MANUFACTURERS/SUPPLIERS OF THE GEOSYNTHETIC REINFORCEMENT SHALL HAVE DEMONSTRATED CONSTRUCTION OF SIMILAR SIZE AND TYPES OF SEGMENTAL RETAINING WALLS ON PREVIOUS PROJECTS.
- 12. THE TYPE, STRENGTH AND PLACEMENT OF THE REINFORCING GEOSYNTHETIC SHALL BE AS DETERMINED BY THE WALL DESIGN ENGINEER, AS SHOWN ON THE FINAL, P.E.-STAMPED RETAINING WALL PLANS.
- 13. MATERIAL FOR LEVELING PAD SHALL CONSIST OF COMPACTED SAND, GRAVEL, OR COMBINATION THEREOF (USCS SOIL TYPES GP, GW, SP, & SW) AND SHALL BE A MINIMUM OF 6 INCHES IN DEPTH. LEAN CONCRETE WITH A STRENGTH OF 200-300 PSI AND 3 INCHES THICK MAXIMUM MAY ALSO BE USED AS A LEVELING PAD MATERIAL. THE LEVELING PAD SHOULD EXTEND LATERALLY AT LEAST A DISTANCE OF 6 INCHES FROM THE TOE AND HEEL OF THE LOWERMOST SRW UNIT.
- 14. DRAINAGE AGGREGATE SHALL BE ANGULAR, CLEAN STONE OR GRANULAR FILL MEETING THE FOLLOWING GRADATION AS DETERMINED IN ACCORDANCE WITH ASTM D422:

SIEVE SIZE	PERCENT PASSING
1 INCH	100
3/4 INCH	75-100
NO. 4	0-60
NO. 40	0-50
NO. 200	0-5


**SEGMENTAL RETAINING WALL CONT.:**

- 15. THE DRAINAGE COLLECTION PIPE SHALL BE A PERFORATED OR SLOTTED PVC, OR CORRUGATED HDPE PIPE. THE DRAINAGE PIPE MAY BE WRAPPED WITH A GEOTEXTILE TO FUNCTION AS A FILTER. DRAINAGE PIPE SHALL BE MANUFACTURED IN ACCORDANCE WITH ASTM F 405 OR ASTM F 758.
- 16. THE REINFORCED SOIL MATERIAL SHALL BE FREE OF DEBRIS, UNLESS OTHERWISE NOTED ON THE FINAL, P.E.-SEALED, RETAINING WALL PLANS PREPARED BY THE WALL DESIGN ENGINEER. THE REINFORCED MATERIAL SHALL CONSIST OF THE INORGANIC USCS SOIL TYPES GP, GW, SW, SP, SM, MEETING THE FOLLOWING GRADATION, AS DETERMINED IN ACCORDANCE WITH ASTM D422:

SIEVE SIZE	PERCENT PASSING
1 INCH	100
NO. 4	20-100
NO. 40	0-60
NO. 200	0-35

- 17. THE MAXIMUM PARTICLE SIZE OF POORLY-GRADED GRAVELS (GP) (NO FINES) SHOULD NOT EXCEED 3/4 INCH UNLESS EXPRESSLY APPROVED BY THE WALL DESIGN ENGINEER AND THE LONG-TERM DESIGN STRENGTH (LTD)S OF THE GEOSYNTHETIC IS REDUCED TO ACCOUNT FOR ADDITIONAL INSTALLATION DAMAGE FROM PARTICLES LARGER THAN THIS MAXIMUM.
- 18. THE PLASTICITY OF THE FINE FRACTION SHALL BE LESS THAN 20.
- 19. THE PH OF THE BACKFILL MATERIAL SHALL BE BETWEEN 3 AND 9 WHEN TESTED IN ACCORDANCE WITH ASTM G 51.
- 20. DRAINAGE GEOTEXTILE SHALL CONSIST OF GEOSYNTHETIC SPECIFICALLY MANUFACTURED FOR USE AS A PERMEABLE SOIL FILTER THAT RETAINS SOIL WHILE STILL ALLOWING WATER TO PASS THROUGHOUT THE LIFE OF THE STRUCTURE. THE TYPE AND PLACEMENT OF THE GEOTEXTILE FILTER MATERIAL SHALL BE AS REQUIRED BY THE WALL DESIGN ENGINEER IN THEIR FINAL WALL PLANS AND SPECIFICATIONS.
- 21. THE DESIGN ANALYSIS FOR THE FINAL, P.E.-STAMPED RETAINING WALL PLANS PREPARED BY THE WALL DESIGN ENGINEER SHALL CONSIDER THE EXTERNAL STABILITY AGAINST SLIDING AND OVERTURNING, INTERNAL STABILITY AND FACIAL STABILITY OF THE REINFORCED SOIL MASS, AND SHALL BE IN ACCORDANCE WITH ACCEPTABLE ENGINEERING PRACTICE AND THESE SPECIFICATIONS. THE INTERNAL AND EXTERNAL STABILITY ANALYSIS SHALL BE PERFORMED IN ACCORDANCE WITH THE "NCMA DESIGN MANUAL FOR SEGMENTAL RETAINING WALLS, 3RD EDITION" USING THE RECOMMENDED MINIMUM FACTORS OF SAFETY IN THIS MANUAL.
- 22. EXTERNAL STABILITY ANALYSIS FOR BEARING CAPACITY, GLOBAL STABILITY, AND TOTAL AND DIFFERENTIAL SETTLEMENT SHALL BE THE RESPONSIBILITY OF THE OWNER AND THE OWNER'S GEOTECHNICAL ENGINEER. THE GEOTECHNICAL ENGINEER SHALL PERFORM BEARING CAPACITY, SETTLEMENT ESTIMATES, AND GLOBAL STABILITY ANALYSIS BASED ON THE FINAL WALL DESIGN PROVIDED BY THE WALL DESIGN ENGINEER AND COORDINATE ANY REQUIRED CHANGES WITH THE WALL DESIGN ENGINEER.
- 23. THE GEOSYNTHETIC PLACEMENT IN THE WALL DESIGN SHALL HAVE 100% CONTINUOUS COVERAGE PARALLEL TO THE WALL FACE. GAPPING BETWEEN HORIZONTALLY ADJACENT LAYERS OF GEOSYNTHETIC (PARTIAL COVERAGE) WILL NOT BE ALLOWED.
- 24. CONTRACTOR'S FIELD CONSTRUCTION SUPERVISOR SHALL HAVE DEMONSTRATED EXPERIENCE AND BE QUALIFIED TO DIRECT ALL WORK AT THE SITE.
- 25. CONTRACTOR SHALL EXCAVATE TO THE LINES AND GRADES SHOWN ON THE PROJECT GRADING PLANS. CONTRACTOR SHALL TAKE PRECAUTIONS TO MINIMIZE OVER-EXCAVATION. OVER-EXCAVATION SHALL BE FILLED WITH COMPACTED INFILL MATERIAL, OR AS DIRECTED BY THE WALL DESIGN ENGINEER, AT THE CONTRACTOR'S EXPENSE.
- 26. CONTRACTOR SHALL VERIFY LOCATION OF EXISTING STRUCTURES AND UTILITIES PRIOR TO EXCAVATION. CONTRACTOR SHALL ENSURE ALL SURROUNDING STRUCTURES ARE PROTECTED FROM THE EFFECTS OF WALL EXCAVATION. EXCAVATION SUPPORT, IF REQUIRED, IS THE RESPONSIBILITY OF THE CONTRACTOR.
- 27. FOLLOWING THE EXCAVATION, THE FOUNDATION SOIL SHALL BE EXAMINED BY THE OWNER'S ENGINEER TO ASSURE ACTUAL FOUNDATION SOIL STRENGTH MEETS OR EXCEEDS THE ASSUMED DESIGN BEARING STRENGTH. SOILS NOT MEETING THE REQUIRED STRENGTH SHALL BE REMOVED AND REPLACED WITH INFILL SOILS, AS DIRECTED BY THE CONTRACTOR'S GEOTECHNICAL ENGINEER.
- 28. FOUNDATION SOIL SHALL BE PROOF-ROLLED AND COMPACTED TO 95% STANDARD PROCTOR DENSITY AND INSPECTED BY THE CONTRACTOR'S GEOTECHNICAL ENGINEER PRIOR TO PLACEMENT OF LEVELING PAD MATERIALS.
- 29. LEVELING PAD SHALL BE PLACED AS SHOWN ON THE FINAL, P.E.-SEALED RETAINING WALL PLANS WITH A MINIMUM THICKNESS OF 6 INCHES. THE LEVELING PAD SHOULD EXTEND LATERALLY AT LEAST A DISTANCE OF 6 INCHES FROM THE TOE AND HEEL OF THE LOWERMOST SRW UNIT.
- 30. GRANULAR LEVELING PAD MATERIAL SHALL BE COMPACTED TO PROVIDE A FIRM, LEVEL BEARING SURFACE ON WHICH TO PLACE THE FIRST COURSE OF UNITS. WELL-GRADED SAND CAN BE USED TO SMOOTH THE TOP 1/4 INCH TO 1/2 INCH OF THE LEVELING PAD. COMPACTION WILL BE WITH MECHANICAL PLATE COMPACTORS TO ACHIEVE 95% OF MAXIMUM STANDARD PROCTOR DENSITY (ASTM D 698).
- 31. ALL SRW UNITS SHALL BE INSTALLED AT THE PROPER ELEVATION AND ORIENTATION AS SHOWN ON THE FINAL, P.E.-SEALED WALL PLANS AND DETAILS OR AS DIRECTED BY THE WALL DESIGN ENGINEER. THE SRW UNITS SHALL BE INSTALLED IN GENERAL ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS. THE SPECIFICATIONS AND DRAWINGS SHALL GOVERN IN ANY CONFLICT BETWEEN THE TWO REQUIREMENTS.
- 32. FIRST COURSE OF SRW UNITS SHALL BE PLACED ON THE LEVELING PAD. THE UNITS SHALL BE LEVELLED SIDE-TO-SIDE, FRONT-TO-REAR AND WITH ADJACENT UNITS, AND ALIGNED TO ENSURE INTIMATE CONTACT WITH THE LEVELING PAD. THE FIRST COURSE IS THE MOST IMPORTANT TO ENSURE ACCURATE AND ACCEPTABLE RESULTS. NO GAPS SHALL BE LEFT BETWEEN THE FRONT OF ADJACENT UNITS. ALIGNMENT MAY BE DONE BY MEANS OF A STRING LINE OR OFFSET FROM BASE LINE TO THE BACK OF THE UNITS.
- 33. ALL EXCESS DEBRIS SHALL BE CLEANED FROM TOP OF UNITS AND THE NEXT COURSE OF UNITS INSTALLED ON TOP OF THE UNITS BELOW.
- 34. CONNECTION PINS SHALL BE INSERTED THROUGH THE PIN HOLES OF EACH UPPER-COURSE UNIT INTO RECEIVING SLOTS IN LOWER-COURSE UNITS. PINS SHALL BE FULLY SEATED IN THE PIN SLOT BELOW. UNITS SHALL BE PUSHED FORWARD TO REMOVE ANY LOOSENESS IN THE UNIT-TO-UNIT CONNECTION.
- 35. PRIOR TO PLACEMENT OF NEXT COURSE, THE LEVEL AND ALIGNMENT OF THE UNITS SHALL BE CHECKED AND CORRECTED WHERE NEEDED.
- 36. LAYOUT OF CURVES AND CORNERS SHALL BE INSTALLED IN ACCORDANCE WITH THE WALL PLAN DETAILS OR IN GENERAL ACCORDANCE WITH SRW MANUFACTURER'S INSTALLATION GUIDELINES. WALLS MEETING AT CORNERS SHALL BE INTERLOCKED BY OVERLAPPING SUCCESSIVE COURSES.
- 37. PROCEDURES ABOVE SHALL BE REPEATED UNTIL REACHING TOP OF WALL UNITS, JUST BELOW THE HEIGHT OF THE CAP UNITS. GEOSYNTHETIC REINFORCEMENT, DRAINAGE MATERIALS, AND REINFORCED BACKFILL SHALL BE PLACED IN SEQUENCE WITH UNIT INSTALLATION.
- 38. ALL GEOSYNTHETIC REINFORCEMENT SHALL BE INSTALLED AT THE PROPER ELEVATION AND ORIENTATION AS SHOWN ON THE FINAL P.E.-SEALED RETAINING WALL PLAN PROFILES AND DETAILS, OR AS DIRECTED BY THE WALL DESIGN ENGINEER.
- 39. AT THE ELEVATIONS SHOWN ON THE FINAL PLANS, (AFTER THE UNITS, DRAINAGE MATERIAL AND BACKFILL HAVE BEEN PLACED TO THIS ELEVATION) THE GEOSYNTHETIC REINFORCEMENT SHALL BE LAID HORIZONTALLY ON COMPACTED INFILL AND ON TOP OF THE CONCRETE SRW UNITS, TO WITHIN 1 INCH OF THE FRONT FACE OF THE UNIT BELOW. EMBEDMENT OF THE GEOSYNTHETIC IN THE SRW UNITS SHALL BE CONSISTENT WITH SRW MANUFACTURER'S RECOMMENDATIONS. CORRECT ORIENTATION OF THE GEOSYNTHETIC REINFORCEMENT SHALL BE VERIFIED BY THE CONTRACTOR TO BE IN ACCORDANCE WITH THE GEOSYNTHETIC MANUFACTURER'S RECOMMENDATIONS. THE HIGHEST-STRENGTH DIRECTION OF THE GEOSYNTHETIC MUST BE PERPENDICULAR TO THE WALL FACE.
- 40. GEOSYNTHETIC REINFORCEMENT LAYERS SHALL BE ONE CONTINUOUS PIECE FOR THEIR ENTIRE EMBEDMENT LENGTH. SPLICING OF THE GEOSYNTHETIC IN THE DESIGN-STRENGTH DIRECTION (PERPENDICULAR TO THE WALL FACE) SHALL NOT BE PERMITTED. ALONG THE LENGTH OF THE WALL, HORIZONTALLY ADJACENT SECTIONS OF GEOSYNTHETIC REINFORCEMENT SHALL BE BUTTED IN A MANNER TO ASSURE 100% COVERAGE PARALLEL TO THE WALL FACE.
- 41. TRACKED CONSTRUCTION EQUIPMENT SHALL NOT BE OPERATED DIRECTLY ON THE GEOSYNTHETIC REINFORCEMENT. A MINIMUM OF 6 INCHES OF BACKFILL IS REQUIRED PRIOR TO OPERATION OF TRACKED VEHICLES OVER THE GEOSYNTHETIC. TURNINGS SHOULD BE KEPT TO A MINIMUM. RUBBER-TIRED EQUIPMENT MAY PASS OVER THE GEOSYNTHETIC REINFORCEMENT AT SLOW SPEEDS (LESS THAN 5 MPH).
- 42. THE GEOSYNTHETIC REINFORCEMENT SHALL BE FREE OF WRINKLES PRIOR TO PLACEMENT OF SOIL FILL. THE NOMINAL TENSION SHALL BE APPLIED TO THE REINFORCEMENT AND SECURED IN PLACE WITH STAPLES, STAKES OR BY HAND TENSIONING UNTIL REINFORCEMENT IS COVERED BY 6 INCHES OF FILL.

CONTRACT:	21231
FILE NO.:	JRG
DRAWN BY:	CTC
CHECKED BY:	AS SHOWN
SCALE:	C501



**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION



**SIGMA** GROUP  
Single Source. Sound Solutions.



**Site**

**SPECIFICATIONS**

**1900 N 116TH STREET**

**WAUWATOSA, WI 53226**

**SEGMENTAL RETAINING WALL CONT.:**

43. DRAINAGE AGGREGATE SHALL BE INSTALLED TO THE LINE, GRADES AND SECTIONS SHOWN ON THE FINAL P.E.-SEALED RETAINING WALL PLANS. DRAINAGE AGGREGATE SHALL BE PLACED TO THE MINIMUM THICKNESS SHOWN ON THE CONSTRUCTION PLANS BETWEEN AND BEHIND UNITS (A MINIMUM OF 1 CUBIC FOOT FOR EACH EXPOSED SQUARE FOOT OF WALL FACE UNLESS OTHERWISE NOTED ON THE FINAL WALL PLANS).
44. DRAINAGE COLLECTION PIPES SHALL BE INSTALLED TO MAINTAIN GRAVITY FLOW OF WATER OUTSIDE THE REINFORCED-SOIL ZONE. THE DRAINAGE COLLECTION PIPE SHALL BE INSTALLED AT THE LOCATIONS SHOWN ON THE FINAL CONSTRUCTION DRAWINGS. THE DRAINAGE COLLECTION PIPE SHALL DAYLIGHT INTO A STORM SEWER OR ALONG A SLOPE, AT AN ELEVATION BELOW THE LOWEST POINT OF THE PIPE WITHIN THE AGGREGATE DRAIN. DRAINAGE LATERALS SHALL BE SPACED AT A MAXIMUM 50-FOOT SPACING ALONG THE WALL FACE.
45. THE REINFORCED BACKFILL SHALL BE PLACED AS SHOWN IN THE FINAL WALL PLANS IN THE MAXIMUM COMPACTED LIFT THICKNESS OF 8 INCHES AND SHALL BE COMPACTED TO A MINIMUM OF 95% OF STANDARD PROCTOR DENSITY (ASTM D 698) AT A MOISTURE CONTENT WITHIN -1% POINT TO +3% POINTS OF OPTIMUM. THE BACKFILL SHALL BE PLACED AND SPREAD IN SUCH A MANNER AS TO ELIMINATE WRINKLES OR MOVEMENT OF THE GEOSYNTHETIC REINFORCEMENT AND THE SRW UNITS.
46. ONLY HAND-OPERATED COMPACTION EQUIPMENT SHALL BE ALLOWED WITHIN 3 FEET OF THE BACK OF THE WALL UNITS. COMPACTION WITHIN THE 3 FEET BEHIND THE WALL UNITS SHALL BE ACHIEVED BY AT LEAST THREE PASSES OF A LIGHTWEIGHT MECHANICAL TAMPER, PLATE, OR ROLLER.
47. AT THE END OF EACH DAY'S OPERATION, THE CONTRACTOR SHALL SLOPE THE LAST LEVEL OF BACKFILL AWAY FROM THE WALL FACING AND REINFORCED BACKFILL TO DIRECT WATER RUNOFF AWAY FROM THE WALL FACE.
48. AT COMPLETION OF WALL CONSTRUCTION, BACKFILL SHALL BE PLACED LEVEL WITH FINAL TOP OF WALL ELEVATION. IF FINAL GRADING, PAVING, LANDSCAPING AND/OR STORM DRAINAGE INSTALLATION ADJACENT TO THE WALL IS NOT PLACED IMMEDIATELY AFTER WALL COMPLETION, TEMPORARY GRADING AND DRAINAGE SHALL BE PROVIDED TO ENSURE WATER RUNOFF IS NOT DIRECTED AT THE WALL NOR ALLOWED TO COLLECT OR POND BEHIND THE WALL UNTIL FINAL CONSTRUCTION ADJACENT TO THE WALL IS COMPLETED.
49. SRW CAPS SHALL BE PROPERLY ALIGNED AND GLUED TO UNDERLYING UNITS WITH VERSA-LOK ADHESIVE, A FLEXIBLE, HIGH-STRENGTH CONCRETE ADHESIVE. RIGID ADHESIVE OR MORTAR ARE NOT ACCEPTABLE.
50. CAPS SHALL OVERHANG THE TOP COURSE OF UNITS BY 3/4 INCH TO 1 INCH. SLIGHT VARIATION IN OVERHANG IS ALLOWED TO CORRECT ALIGNMENT AT THE TOP OF THE WALL.
51. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ENSURING THAT CONSTRUCTION BY OTHERS ADJACENT TO THE WALL DOES NOT DISTURB THE WALL OR PLACE TEMPORARY CONSTRUCTION LOADS ON THE WALL THAT EXCEED DESIGN LOADS, INCLUDING LOADS SUCH AS WATER PRESSURE, TEMPORARY GRADES, OR EQUIPMENT LOADING. HEAVY PAVING OR GRADING EQUIPMENT SHALL BE KEPT A MINIMUM OF 3 FEET BEHIND THE BACK OF THE WALL FACE. EQUIPMENT WITH WHEEL LOADS IN EXCESS OF 150 PSF LIVE LOAD SHALL NOT BE OPERATED WITHIN 10 FEET OF THE FACE OF THE RETAINING WALL DURING CONSTRUCTION ADJACENT TO THE WALL. CARE SHOULD BE TAKEN BY THE GENERAL CONTRACTOR TO ENSURE WATER RUNOFF IS DIRECTED AWAY FROM THE WALL STRUCTURE UNTIL FINAL GRADING AND SURFACE DRAINAGE COLLECTION SYSTEMS ARE COMPLETED.


**BIOFILTRATION BASIN:**

1. BIOFILTRATION BASIN SHALL BE CONSTRUCTED IN GENERAL ACCORDANCE WITH WDNr TECHNICAL STANDARD 1004: BIORETENTION FOR INFILTRATION AND THESE SPECIFICATIONS.
2. ENGINEERED SOIL MIX SHALL CONSIST OF A MIX OF 70 TO 85% SAND AND 15 TO 30% COMPOST BASED ON VOLUME. SAND SHALL MEET THE REQUIREMENTS FOR FINE AGGREGATE SAND SPECIFIED SECTION 501.2.5.3.4 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, LATEST EDITION OR MEET ASTM C33 (FINE AGGREGATE CONCRETE SAND).
3. PRIOR TO PLACEMENT IN THE BIOFILTRATION BASIN, THE ENGINEERED SOIL SHALL BE PREMIXED AND THE MOISTURE CONTENT SHALL BE LOW ENOUGH TO PREVENT CLUMPING AND COMPACTION DURING PLACEMENT.
4. THE ENGINEERED SOIL SHALL BE PLACED IN MULTIPLE LIFTS, EACH APPROXIMATELY 12 INCHES IN DEPTH.
5. ENGINEERED SOIL MIX SHALL BE FREE OF ROCKS, STUMPS, ROOTS, BRUSH OR OTHER MATERIAL OVER ONE INCH IN DIAMETER. NO OTHER MATERIALS SHALL BE MIXED WITH THEE PLANTING SOIL THAT MAY BE HARMFUL TO PLANT GROWTH OR BE A HINDRANCE TO PLANTING OR MAINTENANCE.
6. ENGINEERED SOIL AND GRAVEL SHALL BE IN ACCORDANCE WITH THE LATEST WDNr TECHNICAL STANDARD 1004.
7. PEA GRAVEL SHALL BE GRADED SUCH THAT MINIMUM PARTICLE SIZE IS LARGE ENOUGH TO PREVENT FALLING THROUGH PERFORATIONS OF THE UNDERDRAIN PIPE.
8. BIOFILTRATION BASIN DRAIN PIPE: 6-INCH CORRUGATED HDPE PIPE MEETING PERFORATION REQUIREMENTS OF AASHTO M278 HIGHWAY UNDERDRAIN SPECIFICATIONS WITH 3/8" PERFORATIONS ON 6" CENTERS WITH 4 HOLES PER ROW.
9. BEEHIVE INLET: NEENAH R-2561, OR EQUAL
10. RISER STRUCTURE: 48" DIAMETER PRECAST CATCH BASIN STRUCTURE WITH 24" TOP OPENING TO ACCOMMODATE BEEHIVE INLET. IN GENERAL ACCORDANCE WITH FILE NO. 26 OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN.
11. GRAVEL STORAGE LAYER (IF INDICATED ON PLANS): COURSE AGGREGATE #2 IN ACCORDANCE WITH SECTION 501.2.5.4.4 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION.
12. FILTER FABRIC: GEOTEXTILE FABRIC IN ACCORDANCE WITH SECTION 645.2.2.4 OF WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, LATEST EDITION
13. EXCAVATE TO GRADES AS INDICATED ON PLANS.
14. CONSTRUCT TEMPORARY DIVERSION SWALES OR PROVIDE OTHER MEANS AS NECESSARY TO PREVENT CONSTRUCTION SITE RUNOFF FROM DISTURBED AREAS, AND RUNOFF FROM PERVIOUS AREAS WHICH HAVE NOT YET BEEN STABILIZED, FROM ENTERING THE BIORETENTION AREA.
15. CONSTRUCTION SHALL BE SUSPENDED DURING PERIODS OF RAINFALL OR SNOWMELT. CONSTRUCTION SHALL REMAIN SUSPENDED IF PONDED WATER IS PRESENT OR IF RESIDUAL SOIL MOISTURE CONTRIBUTES SIGNIFICANTLY TO THE POTENTIAL FOR SOIL SMEARING, CLUMPING OR OTHER FORMS OF COMPACTION.
16. COMPACTION AND SMEARING OF THE ENGINEERED SOIL AND TOP SOIL BENEATH THE FLOORS, IN THE SOIL PLANTING BED, AND THE SIDE SLOPES OF THE BASIN, AND COMPACTION OF THE ENGINEERED SOILS IN THE BASIN SHALL BE MINIMIZED. DURING SITE DEVELOPMENT, THE AREA DEDICATED TO THE BIOFILTRATION BASIN SHALL BE CORDONED OFF TO PREVENT ACCESS BY HEAVY EQUIPMENT. ACCEPTABLE EQUIPMENT FOR CONSTRUCTING THE BIOFILTRATION BASIN INCLUDES EXCAVATION HOES, LIGHT EQUIPMENT WITH TURF TYPE TIRES, MARSH EQUIPMENT OR WIDE-TRACK LOADERS.
17. IF COMPACTION OCCURS AT THE BASE OF THE BIOFILTRATION BASIN, THE SOIL SHALL BE REFRACTURED TO A DEPTH OF AT LEAST 12 INCHES. IF SMEARING OCCURS, THE SMEARED AREAS OF THE INTERFACE SHALL BE CORRECTED BY RAKING OR ROTO-TILLING.
18. STEPS MAY BE TAKEN TO INDUCE MILD SETTLING OF THE ENGINEERED SOIL BED AS NEEDED TO PREPARE A STABLE PLANTING MEDIUM AND TO STABILIZE THE PONDING DEPTH. VIBRATING PLATE-STYLE COMPACTIONERS SHALL NOT BE UTILIZED.
19. ANY SEDIMENT ACCUMULATED IN THE BASIN DUE TO CONSTRUCTION ACTIVITIES SHOULD BE REMOVED AND THE ENGINEERED SOIL SHALL BE DEEP TILLED PRIOR TO PLANTING.
20. IMPERVIOUS LINER SHALL BE 45 MIL FIRESTONE EPDM (GSI PRODUCTS), OR 30 MIL PVC (GSI PRODUCTS), OR EQUAL.

**POROUS PAVEMENT:**


1. THE COMPOSITION, PLACING AND CONSTRUCTION OF ASPHALTIC PAVEMENTS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTIONS 450, 455, 460, 465, AND 475 OF THE STATE OF WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, LATEST EDITION (WISDOT STANDARD SPECIFICATIONS) AND WISCONSIN ASPHALT PAVEMENT ASSOCIATION (WAPA) POROUS ASPHALT PAVEMENTS TECHNICAL BULLETIN.
2. CONTRACTOR SHALL PROVIDE PRODUCT DATA FOR EACH TYPE OF PRODUCT INDICATED - INCLUDE TECHNICAL DATA AND TESTED PHYSICAL AND PERFORMANCE PROPERTIES; JOB-MIX DESIGNS: CERTIFICATION THAT MIX MEETS OR EXCEEDS WISDOT STANDARD SPECIFICATIONS; AND MATERIAL CERTIFICATES CERTIFYING COMPLIANCE WITH WISDOT STANDARD SPECIFICATIONS.
3. MANUFACTURER QUALIFICATIONS: MANUFACTURER SHALL BE REGISTERED WITH AND APPROVED BY THE DOT OF THE STATE IN WHICH PROJECT IS LOCATED.
4. ENVIRONMENTAL LIMITATIONS: DO NOT APPLY ASPHALT MATERIALS IF BASE COURSE IS WET OR EXCESSIVELY DAMP OR IF THE FOLLOWING CONDITIONS ARE NOT MET: APPLY TACK COAT WHEN AMBIENT TEMPERATURE IS ABOVE 50 DEGREES FAHRENHEIT AND WHEN TEMPERATURE HAS NOT BEEN BELOW 35 DEGREES FAHRENHEIT FOR 12 HOURS IMMEDIATELY PRIOR TO APPLICATION; PLACE ASPHALTIC CONCRETE SURFACE COURSE WHEN TEMPERATURE IS ABOVE 40 DEGREES FAHRENHEIT; BASE COURSE MAY BE PLACED WHEN AIR TEMPERATURE IS ABOVE 30 DEGREES FAHRENHEIT AND RISING. PROCEED WITH PAVEMENT MARKING ONLY ON CLEAN, DRY SURFACES. DO NOT APPLY BELOW THE MINIMUM PAVEMENT TEMPERATURE AS RECOMMENDED BY THE MANUFACTURER.
5. AGGREGATES SHALL BE IN ACCORDANCE WITH SECTION 460.2.2 OF THE WISDOT STANDARD SPECIFICATIONS AS MODIFIED BY THE WAPA POROUS ASPHALT PAVEMENTS TECHNICAL BULLETIN.
6. ASPHALT MATERIALS SHALL BE IN ACCORDANCE WITH CHAPTER 455 OF THE WISDOT STANDARD SPECIFICATIONS AS MODIFIED BY THE WAPA POROUS ASPHALT PAVEMENTS TECHNICAL BULLETIN.
7. PAVEMENT MARKING PAINT: PROVIDE PAINT FROM THE WISCONSIN DEPARTMENT OF TRANSPORTATION'S APPROVED PRODUCTS LIST. COLOR SHALL BE WHITE UNLESS INDICATED OTHERWISE ON PLANS.
8. POROUS ASPHALT: POROUS ASPHALT MIXES SHALL BE COMPATIBLE WITH WISDOT-APPROVED WARM-MIX ASPHALT TECHNOLOGIES. ASPHALTIC BINDER SHALL BE GRADE 28 IN ACCORDANCE WITH WAPA POROUS ASPHALTIC TECHNICAL BULLETIN.
9. AGGREGATE STORAGE RESERVOIR: USE A WASHED OR OPEN-GRADED BASE CONSISTING OF CRUSHED STONE OR CRUSHED GRAVEL WITH NO GREATER THAN 50% PASSING THE NO. 200 SIEVE. PROVIDE A MINIMUM POROSITY OF 30% PER ASTM C29 STANDARD TEST METHOD FOR BULK DENSITY AND VOIDS IN AGGREGATE. COMPLY WITH SOUNDNESS, WEAR, AND FRACTURE REQUIREMENTS LISTED IN WISCONSIN DOT STANDARD SPECIFICATION SECTION 301.2.4.5 - AGGREGATE BASE PHYSICAL PROPERTIES.
10. PAVEMENT PLACEMENT GENERAL: ASPHALT CONCRETE PAVING EQUIPMENT, WEATHER LIMITATIONS, JOB-MIX FORMULA, MIXING, CONSTRUCTION METHODS, COMPACTION, FINISHING, TOLERANCE AND PROTECTION SHALL CONFORM TO THE REQUIREMENTS OF THE APPROPRIATE SECTIONS OF THE WISDOT STANDARD SPECIFICATIONS AS MODIFIED BY THE WAPA POROUS ASPHALT PAVEMENTS TECHNICAL BULLETIN.
11. PREPARE AND PROOFROLL SUBGRADES AND AGGREGATE BASE COURSE AS OUTLINED IN EARTH MOVING SPECIFICATIONS PRIOR TO PLACEMENT OF ASPHALT PAVEMENTS. THE SLOPE OF THE SUBGRADE SHALL BE AS FLAT AS POSSIBLE BUT NO GREATER THAN 2%.
12. SWEEP LOOSE GRANULAR PARTICLES FROM SURFACE OF AGGREGATE BASE COURSE PRIOR TO PAVEMENT PLACEMENT. DO NOT DISLODGE OR DISTURB AGGREGATE EMBEDDED IN COMPACTED SURFACE OF BASE COURSE.
13. SPREAD AND FINISH ASPHALTIC MIXTURE IN ACCORDANCE WITH SECTION 450.3.2.5 OF THE WISDOT STANDARD SPECIFICATIONS AS MODIFIED BY THE WAPA POROUS PAVEMENTS TECHNICAL BULLETIN. PAVEMENT THICKNESSES SHALL BE AS INDICATED ON THE PLANS.
14. PROMPTLY CORRECT SURFACE IRREGULARITIES IN PAVING COURSE BEHIND PAVER. USE SUITABLE HAND TOOLS TO REMOVE EXCESS MATERIAL FORMING HIGH SPOTS. FILL DEPRESSIONS WITH POROUS ASPHALT TO PREVENT SEGREGATION OF MIX; USE SUITABLE HAND TOOLS TO SMOOTH SURFACE.
15. COMPACT ASPHALTIC PAVEMENT IN ACCORDANCE WITH SECTION 450.3.2.6 OF THE WISDOT STANDARD SPECIFICATIONS AS MODIFIED BY THE WAPA POROUS ASPHALT PAVEMENTS TECHNICAL BULLETIN. POROUS ASPHALT SHOULD BE COMPACTED WITH TWO TO FOUR PASSES OF A 10-TON ROLLER.
16. PROTECTION: AFTER FINAL ROLLING, DO NOT PERMIT VEHICULAR TRAFFIC ON PAVEMENT FOR AT LEAST 24 HOURS. ERECT BARRICADES TO PROTECT PAVING FROM TRAFFIC UNTIL MIXTURE HAS COOLED ENOUGH NOT TO BECOME MARKED.
17. THICKNESS TOLERANCE: COMPACT EACH COURSE TO PRODUCE THE THICKNESS INDICATED WITHIN PLUS/MINUS 1/4 INCH FOR BINDER COURSE AND PLUS 1/4 INCH FOR SURFACE COURSE, NO MINUS.
18. SURFACE SMOOTHNESS TOLERANCE: COMPACT EACH COURSE TO PRODUCE A SURFACE SMOOTHNESS WITHIN THE FOLLOWING TOLERANCES AS DETERMINED BY USING A 10-FOOT STRAIGHTEDGE APPLIED TRANSVERSELY OR LONGITUDINALLY TO PAVED AREAS: BINDER COURSE: 1/4 INCH; SURFACE COURSE: 1/8 INCH. REMOVE AND REPLACE ALL HUMPS OR DEPRESSIONS EXCEEDING THE SPECIFIED TOLERANCES.
19. DO NOT APPLY PAVEMENT-MARKING PAINT UNTIL LAYOUT, COLORS, AND PLACEMENT HAVE BEEN VERIFIED WITH ENGINEER.
20. APPLY MARKINGS TO A DRY SURFACE FREE FROM FROST. REMOVE DUST, DIRT, OIL, GREASE, GRAVEL, DEBRIS OR OTHER MATERIAL THAT MAY PREVENT BONDING TO THE PAVEMENT.
21. APPLY PAINT AS THE MANUFACTURER SPECIFIES WITH MECHANICAL EQUIPMENT TO PRODUCE PAVEMENT MARKINGS, OF DIMENSIONS INDICATED, WITH UNIFORM, STRAIGHT EDGES. APPLY AT MANUFACTURER'S RECOMMENDED RATES AT A MINIMUM RATE OF 17.6 GALLONS/MILE FOR A CONTINUOUS 4" LINE.
22. TESTING AGENCY: CONTRACTOR SHALL ENGAGE A QUALIFIED INDEPENDENT TESTING AND INSPECTING AGENCY TO PERFORM FIELD TESTS AND INSPECTIONS AND TO PREPARE TEST REPORTS.

DATE	DESCRIPTION




**SPECIFICATIONS**  
**1900 N 116TH STREET**  
**WAUWATOSA, WI 53226**


CONTRACT:	21231
FILE NO.:	JRG
DRAWN BY:	CTC
CHECKED BY:	AS SHOWN
SCALE:	<b>C502</b>



**LEGEND**

-  PROPERTY LINE
  -  RAISED CONCRETE CURB
  -  FLUSH CONCRETE CURB
  -  EXPANSION JOINT
  -  CONTROL JOINT
  -  THICKENED EDGE CONCRETE PAVEMENT
  -  STABILIZED AGGREGATE PAVING
  -  CONCRETE PAVEMENT
  -  PLAY TURF SURFACING W/ AGGREGATE SUBBASE
  -  PLAY TURF SURFACING W/ CONCRETE SUBBASE
  -  ENGINEERED WOOD FIBER
  -  BOULDERS
  -  STONE STEPPERS
  -  LAWN SEED MIX
  -  PERENNIALS AND ORNAMENTAL GRASSES
  -  LOW PRAIRIE SEED MIX
  -  BASIN SEED MIX
  -  EMERGENT SLOPE SEED MIX
  -  NO MOW LAWN SEED MIX
  -  SHADE TREE
  -  ORNAMENTAL TREE
  -  EVERGREEN TREE
  -  SHRUBS
  -  EXISTING TREES TO REMAIN AND BE PROTECTED
  -  HANDRAIL
  -  WOODEN PLATFORM
  -  TRASH RECEPTACLE
  -  RECYCLING RECEPTACLE
  -  BENCH SWINGS
  -  PICNIC TABLE, TYPE 1
  -  PICNIC TABLE, TYPE 2
  -  PICNIC TABLE, TYPE 3
  -  BENCH, TYPE 1
  -  BENCH, TYPE 2
  -  BENCH, TYPE 3
  -  GAME TABLE
  -  BIKE RACK
  -  HOT COAL RECEPTACLE
  -  ADA CLEARANCE
- NOTE:  
SEE SCHEDULES TO DETERMINE FURNISH AND INSTALLATION RESPONSIBILITIES

1 OVERALL SITE PLAN (FOR REFERENCE ONLY)  
1"= 80'-0"




CONTRACT:	DESCRIPTION
9509	
FILE NO:	
DN	
DRAWN BY:	
BK	
CHECKED BY:	
SCALE:	
<b>L002</b>	


  

DATE	DESCRIPTION

 <b>CITY OF WAUWATOSA</b> ENGINEERING SERVICES DIVISION	<b>1700 N 116TH STREET</b> <b>WAUWATOSA, WI 53226</b>
--	--







**LEGEND**

- PROPERTY LINE
- RAISED CONCRETE CURB
- FLUSH CONCRETE CURB
- EXPANSION JOINT
- CONTROL JOINT
- THICKENED EDGE CONCRETE PAVEMENT
- STABILIZED AGGREGATE PAVING
- CONCRETE PAVEMENT
- PLAY TURF SURFACING W/ AGGREGATE SUBBASE
- PLAY TURF SURFACING W/ CONCRETE SUBBASE
- ENGINEERED WOOD FIBER
- BOULDERS
- STONE STEPPERS
- LAWN SEED MIX
- PERENNIALS AND ORNAMENTAL GRASSES
- LOW PRAIRIE SEED MIX
- BASIN SEED MIX
- EMERGENT SLOPE SEED MIX
- NO MOW LAWN SEED MIX
- SHADE TREE
- ORNAMENTAL TREE
- EVERGREEN TREE
- SHRUBS
- EXISTING TREES TO REMAIN AND BE PROTECTED
- HANDRAIL
- WOODEN PLATFORM
- TRASH RECEPTACLE
- RECYCLING RECEPTACLE
- BENCH SWINGS
- PICNIC TABLE, TYPE 1
- PICNIC TABLE, TYPE 2
- PICNIC TABLE, TYPE 3
- BENCH, TYPE 1
- BENCH, TYPE 2
- BENCH, TYPE 3
- GAME TABLE
- BIKE RACK
- HOT COAL RECEPTACLE
- ADA CLEARANCE

**1** LANDSCAPE SITE PLAN  
1"=80'-0"



CONTRACT:	9509	DATE	DESCRIPTION
FILE NO:	DN		
DRAWN BY:	BK		
CHECKED BY:			
SCALE:			
<b>CITY OF WAUWATOSA</b>			
<b>ENGINEERING SERVICES DIVISION</b>			
<b>LANDSCAPE SITE PLAN</b> <b>1700 N 116TH STREET</b> <b>WAUWATOSA, WI 53226</b>			
			<b>L101</b>




**LEGEND**

- PROPERTY LINE
- RAISED CONCRETE CURB
- FLUSH CONCRETE CURB
- EXPANSION JOINT
- CONTROL JOINT
- THICKENED EDGE CONCRETE PAVEMENT
- STABILIZED AGGREGATE PAVING
- CONCRETE PAVEMENT
- PLAY TURF SURFACING W/ AGGREGATE SUBBASE
- PLAY TURF SURFACING W/ CONCRETE SUBBASE
- ENGINEERED WOOD FIBER
- BOULDERS
- STONE STEPPERS
- LAWN SEED MIX
- PERENNIALS AND ORNAMENTAL GRASSES
- LOW PRAIRIE SEED MIX
- BASIN SEED MIX
- EMERGENT SLOPE SEED MIX
- NO MOW LAWN SEED MIX
- SHADE TREE
- ORNAMENTAL TREE
- EVERGREEN TREE
- SHRUBS
- EXISTING TREES TO REMAIN AND BE PROTECTED
- HANDRAIL
- WOODEN PLATFORM
- TRASH RECEPTACLE
- RECYCLING RECEPTACLE
- BENCH SWINGS
- PICNIC TABLE, TYPE 1
- PICNIC TABLE, TYPE 2
- PICNIC TABLE, TYPE 3
- BENCH, TYPE 1
- BENCH, TYPE 2
- BENCH, TYPE 3
- GAME TABLE
- BIKE RACK
- HOT COAL RECEPTACLE
- ADA CLEARANCE

**1 LANDSCAPE SITE PLAN ENLARGEMENT**  
 1"=20'-0"



CONTRACT:	9509	DESCRIPTION:
FILE NO.:	DN	DATE:
DRAWN BY:	BK	
CHECKED BY:		
SCALE:		
<b>CITY OF WAUWATOSA</b>  <b>ENGINEERING SERVICES DIVISION</b>		
<b>THE SIGMA GROUP</b>  <b>site</b>		
<b>LANDSCAPE SITE PLAN ENLARGEMENT</b> <b>1700 N 116TH STREET</b> <b>WAUWATOSA, WI 53226</b>		
		<b>L101A.1</b>



**LEGEND**

	PROPERTY LINE
	RAISED CONCRETE CURB
	FLUSH CONCRETE CURB
	EXPANSION JOINT
	CONTROL JOINT
	THICKENED EDGE CONCRETE PAVEMENT
	STABILIZED AGGREGATE PAVING
	CONCRETE PAVEMENT
	PLAY TURF SURFACING W/ AGGREGATE SUBBASE
	PLAY TURF SURFACING W/ CONCRETE SUBBASE
	ENGINEERED WOOD FIBER
	BOULDERS
	STONE STEPPERS
	LAWN SEED MIX
	PERENNIALS AND ORNAMENTAL GRASSES
	LOW PRAIRIE SEED MIX
	BASIN SEED MIX
	EMERGENT SLOPE SEED MIX
	NO MOW LAWN SEED MIX
	SHADE TREE
	ORNAMENTAL TREE
	EVERGREEN TREE
	SHRUBS
	EXISTING TREES TO REMAIN AND BE PROTECTED
	HANDRAIL
	WOODEN PLATFORM
	TRASH RECEPTACLE
	RECYCLING RECEPTACLE
	BENCH SWINGS
	PICNIC TABLE, TYPE 1
	PICNIC TABLE, TYPE 2
	PICNIC TABLE, TYPE 3
	BENCH, TYPE 1
	BENCH, TYPE 2
	BENCH, TYPE 3
	GAME TABLE
	BIKE RACK
	HOT COAL RECEPTACLE

**1 LANDSCAPE PLAN ENLARGEMENT**  
1"=10'-0"


CONTRACT:	DATE	DESCRIPTION
9509		
FILE NO. DN		
DRAWN BY: BK		
CHECKED BY:		
SCALE:		

**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION

**THE SIGMA GROUP**  
Single Source. Sound Solutions.

**LANDSCAPE PLAN ENLARGEMENT**  
**1700 N 116TH STREET**  
**WAUWATOSA, WI 53226**


**L101A.2**




**LEGEND**

	PROPERTY LINE
	RAISED CONCRETE CURB
	FLUSH CONCRETE CURB
	EXPANSION JOINT
	CONTROL JOINT
	THICKENED EDGE CONCRETE PAVEMENT
	BOULDERS
	STONE STEPPERS
	WOODEN PLATFORM
	SPOT ELEVATIONS

**1 PLAYGROUND GRADING PLAN ENLARGEMENT**  
1"=10'-0"



CONTRACT: FILE NO: DRAWN BY: CHECKED BY: SCALE:	9509 DN BK	CITY OF <b>WAUWATOSA</b> ENGINEERING SERVICES DIVISION	
	PLAYGROUND GRADING PLAN ENLARGEMENT  1700 N 116TH STREET WAUWATOSA, WI 53226		
DATE	DESCRIPTION		
<b>L102A.2</b>			



**LEGEND**

- PROPERTY LINE
- RAISED CONCRETE CURB
- FLUSH CONCRETE CURB
- EXPANSION JOINT
- CONTROL JOINT
- THICKENED EDGE CONCRETE PAVEMENT
- STABILIZED AGGREGATE PAVING
- CONCRETE PAVEMENT
- PLAY TURF SURFACING W/ AGGREGATE SUBBASE
- PLAY TURF SURFACING W/ CONCRETE SUBBASE
- ENGINEERED WOOD FIBER
- BOULDERS
- STONE STEPPERS

DATE	DESCRIPTION

**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION


**THE SIGMA GROUP**  
Single Source. Sound Solutions.

**HARDSCAPE PLAN ENLARGEMENT**  
**1700 N 116TH STREET**  
**WAUWATOSA, WI 53226**

CONTRACT:	9509
FILE NO:	DN
DRAWN BY:	BK
CHECKED BY:	
SCALE:	

**L103A.1**

**1 HARDSCAPE PLAN ENLARGEMENT**  
1"= 20'-0"




FILE NAME:

PLOT DATE:

PLOTTED BY:

SHEET:




**LEGEND**

	PROPERTY LINE
	RAISED CONCRETE CURB
	FLUSH CONCRETE CURB
	EXPANSION JOINT
	CONTROL JOINT
	THICKENED EDGE CONCRETE PAVEMENT
	STABILIZED AGGREGATE PAVING
	CONCRETE PAVEMENT
	PLAY TURF SURFACING W/ AGGREGATE SUBBASE
	PLAY TURF SURFACING W/ CONCRETE SUBBASE
	ENGINEERED WOOD FIBER
	BOULDERS
	STONE STEPPERS


**1 HARDSCAPE PLAN ENLARGEMENT**  
1"= 10'-0"




CONTRACT:	DESCRIPTION
9509	
FILE NO.:	DATE
DN	
DRAWN BY:	
BK	
CHECKED BY:	
SCALE:	
<b>CITY OF WAUWATOSA</b>	
<b>ENGINEERING SERVICES DIVISION</b>	
<b>HARDSCAPE PLAN ENLARGEMENT</b>	
<b>1700 N 116TH STREET</b>	
<b>WAUWATOSA, WI 53226</b>	
<b>L103A.2</b>	



**LEGEND**


-  PROPERTY LINE
-  WOODEN PLATFORM
-  BENCH SWINGS
-  TRASH RECEPTACLE
-  RECYCLING RECEPTACLE
-  PICNIC TABLE, TYPE 1
-  PICNIC TABLE, TYPE 2
-  PICNIC TABLE, TYPE 3
-  BENCH, TYPE 1
-  BENCH, TYPE 2
-  BENCH, TYPE 3
-  GAME TABLE
-  BIKE RACK
-  HOT COAL RECEPTACLE
-  ADA CLEARANCE


**1 SITE FURNISHINGS PLAN ENLARGEMENT**  
1"= 20'-0"



CONTRACT:	DATE	DESCRIPTION
9509		
FILE NO.:		
DN		
DRAWN BY:		
BK		
CHECKED BY:		
SCALE:		
<b>L104A.1</b>		

<b>CITY OF WAUWATOSA</b> ENGINEERING SERVICES DIVISION	
	
	
<b>1700 N 116TH STREET</b> <b>WAUWATOSA, WI 53226</b>	



**LEGEND**

	PROPERTY LINE
	WOODEN PLATFORM
	BENCH SWINGS
	TRASH RECEPTACLE
	RECYCLING RECEPTACLE
	PICNIC TABLE, TYPE 1
	PICNIC TABLE, TYPE 2
	PICNIC TABLE, TYPE 3
	BENCH, TYPE 1
	BENCH, TYPE 2
	BENCH, TYPE 3
	GAME TABLE
	BIKE RACK
	HOT COAL RECEPTACLE
	ADA CLEARANCE

**1** PLAYGROUND EQUIPMENT ENLARGEMENT PLAN (FOR REFERENCE ONLY)  
1"=10'-0"



CONTRACT:	DATE	DESCRIPTION
9509		
FILE NO:		
DN		
DRAWN BY:		
BK		
CHECKED BY:		
SCALE:		

**PLAYGROUND EQUIPMENT ENLARGEMENT PLAN (FOR REFERENCE ONLY)**

**1700 N 116TH STREET  
WAUWATOSA, WI 53226**

**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION


**SIGMA GROUP**  
Single Source, Sound Solutions.

**site**

**L104A.2**







**LEGEND**

- PROPERTY LINE
- LAWN SEED MIX
- PERENNIALS AND ORNAMENTAL GRASSES
- LOW PRAIRIE SEED MIX
- BASIN SEED MIX
- EMERGENT SLOPE SEED MIX
- NO MOW TURF
- SHADE TREE
- ORNAMENTAL TREE
- EVERGREEN TREE
- SHRUBS
- EXISTING TREES TO REMAIN AND BE PROTECTED
- EXISTING TREE TO REMAIN

**1 NORTH TREES AND SHRUBS PLANTING PLAN ENLARGEMENT**  
1"= 30'-0"




CONTRACT:	DATE	DESCRIPTION
9509		
FILE NO: DN		
DRAWN BY: BK		
CHECKED BY:		
SCALE:		
<b>L106A</b>		
<b>CITY OF WAUWATOSA</b> ENGINEERING SERVICES DIVISION 		
<b>THE SIGMA GROUP</b> Single Source. Sound Solutions.		
<b>NORTH TREES AND SHRUBS PLANTING PLAN ENLARGEMENT</b> <b>1700 N 116TH STREET</b> <b>WAUWATOSA, WI 53226</b>		



**LEGEND**

- PROPERTY LINE
- LAWN SEED MIX
- PERENNIALS AND ORNAMENTAL GRASSES
- LOW PRAIRIE SEED MIX
- BASIN SEED MIX
- EMERGENT SLOPE SEED MIX
- NO MOW TURF
- SHADE TREE
- ORNAMENTAL TREE
- EVERGREEN TREE
- SHRUBS
- EXISTING TREES TO REMAIN AND BE PROTECTED
- EXISTING TREE TO REMAIN


**1 PLAYGROUND SHRUBS AND PERENNIALS PLANTING PLAN ENLARGEMENT**  
1" = 10'-0"



CONTRACT:	9509	DESCRIPTION	
FILE NO.:	DN	DATE	
DRAWN BY:	BK		
CHECKED BY:			
SCALE:			
<b>PLAYGROUND SHRUBS AND PERENNIALS PLANTING PLAN ENLARGEMENT</b> <b>1700 N 116TH STREET</b> <b>WAUWATOSA, WI 53226</b>		<b>CITY OF WAUWATOSA</b> <b>ENGINEERING SERVICES DIVISION</b>	
<b>L106A.1.1</b>			



1 PLANTING PLAN ENLARGEMENT  
1"= 30'-0"



**LEGEND**

- PROPERTY LINE
- LAWN SEED MIX
- PERENNIALS AND ORNAMENTAL GRASSES
- LOW PRAIRIE SEED MIX
- BASIN SEED MIX
- EMERGENT SLOPE SEED MIX
- NO MOW TURF
- SHADE TREE
- ORNAMENTAL TREE
- EVERGREEN TREE
- SHRUBS
- EXISTING TREES TO REMAIN AND BE PROTECTED
- EXISTING TREE TO REMAIN

CONTRACT:	DESCRIPTION
9509	
FILE NO: DN	
DRAWN BY: BK	
CHECKED BY: BK	
SCALE:	


PLANTING PLAN ENLARGEMENT  
1700 N 116TH STREET  
WAUWATOSA, WI 53226


**L106B**

**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION


**THE SIGMA GROUP**  
Single Source. Sound Solutions.




**LEGEND**


-  PROPERTY LINE
-  LAWN SEED MIX
-  PERENNIALS AND ORNAMENTAL GRASSES
-  LOW PRAIRIE SEED MIX
-  BASIN SEED MIX
-  EMERGENT SLOPE SEED MIX
-  NO MOW TURF
-  SHADE TREE
-  ORNAMENTAL TREE
-  EVERGREEN TREE
-  SHRUBS
-  EXISTING TREES TO REMAIN AND BE PROTECTED
-  EXISTING TREE TO REMAIN

1 **PLANTING PLAN ENLARGEMENT**  
1"= 30'-0"




CONTRACT:	DESCRIPTION
9509	
FILE NO:	DATE
DN	
BK	
SCALE:	
 <b>CITY OF WAUWATOSA</b> ENGINEERING SERVICES DIVISION	
 <b>THE SIGMA GROUP</b> Single Source. Sound Solutions.	
 <b>site</b>	
<b>PLANTING PLAN ENLARGEMENT</b> <b>1700 N 116TH STREET</b> <b>WAUWATOSA, WI 53226</b>	
<b>L106C</b>	






**X** PEDESTRIAN CONCRETE PAVING SECTION  
1" = 1'-0"


NOTES:  
1. X = 1/3 OF CONCRETE PAVING DEPTH




**X** PEDESTRIAN CONCRETE PAVING THICKENED EDGE SECTION  
1" = 1'-0"




**X** PEDESTRIAN CONCRETE PAVING W/ RAISED CONCRETE CURB SECTION  
1" = 1'-0"




**X** PEDESTRIAN AGGREGATE PAVING SECTION  
1" = 1'-0"




**X** SAWCUT CONTROL JOINT SECTION  
1" = 1'-0"




**X** EXPANSION JOINT SECTION  
1" = 1'-0"




**X** PLAY TURF SURFACING SECTION  
1" = 1'-0"



**X** PLAY TURF SURFACING W/ FLUSH CONCRETE CURB SECTION  
1" = 1'-0"



**X** PLAY TURF SURFACING AT BOTTOM OF BERM W/ THICKENED CONCRETE EDGE SECTION  
1" = 1'-0"



**X** PLAY TURF SURFACING AT TOP OF BERM SECTION  
1" = 1'-0"

DATE	DESCRIPTION

**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION



**ESIGMA** GROUP  
THE Single Source. Sound Solutions.

HARDSCAPE DETAILS  
1700 N 116TH STREET  
WAUWATOSA, WI 53226

CONTRACT NO:	9509
FILE NO:	DN
DRAWN BY:	BK
CHECKED BY:	
SCALE:	


**L503**





**1** SENSORY WALKING PATH KEY PLAN  
3/16" = 1'-0"

**2** RIVER ROCK SECTION  
1" = 1'-0"



**1A** SENSORY WALKING PATH SECTION  
1/2" = 1'-0"

DATE	DESCRIPTION

**CITY OF WAUWATOSA**  
ENGINEERING SERVICES DIVISION

**THE SIGMA GROUP**  
Single Source. Sound Solutions.

**HARDSCAPE DETAILS**  
1700 N 116TH STREET  
WAUWATOSA, WI 53226

CONTRACT:	9509
FILE NO:	DN
DRAWN BY:	BK
CHECKED BY:	
SCALE:	

**L503B**















NOTES:  
1. PROPOSED MFR, SEE SITE FURNISHINGS SCHEDULE.  
2. GC SHALL ENSURE LOGS DO NOT ROCK OR ROLL.

**LOG BEAM, SECTION**  
1" = 1'-0"


1



NOTES:  
1. PROPOSED MFR, SEE SITE FURNISHINGS SCHEDULE.  
2. GC SHALL ENSURE LOGS DO NOT ROCK OR ROLL.

**LOG STUMP STEPPERS, SECTION**  
1" = 1'-0"


2



NOTES:  
1. PROPOSED MFR, SEE SITE FURNISHINGS SCHEDULE.  
2. GC SHALL ENSURE LOGS DO NOT ROCK OR ROLL.

**LOG STUMP STEPPERS, SLOPED SECTION**  
1" = 1'-0"


3



NOTES:  
1. PROPOSED MFR, SEE SITE FURNISHINGS SCHEDULE.  
2. GC SHALL ENSURE LOGS DO NOT ROCK OR ROLL.

**LOG EDGING TO FLUSH CONCRETE CURB, SECTION**  
1" = 1'-0"


4



NOTES:  
1. PROPOSED MFR, SEE SITE FURNISHINGS SCHEDULE.


**LOG STUMP SEAT, SECTION**  
1" = 1'-0"

5




**WILLOW HUT SECTION**  
1" = 1'-0"

6




**PLAYGROUND SLIDE ELEVATION**  
1/2" = 1'-0"

7



**PLAY EQUIPMENT FOOTING DETAIL**  
1/2" = 1'-0"

8



**CLIMBING GRIP DETAIL**  
1-1/2" = 1'-0"

9

CONTRACT:	DESCRIPTION
FILE NO:	
DRAWN BY:	
CHECKED BY:	
SCALE:	
<b>CITY OF WAUWATOSA ENGINEERING SERVICES DIVISION</b>	
<b>PLAYGROUND DETAILS</b>	
<b>L504C</b>	







MOCKUPS	CODE	COMPONENT	SOURCE	MATERIAL	SIZE	COLOR	FINISH	NOTES	SHEET	DETAIL	SPECIFICATION
	PA-01	CONCRETE PAVING MOCKUP (10' x 10')	-	PROVIDE MOCKUP FOR EVERY TYPE PER SCHEDULE	FULL PROFILE PER DETAIL	PER SCHEDULE	PER SCHEDULE	PROVIDE EXAMPLES OF EACH UNIQUE CONDITION PER PLANS/DETAILS	L-X	X	XX XX XX
	SW-01	SENSORY WALK TYPE 1 MOCKUP (3' x 10')	-	PER SCHEDULE	FULL PROFILE PER DETAIL	SENSORY WALK TYPE 1	PER SCHEDULE	PROVIDE EXAMPLES OF EACH UNIQUE CONDITION PER PLANS/DETAILS	L-X	X	XX XX XX
	SW-02	SENSORY WALK TYPE 2 MOCKUP (3' x 10')	-	PER SCHEDULE	FULL PROFILE PER DETAIL	SENSORY WALK TYPE 2	PER SCHEDULE	PROVIDE EXAMPLES OF EACH UNIQUE CONDITION PER PLANS/DETAILS	L-X	X	XX XX XX
	PM-01	PAINTED WALK MOCKUP (3' x 10')	-	PER SCHEDULE	FULL PROFILE PER DETAIL	PAINTED WALK	PER SCHEDULE	PROVIDE EXAMPLES OF EACH UNIQUE CONDITION PER PLANS/DETAILS	L-X	X	XX XX XX

**STRUCTURES AND ASSEMBLIES**

CODE	FURNISH/INSTALL SCOPE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
BD-1	OF-CI	RESTROOM BUILDING	[Owner Furnished] 6707 E. Flamingo Ave. Bldg 300 Nampa, ID 83687	Precast concrete flush toilet building	Denali CXT Standard Building	19'-8 x 10'-3" x 13'-0" H	N/A	N/A	N/A	N/A	[Owner Furnished] REQUIRED	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE	CF-CI	FOUNDATION	N/A	Concrete Footing	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ST-01	OF-CI	PICNIC SHELTER	[Owner Furnished] Gerber Leisure Products, Inc. Contact: Meghan Barrett p. 605-514-5323 meghan@gerberleisure.com	Steel Frame Shelter	MP25x30S-P3	25' x 30' x 15'-2.3" H	N/A	N/A	N/A	N/A	[Owner Furnished] REQUIRED	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE	CF-CI	CONCRETE FOOTING	N/A	Concrete Footing	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ST-02	OF-CI	BENCH SWINGS	[Owner Furnished] Landscape Forms Studio 431 7800 E. Michigan Ave Kalamazoo, MI 49048 Contact: Jennifer Woods P. 800.430.6206 x 1336 jenniferw@landscapeforms.com	Steel Frame	2-Bay Austin Cantilever Structure with Perforated Metal Roof	Per Manufacturer 19' L	N/A	N/A	N/A	N/A	N/A	N/A	L-X	X
ASSEMBLY COMPONENT FOR ITEM ABOVE	CF-CI	CONCRETE FOOTING	N/A	Concrete Footing	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

**WALLS**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
REFER TO CIVIL	CF-CI	RETAINING WALL	REFER TO CIVIL	MODULAR BLOCK MSE RETAINING WALLS	REFER TO CIVIL	SEE DETAIL(S)	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REQUIRED	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL

**CURBS**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
CB-01	CF-CI	RAISED CONCRETE CURB	N/A	CIP Concrete Barrier Curb w/ Rebar Reinforcement	N/A	SEE DETAIL(S)	Light Broom	Cauked Snap Cap Expansion Joints w/ Saw-cut Control Joints	N/A	N/A	N/A	L503	X
CB-02	CF-CI	FLUSH CONCRETE CURB	N/A	CIP Concrete Flush Curb w/ Rebar Reinforcement	N/A	SEE DETAIL(S)	Light Broom	Cauked Snap Cap Expansion Joints w/ Saw-cut Control Joints	N/A	N/A	N/A	L503	X

**PAVING**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
PA-01	CF-CI	CONCRETE PAVEMENT	N/A	CIP Concrete w/ Steel Mesh Reinforcement	N/A	5" THK	Light Broom	Cauked Snap Cap Expansion Joints w/ Saw-cut Control Joints	N/A	N/A	N/A	L503	1
ASSEMBLY COMPONENT FOR ITEM ABOVE	CF-CI	THICKENED EDGE CONCRETE PAVING	N/A	N/A	N/A	X	N/A	N/A	N/A	N/A	N/A	L503	X
PA-02	CF-CI	STABILIZED AGGREGATE PAVING	Kafka Granite 550 East Hwy 153 Mosinee, WI 54455	Stabilized Stone Aggregate Paving	X	3" THK	N/A	N/A	REQUIRED	N/A	N/A	L503	X
PA-03	OF-ON	PLAY TURF SURFACING	Forever Lawn 8007 Season St Louisville, OH 44641 p. 866.992.7879	Protective Play Surface, Synthetic Turf	Playground Grass	X	X	N/A	REQUIRED	REQUIRED	X	L503	X
ASSEMBLY COMPONENT FOR ITEM ABOVE	CF-CI	SITE PREP: GRADING, SUBBASE, AGGREGATE CONCRETE BASE	N/A	N/A	N/A	N/A	N/A	N/A	X	N/A	N/A	N/A	N/A
PA-04	CF-CI	ENGINEERED WOOD FIBER	X	Protective Play Surface, Engineered Wood Fiber	X	12" THK	N/A	N/A	X	N/A	N/A	L503A	1
SW-01	CF-CI	SENSORY WALK TYPE 1	N/A	X	X	12" THK	N/A	'Advanced' Sensory Walk.	REQUIRED	REQUIRED	REQUIRED	L-X	X
SW-02	CF-CI	SENSORY WALK TYPE 2	N/A	X	X	12" THK	N/A	'Intermediate' Sensory Walk.	REQUIRED	REQUIRED	REQUIRED	L-X	X
PM-01	CF-CI	PAINTED WALK	X	Pavement Markings	StreetBond SB 150AL with primer	SEE DETAIL(S)	SW 6939 - Turquoise SW 6921 - Electric Lime SW 6839 Kimono Violet SW 6926 - Lucky Green	N/A	N/A	REQUIRED	REQUIRED	L-X	X
REFER TO CIVIL	CF-CI	ADA TACTILE WARNING TILES	REFER TO CIVIL	Tactile Warning Surfacing	REFER TO CIVIL	2' x 5'	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL
REFER TO CIVIL	CF-CI	POROUS ASPHALTIC PAVEMENT	REFER TO CIVIL	POROUS ASPHALTIC PAVEMENT	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL	REFER TO CIVIL

**DECKING**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
DK-01	CF-CI	NATURE PLAY WOOD PLATFORM	N/A	Wood Decking and Framing, Robinia	N/A	SEE DETAIL(S)	N/A	N/A	N/A	REQUIRED	N/A	L504A	X

**WOOD EDGING**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
WE-01	CF-CI	WOOD LOG EDGE TYPE 1	N/A	Robinia Wood Log	N/A	SEE DETAIL(S)	N/A	Vertical Log	N/A	REQUIRED	N/A	L504A	X
WE-02	CF-CI	WOOD LOG EDGE TYPE 2	N/A	Robinia Wood Log	N/A	SEE DETAIL(S)	N/A	Horizontal Log	N/A	REQUIRED	N/A	L504A	X

**FENCES**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
REFER TO CIVIL	CF-CI	8' HT CHAIN LINK	N/A	REFER TO CIVIL	REFER TO CIVIL	Black	Yinyl Coating	N/A	N/A	N/A	N/A	REFER TO CIVIL	REFER TO CIVIL

**GATES**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
REFER TO CIVIL	CF-CI	ACCESS GATE (SWNG)	N/A	REFER TO CIVIL	REFER TO CIVIL	Black	Yinyl Coating	N/A	N/A	N/A	N/A	REFER TO CIVIL	REFER TO CIVIL

**HANDRAILS**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
HR-01	CF-CI	SENSORY WALK HANDRAIL	N/A	Stainless Steel Pipe Handrail	N/A	1.5" OD PIPE	X	N/A	N/A	Required	N/A	L-X	X
ASSEMBLY COMPONENT FOR ITEM ABOVE	CF-CI	CONCRETE FOOTING	N/A	Concrete Footing	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

**NATURAL STONE**

CODE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
NS-01	OF-CI	BOULDERS	OWNER PROVIDED	N/A	N/A	N/A	N/A	Coordinate and install owner provided boulders	N/A	N/A	N/A	L503A	N/A
NS-02	OF-CI	STONE STEPPERS	OWNER PROVIDED	N/A	N/A	N/A	N/A	Coordinate and install owner provided stone steppers	N/A	N/A	N/A	L503A	N/A

FILE NAME:

PLOT DATE:

PLOTTED BY:

SHEET:

DESCRIPTION	
DATE	
	
	
<p><b>HARDSCAPE SCHEDULE</b></p> <p><b>1700 N 116TH STREET</b></p> <p><b>WAUWATOSA, WI 53226</b></p>	
CONTRACT:	9509
FILE NO.:	DN
DRAWN BY:	BK
CHECKED BY:	BK
SCALE:	L603

PLAY EQUIPMENT															
CODE	UNIT	FURNISH/INSTALL SCOPE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
PG-01	LS	OF-CI	PLAYGROUND EQUIPMENT	[Owner Furnished] Gerber Leisure Products, Inc. Contact: Meghan Barrett p. 608-514-6323 meghan@gerberleisure.com	N/A	Landscape Structures, Inc. Freestanding System Project ID: 23091802	See LSI Drawing #23092802-02	N/A	N/A	Owner Furnished, Contractor Installed	N/A	N/A	N/A	L504C	(for reference only)
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE FOOTINGS	N/A	Concrete Footing	N/A	Per Manufacturer	N/A	N/A	N/A	N/A	N/A	N/A	L504B	3
SIGNAGE															
CODE	UNIT	FURNISH/INSTALL SCOPE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
REFER TO CIVL	EA	CF-CI	GENERAL SIGNAGE	N/A	ALUMINUM PANEL SIGN, PAINT AND VINYL GRAPHICS,	N/A	N/A	N/A	N/A	PROVIDE AND INSTALL SIGNS WHERE SHOWN ON PLANS INCLUDING ADA. FURNISH AND INSTALL POSTS, SIGNS, FOOTINGS, INCLUDING HARDWARE	N/A	REQUIRED	N/A	REFER TO CIVL	
MS-1	EA		ENTRY SIGN	X	PRECAST CONCRETE WALL WITH CUSTOM METAL FABRICATED SIGNAGE	N/A	16' L x 1'-11" W x 4' H	N/A	N/A	X	REQUIRED	REQUIRED	N/A	L503D L503E	ALL
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE FOOTING	N/A	Concrete Footing	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503E	1
BIKE RACKS															
CODE	UNIT	FURNISH/INSTALL SCOPE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
BR-01	EA	OF-OI	BIKE RACKS	[Owner Furnished] Wadix Graber Manufacturing, Inc. Waukesha, WI 53597	Powder Coated Steel	3 Hoop on Rail L190-6-P	21" W x 36" H x 66" L	Patriot Blue	Powder Coat	Surface Mount	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
FURNITURE															
CODE	UNIT	FURNISH/INSTALL SCOPE	COMPONENT	SOURCE	MATERIAL	MODEL	SIZE	COLOR	FINISH	NOTES	SAMPLE	SHOP DRAWING	MOCKUP	SHEET	DETAIL
BN-01	EA	OF-CI	BENCH TYPE 1	[Owner Furnished] Wausau Tile P.O. BOX 1520 Wausau, WI 64402 www.wausautile.com	Precast Concrete	TF5117	48" L, 18" W, 18" HT,	N/A	N/A	Surface Mount	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
BN-02	EA	OF-OI	BENCH TYPE 2	[Owner Furnished] Thomas Steele Division of Graber Manufacturing, Inc. 1080 Unitek Drive, Waukesha, WI 53597 P 800.241.2505, F 608.849.1081	Steel Frame Recycled Plastic Slats	6 Ft Walden Circle Arm Bench	76" L x 31" H x 24" W	Walnut (Slats) Storm Metallic (Frame)	Powder Coated	Surface Mount	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
BN-03	EA	OF-CI	BENCH TYPE 3	[Owner Furnished] Wausau Tile P.O. BOX 1520 Wausau, WI 64402 www.wausautile.com	Precast Concrete	TF5116	Arc: Total Length 73-1/2"; 18" Seat Width 18" HT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
TB-01	EA	OF-OI	PICNIC TABLE- TYPE 1	[Owner Furnished] Wausau Tile P.O. BOX 1520 Wausau, WI 64402 www.wausautile.com	Precast Concrete	TF3128	66" L x 64" W x 30" H	Darkest Gray A38y	Standard Ground and Acid Wash Legs	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
TB-02	EA	OF-OI	PICNIC TABLE- TYPE 2	[Owner Furnished] Wausau Tile P.O. BOX 1520 Wausau, WI 64402 www.wausautile.com	Precast Concrete	TF3125	66" DIA x 30" H	Darkest Gray A38y	Standard Ground and Polish Top and Bench, Acid Wash Legs	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
TB-03	EA	OF-OI	PICNIC TABLE- TYPE 3	[Owner Furnished] Kay Park Recreation 1301 Pine St Janesville, IA 50647 P. 866.741.8266	Galvanized Steel Pipe Frame Composite Slats	J2 Series	8' L	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
TB-04	EA	OF-OI	GAME TABLE	[Owner Furnished] Wausau Tile P.O. BOX 1520 Wausau, WI 64402 www.wausautile.com	Precast Concrete	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
TR-01	EA	OF-OI	MESH TRASH RECEPTACLES	[Owner Furnished] Kay Park Recreation 1301 Pine St Janesville, IA 50647 P. 866.741.8266	Steel Mesh	52 Gallon	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
TR-02	EA	OF-OI	TRASH RECEPTACLES, TYPE 1	[Owner Furnished] Max-R W248 N5499 Executive Drive Sussex, WI 53089 P. 855.204.3560	HDPE Recycled Plastic	Infinity Round Rivited	55 Gallon	Black	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
TR-03	EA	OF-OI	RECYCLING RECEPTACLE	[Owner Furnished] Max-R W248 N5499 Executive Drive Sussex, WI 53089 P. 855.204.3560	HDPE Recycled Plastic	Infinity Round Rivited	N/A	Blue	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1
CR-01	EA	OF-OI	HOT COAL RECEPTACLE	[Owner Furnished] Kay Park Recreation 1301 Pine St Janesville, IA 50647 P. 866.741.8266	Precast Concrete	Concrete Hot Ash Receptacle SKU: CHAR2235	22" x 22" x 35" H	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ASSEMBLY COMPONENT FOR ITEM ABOVE		CF-CI	CONCRETE BASE	N/A	SEE CONCRETE PAVEMENT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	L503	1

FILE NAME:

PLOT DATE:


PLOTTED BY:

SHEET:

CONTRACT:	9509
FILE NO.:	DN
DRAWN BY:	BK
CHECKED BY:	
SCALE:	

**L604**

CITY OF WAUWATOSA  
ENGINEERING SERVICES DIVISION




SITE FURNISHINGS SCHEDULE

1700 N 116TH STREET  
WAUWATOSA, WI 53226

Code	Nursery	Trees	Common Name	Mature Size	Purchase Size	Quantity	Unit Price	Total
<b>SHADE TREES</b>								
CE.OC	Johnson's	<i>Celtis occidentalis</i>	Common Hackberry	40' ht x 60' spread	#5 container	6	\$ 99.00	\$ 594.00
FA.GR	Johnson's	<i>Fagus granifolia</i>	American Beech	60' ht x 55' spread	1.5"	7	\$ 285.00	\$ 1,995.00
LI.TU	Wayside	<i>Liriodendron tulipifera</i>	Tulip Tree	80' ht x 45' spread	1.75"	8	\$ 195.00	\$ 1,560.00
PO.GR	Johnson's	<i>Populus grandidentata</i>	Big-tooth Aspen	60' ht x 14' spread	#5 container	13	\$ 45.00	\$ 585.00
QU.BI	Johnson's	<i>Quercus bicolor</i>	Swamp White Oak	75' ht x 65' spread	#25 container	5	\$ 195.00	\$ 975.00
QU.MA	Johnson's	<i>Quercus macrocarpa</i>	Bur Oak	60' ht x 60' spread	#25 container	13	\$ 195.00	\$ 2,535.00
						52		\$ 15,047.00
<b>ORNAMENTAL TREES</b>								
AM.AU		<i>Amelanchier x grandiflora</i> 'Autumn Brilliance'	Autumn Brilliance Serviceberry	15' ht x 25' spread	#5 container	18		
BE.CU	Wayside	<i>Betula nigra</i> 'Cully'	Heritage River Birch	40' tall x 40' wide (multi-stem)	6'	5	\$ 144.00	\$ 720.00
CA.CA	Wayside	<i>Carpinus caroliniana</i>	Musclewood	25' ht x 25' spread	2"	18	\$ 215.00	\$ 3,870.00
CA.SP	Wayside	<i>Catalpa speciosa</i>	Northern Catalpa	40' ht x 30' spread	1.75"	13	\$ 150.00	\$ 1,950.00
CE.CA	Wayside	<i>Cercis canadensis</i>	Redbud	20' ht x 25' spread (multi-stem)	6'	9	\$ 192.00	\$ 1,728.00
CE.JA	Wayside	<i>Cercidiphyllum japonicum</i>	Katsura Tree	50' ht x 20' spread	1.75"	5	\$ 199.00	\$ 995.00
CO.AL	Wayside	<i>Cornus alternifolia</i>	Pagoda Dogwood	15' ht x 15' spread	4'	16	\$ 92.00	\$ 1,472.00
CO.MA	Wayside	<i>Cornus mas</i>	Corneliancherry Dogwood	20' ht x 15' spread (tree-form)	1.75"	20	\$ 167.00	\$ 3,340.00
CR.CR		<i>Crataegus crus-galli</i>	Cockspur Hawthorn	20-30' ht x 25-35' spread	#5 container	6	\$ 108.00	\$ 648.00
MA.BU	Wayside	<i>Magnolia</i> 'Butterflies'	Magnolia 'Butterflies'	20' ht x 20' spread	1.75"	7	\$ 230.00	\$ 1,610.00
MA.LE	Wayside	<i>Magnolia</i> 'Leonard Messel'	Magnolia 'Leonard Messell'	15' ht x 20' spread (multi-stem)	5'	9	\$ 180.00	\$ 1,620.00
PO.TR	Wayside	<i>Populus tremuloides</i>	Quaking Aspen	40' ht x 25' spread (multi-stem)	8'	20	\$ 170.00	\$ 3,400.00
						128		\$ 21,353.00
<b>EVERGREEN TREES</b>								
JU.CO	Johnson's	<i>Juniper communis</i>	Old Field Common Juniper	4'h x 10' spread	#2 container	50	\$ 27.00	\$ 1,350.00
JU.VI	Johnson's	<i>Juniperus virginiana</i>	Eastern Redcedar	30-40'ht x 8-20' spread	#5 container	56	\$ 50.00	\$ 2,800.00
LA.LA	Johnson's	<i>Larix laricina</i>	Tamarack	30-50' ht x 10-15' spread	#10 container	28	\$ 93.00	\$ 2,604.00
ME.GL	Wayside	<i>Metasequoia glyptostroboides</i>	Dawn Redwood	75' ht x 15-25' spread	2"	4	\$ 170.00	\$ 680.00
PI.AB	Wayside	<i>Picea abies</i>	Norway Spruce		6'	50	\$ 250.00	\$ 12,500.00
TH.ST	Wayside	<i>Thuja plicata</i> 'Standishii'	Green Giant Arborvitae	60' ht x 12-20' spread	5'	34	\$ 160.00	\$ 5,440.00
						222		\$ 15,047.00
<b>SHRUBS</b>								
CE.AM	Midwest	<i>Ceanothus americanus</i>	New Jersey Tea	2-3' ht x 4' spread	#3 container	40	\$ 19.75	\$ 790.00
CO.SE	Midwest	<i>Cornus sericea</i>	Red osier Dogwood	6' ht x 6' spread	#5 container	18	\$ 19.25	\$ 346.50
DI.G2	Midwest	<i>Diervilla x 'G2X88544'</i>	Kodiak Orange Diervilla	4' ht x 4' spread	#3 container	65	\$21.75	\$ 1,413.75
DI.JE	Johnson's	<i>Diervilla lanicera</i> 'Jewell'	Jewel Honeysuckle	4' ht x 4' spread	#2 container	77	\$ 17.00	\$ 1,309.00
DI.SM	Midwest	<i>Diervilla rivularis</i> 'SMNDRSF'	Kodiak Black Diervilla	4' ht x 4' spread	#3 container	26	\$21.75	\$ 565.50
FO.NI	Midwest	<i>Forsythia x 'NIMBUS'</i>	Sugar Baby Forsythia	24" ht x 4' spread	#3 container	62	\$ 21.75	\$ 1,348.50
HA.VI	Midwest	<i>Hamamelis virginiana</i>	Common Witchhazel	12' ht x 12' spread	#5 container	24	\$ 29.50	\$ 708.00
PH.PO	Midwest	<i>Physocarpus opulifolius</i> 'Podaras 3'	Lemon Candy Ninebark	2.5' ht x 3' spread	#5 container	40	\$ 25.50	\$ 1,020.00
RH.BA	Midwest	<i>Rhus typhina</i> 'Bailtiger'	Tiger Eye Sumac	10'ht x 10' spread	#5 container	9	\$ 25.50	\$ 229.50
RH.TY	Midwest	<i>Rhus typhina</i>	Staghorn Sumac	12' ht x 20' spread	#5 container	80	\$ 24.25	\$ 1,940.00
SP.CO	Wayside	<i>Spiraea betulifolia</i> 'COURISPI01'	Pink Sparkler Spirea	4' ht x 4' spread	18"	43	\$ 21.00	\$ 903.00
SY.BL	Midwest	<i>Syringa x 'Bloomerang Lilac'</i>	Bloomerang Lilac dark purple	4' ht x 4' spread	#3 container	11	\$ 22.50	\$ 247.50
						495		\$ 10,821.25
<b>FORBS</b>								
AL.SU	Radtke	<i>Allium 'Summer Beauty'</i>	Summer Beauty Allium	18"ht x 12" spread	#1 container	57	\$ 7.25	\$ 413.25
AM.CA	Radtke	<i>Amarpha canescens</i>	Lead Plant	3'ht x 4' spread	quart	21	\$ 6.25	\$ 131.25
AS.TU	Radtke	<i>Asclepias tuberosa</i>	Butterfly Weed	2'ht x 12" spread	#1 container	69	\$ 7.50	\$ 517.50
BA.TW	Radtke	<i>Baptisia x varicolor</i> 'Twilite'	Twilite Prairieblues Baptisia	24" ht x 4' spread	#1 container	34	\$ 10.50	\$ 357.00
BA.VA	Radtke	<i>Baptisia Decadence</i> 'Vanilla Cream'	Baptisia Vanilla Cream	24" ht x 4' spread	#1 container	19	\$ 14.00	\$ 266.00
CA.MO	Radtke	<i>Calamintha nepeta</i> 'Montrose White'	Montrose White Catmint	18"ht x 24" spread	#1 container	82	\$ 6.50	\$ 533.00
EU.BA	Radtke	<i>Eupatorium dubium</i> 'Baby Joe'	Baby Joe-pye Weed	2'ht x 2' spread	quart	36	\$ 4.00	\$ 144.00
HE.BE	Radtke	<i>Hemerocallis</i> 'Bela Lugosi' (sub)	Bela Lugosi Daylily (sub)	28" ht x 1.5' spread	#1 container	71	\$ 10.00	\$ 710.00
HE.HY	Radtke	<i>Hemerocallis</i> 'Hyperion'	Hyperion Daylily	3' ht x 1.5' spread	#1 container	74	\$ 7.50	\$ 555.00
HI.CR	Midwest	<i>Hibiscus Summerific</i> 'Cranberry Crush'	Cranberry Crush Hibiscus	3' ht x 4' spread	#2 container	7	\$ 13.95	\$ 97.65
RU.LI	Radtke	<i>Rudbeckia fulgida</i> var. <i>sullivantii</i> 'Little Goldstar'	Little Goldstar Black-eyed Susan	14" x 14"	#1 container	107	\$ 10.00	\$ 1,070.00
SA.CA	Radtke	<i>Salvia nemerosa</i> 'Caradonna'	Caradonna Salvia	24" ht x 24" spread	#1 container	67	\$ 6.50	\$ 435.50
SA.MA	Radtke	<i>Salvia nemerosa</i> 'Mainacht'	May Night Salvia	18" ht x 24" spread	#1 container	35	\$ 6.50	\$ 227.50
ST.HU	Radtke	<i>Stachys monieri</i> 'Hummelo'	Hummelo Lamb's Ear	20" ht x 20" spread	#1 container	51	\$ 6.50	\$ 331.50
						730		\$ 5,789.15
<b>GRASSES</b>								
AN.GE	Radtke	<i>Andropogon gerardii</i>	Big Bluestem	4' ht x 24" spread	#1 container	91	\$ 6.25	\$ 568.75
CH.LA	Radtke	<i>Chasmanthium latifolium</i>	Northern Sea Oats	30" ht x 12" spread	#1 container	47	\$ 6.25	\$ 293.75
PA.SH	Radtke	<i>Panicum virgatum</i> 'Shenandoah'	Shenandoah Switch Grass	4' ht x 2' spread	#1 container	61	\$ 9.50	\$ 579.50
SC.SC	Radtke	<i>Schizachyrium scoparium</i>	Little Bluestem	2' ht x 12" spread	#1 container	163	\$ 7.00	\$ 1,141.00
SE.AU	Radtke	<i>Sesleria autumnalis</i>	Autumn Moor Grass	3' ht x2' spread	#1 container	117	\$ 9.50	\$ 1,111.50
						479		\$ 3,694.50
<b>SEED MIXES</b>								
		<i>Lawn Turf</i>			SF	109100		
	Agrecol	<i>Low Prairie Seed Mix</i>			SF	51,800		
		<i>No Mow Turf</i>			SF	55900		
	Agrecol	<i>Basin Seed Mix</i>			SF	13600		
	Agrecol	<i>Emergent Slope Mix</i>			SF	12,600		
		<i>Mulch area/planting bed</i>			SF	16170		

DESCRIPTION

DATE




PLANTING SCHEDULE

1700 N 116TH STREET  
WAUWATOSA, WI 53226

CONTRACT: 9509  
FILE NO: DN  
DRAWN BY: BK  
CHECKED BY: BK  
SCALE:


L606



**LEGEND**


-  PROPERTY LINE
-  AREA TO BE IRRIGATED
-  SHADE TREE
-  ORNAMENTAL TREE
-  EVERGREEN TREE
-  EXISTING TREES TO REMAIN AND BE PROTECTED
-  EXISTING TREE TO REMAIN

1 AREAS TO BE IRRIGATED  
1"=30'-0"



CONTRACT:	FILE NO:	DATE	DESCRIPTION
9509	DN		
DRAWN BY:	DN		
CHECKED BY:	BK		
SCALE:			
<b>L1000</b>			
 			
<b>AREAS TO BE IRRIGATED</b> <b>1700 N 116TH STREET</b> <b>WAUWATOSA, WI 53226</b>			
		<b>CITY OF WAUWATOSA</b> <b>ENGINEERING SERVICES DIVISION</b>	

ABBREVIATIONS		LIGHTING LEGEND		POWER LEGEND		GENERAL LEGEND		GENERAL NOTES		
AC	ALTERNATING CURRENT	NIC	NOT INCLUDED IN CONTRACT	⊕	SINGLE RECEPTACLE	□	NEW ELECTRICAL COMPONENT	<p>1. DRAWINGS ARE DIAGRAMMATIC AND DO NOT SHOW ALL REQUIRED COMPONENTS FOR A COMPLETE INSTALLATION. CONTRACTOR SHALL FURNISH AND INSTALL MATERIAL EQUIPMENT, DEVICES, FIXTURES, SERVICE REQUIREMENTS NECESSARY TO CONFORM TO THE STRUCTURE, EQUIPMENT CONNECTIONS, FOR A COMPLETE AND FUNCTIONAL INSTALLATION AND SHALL MAINTAIN APPROPRIATE CLEARANCES.</p> <p>2. ALL WORK SHALL COMPLY WITH APPLICABLE NATIONAL, STATE, LOCAL CODES, FEDERAL AND STATE REGULATIONS, AND ALL REQUIREMENTS OF THE LOCAL AUTHORITIES HAVING JURISDICTION.</p> <p>3. CONTRACTOR SHALL COORDINATE WORK WITH ALL OTHER TRADES PRIOR TO INSTALLATION.</p> <p>4. THE CONTRACTOR SHALL VISIT THE SITE TO DETERMINE THE FULL EXTENT OF WORK AND PROJECT CONDITIONS. FAILURE TO DO SO WILL NOT RELIEVE THE CONTRACTOR OF THE OBLIGATIONS OF THE CONTRACT.</p> <p>5. THE CONTRACTOR SHALL CHECK ALL DRAWINGS AND SPECIFICATIONS OF OTHER TRADES AND INCLUDE IN THEIR BID ANY ADDITIONAL WORK REQUIRED BY THIS TRADE.</p> <p>6. CONTRACTOR SHALL VERIFY ALL EQUIPMENT CONNECTION CONFIGURATIONS BEFORE PURCHASE. ALL DEVICES SHOWN ARE FOR REFERENCE ONLY. TO COMMUNICATE DESIGN INTENT, FINAL LOCATIONS SHALL BE VERIFIED PRIOR TO INSTALLATION. THIS NOTE SHALL APPLY TO, BUT NOT BE LIMITED TO, RECEPTACLES, SWITCHES, DATA PORTS, AUDIO/VIDEO DEVICES, AND TELEPHONE JACKS.</p> <p>7. CONDUCTOR SIZES INDICATED ARE MINIMUM SIZES BASED ON 60°C COPPER CONDUCTOR 100 AMPS OR LESS AND 75°C COPPER CONDUCTOR GREATER THAN 100 AMPS. CAPACITIES OF CONDUCTORS DO NOT TAKE VOLTAGE DROP INTO CONSIDERATION. CONTRACTOR SHALL SIZE CONDUCTORS FOR FEEDERS AND BRANCH CIRCUITS TO PREVENT A VOLTAGE DROP EXCEEDING 3 PERCENT AT THE FARTHEST OUTLET OF POWER, HEATING, AND LIGHTING LOADS, OR COMBINATION OF SUCH LOADS, AND WHERE THE MAXIMUM TOTAL VOLTAGE DROP ON BOTH FEEDERS AND BRANCH CIRCUITS TO THE FARTHEST OUTLET DOES NOT EXCEED 5 PERCENT, TO PROVIDE REASONABLE EFFICIENCY OF OPERATION.</p>	DATE	DESCRIPTION
AFF	ABOVE FINISHED FLOOR	NL	NIGHT LIGHT	⊕ <sub>3</sub>	THREE WAY WALL SWITCH	□	EXISTING ELECTRICAL COMPONENT			
AFG	ABOVE FINISHED GRADE	NO	NORMALLY OPEN	⊕ <sub>4</sub>	FOUR WAY WALL SWITCH	⊕	DEMOLISHED ELECTRICAL COMPONENT			
AHJ	AUTHORITY HAVING JURISDICTION	NTS	NOT TO SCALE	⊕ <sub>D</sub>	DIMMING SWITCH	⊕ <sub>6"</sub>	KEY NOTE			
AIC	AMPERE INTERRUPTING CAPACITY			⊕ <sub>D3</sub>	THREE WAY DIMMING SWITCH	⊕ <sub>6"</sub>	TYPICAL CIRCUIT			
ALT	ALTERNATE	OC	ON CENTER	⊕ <sub>D4</sub>	FOUR WAY DIMMING SWITCH	⊕ <sub>6"</sub>	UNSWITCHED CIRCUIT			
AMP	AMPERE	OD	OUTSIDE DIAMETER	⊕ <sub>SD</sub>	STEP DIMMING SWITCH	⊕ <sub>6"</sub>				
AOR	AREA OF REFUGE	OL	OVERLOAD	⊕ <sub>K</sub>	KEYED SWITCH	⊕ <sub>6"</sub>				
AORM	AREA OF REFUGE MASTER STATION	OS	OPTIONAL STANDBY	⊕ <sub>K3</sub>	THREE WAY KEYED SWITCH	⊕ <sub>6"</sub>				
AORR	AREA OF REFUGE REMOTE STATION			⊕ <sub>K4</sub>	FOUR WAY KEYED SWITCH	⊕ <sub>6"</sub>				
ATS	AUTOMATIC TRANSFER SWITCH	P	POLE	⊕ <sub>SS</sub>	DUAL LEVEL SWITCH	⊕ <sub>6"</sub>				
AUTO	AUTOMATIC	PA	PUBLIC ADDRESS	⊕ <sub>SS</sub>	SWITCH STATION	⊕ <sub>6"</sub>				
AV	AUDIO VISUAL	PB	PUSHBUTTON	⊕ <sub>OS</sub>	WALL MOUNT OCCUPANCY SENSOR	⊕ <sub>6"</sub>				
BLDG	BUILDING	PC	PLUMBING CONTRACTOR	⊕ <sub>OS</sub>	CEILING MOUNT OCCUPANCY SENSOR	⊕ <sub>6"</sub>				
BOT	BOTTOM	PE	PHOTOELECTRIC CELL, PHOTOEYE	⊕ <sub>VS</sub>	SWITCH-BOX VACANCY SENSOR	⊕ <sub>6"</sub>				
C	CONDUIT	PED	PEDESTAL	⊕ <sub>VS</sub>	WALL MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CAB	CABINET	PEND	PENDANT	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CATV	COMMUNITY ANTENNA TELEVISION	PF	POWER FACTOR	⊕ <sub>VS</sub>	WALL MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CB	CIRCUIT BREAKER	PH	PHASE	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CCTV	CLOSED CIRCUIT TELEVISION	PL	PILOT LIGHT	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CD	CANDELA OR CONSTRUCTION DOCUMENT	PNL	PANEL	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CKT	CIRCUIT	PWR	POWER	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CLG	CEILING	RC	REMOTE CONTROL	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
COAX	COAXIAL CABLE	RCP	REFLECTED CEILING PLAN	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CP	CONTROL PANEL	REC	RECESSED	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CT	CURRENT TRANSFORMER	RECP	RECEPTACLE	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
CU	COPPER	SCC	SHORT CIRCUIT CAPACITY	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
dB	DECIBEL	SF	SQUARE FOOT (FEET)	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DB	DIRECT BURIAL	SPD	SURGE PROTECTION DEVICE SPECIFICATION	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DEMO	DEMOLITION	SPEC	SPECIFICATION	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DISC	DISCONNECT	SPST	SINGLE POLE, SINGLE THROW SWITCH STATION	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DIST	DISTRIBUTION	SW	SWITCH	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DM	DIMMING	T	TAMPERPROOF	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DN	DOWN	TC	TIMECLOCK	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DPDT	DOUBLE POLE, DOUBLE THROW	TV	TELEVISION	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DPST	DOUBLE POLE, SINGLE THROW	TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSION	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DS	DAYLIGHT SENSOR	TYP	TYPICAL	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
DWG	DRAWING			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
EBU	EMERGENCY BATTERY UNIT	UL	UNDERWRITERS LABORATORY	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
EC	ELECTRICAL CONTRACTOR	UNV	UNIVERSAL	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
ELEV	ELEVATOR	UPS	UNINTERRUPTIBLE POWER SUPPLY	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
EM	EMERGENCY	V	VOLT	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
ENCL	ENCLOSURE	VA	VOLT AMPERE	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
ER	ELEVATOR RECALL	VAC	VOLT AMPERE CURRENT	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
ERL	EXISTING TO BE RELOCATED	VFD	VARIABLE FREQUENCY DRIVE	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
ES	ELECTRIC STRIKE	W	WATT OR WIRE	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
ETR	EXISTING TO REMAIN	WAP	WIRELESS ACCESS POINT	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FA	FIRE ALARM	WP	WEATHERPROOF	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FAAP	FIRE ALARM ANNUNCIATOR PANEL			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FACP	FIRE ALARM CONTROL PANEL	X-	EXISTING	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FC	FOOT-CANDLE	XFER	TRANSFER	⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FLA	FULL LOAD AMPERE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FP	FIRE PROTECTION			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FSS	FUSED SAFETY SWITCH			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FVNR	FULL VOLTAGE NON-REVERSING			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
FVR	FULL VOLTAGE REVERSING			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
GEN	GENERATOR			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
GRD	GROUND			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
GC	GENERAL CONTRACTOR			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
GFI / GFCI	GROUND FAULT CIRCUIT INTERRUPTER			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
HID	HIGH INTENSITY DISCHARGE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
HOA	HAND-OFF-AUTO			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
HP	HORSE POWER			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
HZ	HERTZ			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
IG	INSULATED GROUND			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
K	KEY OPERATED			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
JB	JUNCTION BOX			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
KV	KILOVOLT			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
KVA	KILOVOLT AMPERE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
KW	KILOWATT			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
KWH	KILOWATT HOUR			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
LCP	LIGHTING CONTROL PANEL			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
LED	LIGHT EMITTING DIODE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
LF	LINEAR FOOT (FEET)			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
LM	LUMEN			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
LPS	LOW PRESSURE SODIUM			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
LRA	LOCKED ROTOR AMPERAGE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
LTG	LIGHTING			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
LV	LOW VOLTAGE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MAG	MAGNETIC STARTER			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MAN	MANUAL STARTER			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MATV	MASTER ANTENNA TELEVISION SYSTEM			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MC	MECHANICAL CONTRACTOR			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MCA	MINIMUM CIRCUIT AMPACITY			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MCB	MAIN CIRCUIT BREAKER			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MFG	MANUFACTURER			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MH	MANHOLE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MOCPP	MAXIMUM OVERCURRENT PROTECTION			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MLO	MAIN LUG ONLY			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MTD	MOUNTED			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MTS	MANUAL TRANSFER SWITCH			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
MV	MEDIUM VOLTAGE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
N	NEUTRAL			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
NA	NOT APPLICABLE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
NAC	NOTIFICATION APPLIANCE CIRCUIT			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
NC	NORMALLY CLOSED			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
NEC	NATIONAL ELECTRICAL CODE			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
NFPA	NATIONAL FIRE PROTECTION AGENCY			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				
NFSS	NON-FUSED SAFETY SWITCH			⊕ <sub>VS</sub>	CEILING MOUNT VACANCY SENSOR	⊕ <sub>6"</sub>				



**ELECTRICAL LEGEND AND NOTES**


1900 N 116TH STREET  
WAUWATOSA, WI 53226

CONTRACT NO:	21231
FILE NO:	FA
DRAWN BY:	DH
CHECKED BY:	AS SHOWN
SCALE:	E000



**NOT FOR CONSTRUCTION**





### LIGHTING FIXTURE SCHEDULE


FIXT.	DESCRIPTION	TYPE	INPUT		VOLT	MANUFACTURER	CATALOG NUMBER	MOUNTING	SEE NOTE
			W						
OF1	FLOODLIGHT	18,000 LUMEN, 3000K	170W		120V	LITHONIA	DSXF3 LED-P2-30K-70CRI-MSP-[VOLTAGE]-[MOUNTING]-[OPTIONS]-DBLXD	POLE	3
OP1	AREA HEAD	3700 LUMEN, 3000K	22W		SOLAR	SUNNA DESIGN	SL4249-1-[LIGHTING PROFILE]-290-RL204-3-120-2-27	POLE	1,2
OP2	AREA HEAD	3700 LUMEN, 3000K	22W		SOLAR	SUNNA DESIGN	SL4249-1-[LIGHTING PROFILE]-290-RL204-3-120-2-07	POLE	1,2
OP3	AREA HEAD	33,000 LUMEN, 3000K	277W		120V	LITHONIA	DSX1 LED-P9-30K-70CRI-TM-[VOLTAGE]-[MOUNTING]-[OPTIONS]-DBLXD	POLE	3

**REMARKS:**

- CATALOG NUMBERS ARE TO PROVIDE GUIDANCE ONLY AND MAY NOT BE COMPLETE.
- FIXTURES SPECIFIED TO MEET DESIGN INTENT. EQUALS MAY BE SUBSTITUTED SUBJECT TO DESIGN TEAM'S APPROVAL WITH PROOF OF SYSTEM PERFORMANCE VIA CALCULATION AND PRODUCT DOCUMENTATION.
- PROVIDE ALL PARTS AND PIECES NECESSARY FOR A COMPLETE AND FUNCTIONAL INSTALLATION.
- ARCHITECT TO DETERMINE ALL FINISHES.
- VERIFY DIMMING CONTROLS ARE COMPATIBLE WITH DIMMING DRIVER SELECTED FOR FIXTURE.
- POLE HEIGHTS SHALL NOT EXCEED 25 FEET AFG.

**NOTES:**

- SOLAR SYSTEM SHALL BE CONFIGURED AND AIMED PER MANUFACTURER'S GUIDELINES.
- POLES FOR SOLAR FIXTURES ARE INCLUDED TOGETHER AS A UNIT WITH SOLAR PANELS, LIGHTING FIXTURES, AND BATTERIES.
- POLES FOR HARD WIRED FIXTURES SHALL BE PROVIDED BASED ON THE COMPLETE INSTALLATION OF ALL LIGHT FIXTURES AND MOUNTING EQUIPMENT AS DIRECTED BY FIXTURE MANUFACTURER. MANUFACTURER SHALL PROVIDE SHOP DRAWING FOR THIS INSTALLATION.



### 3 LIGHT POLE BASE

N.T.S.

POLE HEIGHT	BASE EMBEDMENT / DIAMETER			
	EPA 2.0 FT <sup>2</sup> OR LESS	EPA 4.0 FT <sup>2</sup> TO 2.1 FT <sup>2</sup>	EPA 6.0 FT <sup>2</sup> TO 4.1 FT <sup>2</sup>	EPA 6.1 FT <sup>2</sup> OR GREATER
15'-0"	6'5 1/2"-6"	6'5 1/2"-6"	6'5 1/2"-6"	6'5 1/2"-6"
20'-0"	6'5 1/2"-6"	6'5 1/2"-6"	8'-0 1/2"-6"	8'-0 1/2"-6"
25'-0"	6'5 1/2"-6"	8'-0 1/2"-6"	9'-0 1/2"-6"	10'-0 1/2"-6"
30'-0"	8'-0 1/2"-6"	9'-0 1/2"-6"	10'-0 1/2"-6"	10'-0 1/2"-6"

**NOTES:**


- TABLE IS BASED ON SOIL BEARING PRESSURE OF 300 PSF.

### 2 SLED PUSHBUTTON/STROBE DETAIL

N.T.S.

### PARK SERVICE ENCLOSURE EQUIPMENT LIST

- FREE-STANDING 3" GALVANIZED PIPE AND STAINLESS STEEL UNISTRUT (BACK-TO-BACK DOUBLE CHANNEL P1001 SERIES) SUPPORT FRAME FOR MOUNTING ELECTRICAL EQUIPMENT. PROVIDE A MINIMUM OF (2) PIPES. TOP OF PIPES TO BE CAPPED. INSTALL SUPPORT FRAME PIPES THRU CORE-DRILLED HOLES IN CONCRETE PAD.
- UTILITY APPROVED 100A, 120/240V, 1φ, 3W OUTDOOR TRANSOCKET WITH METER SOCKET MOUNTED ON COVER. MOUNT TRANSOCKET TO FREE-STANDING 3" GALVANIZED PIPE (MINIMUM OF 3 CAPPED PIPES) AND STAINLESS STEEL UNISTRUT SUPPORT FRAME. INSTALL SUPPORT FRAME PIPES THRU CORE-DRILLED HOLES IN CONCRETE PAD.
- 24 CKT., 120/240V, 1φ, 3-WIRE PANELBOARD WITH 100A MAIN BREAKER-SQUARE D TYPE NO. PANEL TO BE TYPE NEMA 3R ENCLOSURE. ENCLOSURE TO HAVE HASP FOR PADLOCK. REFER TO PANELS SCHEDULE FOR MORE INFORMATION.
- PROVIDE GRAVEL A MINIMUM OF 12" DEEP BELOW PAD AND EXTENDING 12" OUT FROM EDGES OF PAD.
- 20A, 120V DOUBLE-DUPLEX GFCI WEATHER RESISTANT RECEPTACLES, WITH WEATHERPROOF "WHILE-IN-USE" COVER.



### 1 ELECTRICAL SERVICE EQUIPMENT

N.T.S.

#### PANEL NAME: A

LOCATION:	Sled hill	VOLTS:	120/240	AIC RATING:	10,000 MIN. EC TO VERIFY
SUPPLY FROM:	Utility	PHASES:	1	MAINS TYPE:	MCB
MOUNTING:	Surface	WIRES:	3	BUS RATING:	100
ENCLOSURE:	Type 3R			MCB RATING:	100

POLE NO.	POLES	AMP	DESCRIPTION	NOTES	A	B	DESCRIPTION	NOTES	AMP	POLES	POLE NO.
1	1	20	RECEPT		720			SPARE	20	1	2
3	1	20	LIGHTS			1234		SPARE	20	1	4
5	1	20	SPARE					SPARE	20	1	6
7											8
9											10
11											12
13											14
15											16
17											18
19											20
21											22
23											24
PHASE TOTAL:					720	0					
TOTAL LOAD:					720	0					

**NOTES:**

- GFI BREAKER
- SHUNT TRIP BREAKER

#### PANEL NAME: R

LOCATION:	Restroom	VOLTS:	120/240	AIC RATING:	10,000 MIN. EC TO VERIFY
SUPPLY FROM:	Utility	PHASES:	1	MAINS TYPE:	MCB
MOUNTING:	Surface	WIRES:	3	BUS RATING:	100
ENCLOSURE:	Type 3R			MCB RATING:	100

POLE NO.	POLES	AMP	DESCRIPTION	NOTES	A	B	DESCRIPTION	NOTES	AMP	POLES	POLE NO.
1	1	20	RECEPT					SPARE	20	1	2
3	1	20	LIGHTS					SPARE	20	1	4
5	1	20	SPARE					SPARE	20	1	6
7											8
9											10
11											12
13											14
15											16
17											18
19											20
21											22
23											24
PHASE TOTAL:					0	0					
TOTAL LOAD:					0	0					

**NOTES:**

- GFI BREAKER
- SHUNT TRIP BREAKER

**NOT FOR CONSTRUCTION**

CONTRACT:	21231
FILE NO.:	FA
DRAWN BY:	DH
CHECKED BY:	AS SHOWN
SCALE:	E500

**ELECTRICAL SCHEDULES**

1900 N 116TH STREET  
WAUWATOSA, WI 53226

CITY OF WAUWATOSA  
ENGINEERING SERVICES DIVISION

THE SIGMA GROUP  
Single Source, Sound Solutions

